HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminaire Photometric Data


Description Information

Luminary Name: HCP-1022122+HCP-1032122 5000K 15D		Lum. Catelog:	Test ID: 01
Lamp Name:		Lamp Catelog: LED	Test Date: 2020/12/03
Manufacture: Havit Commercial		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency(Hz):	Lamp CCT(K): Ra:
Lum.Size(W*L*H):0.000m*0.000m*0.000m		Lum.Area(m2):0.000	Lum.W(kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp.(℃): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 564.670	Luminary Flux(lm): 564.675	Field Angle(10%Imax): 38.6(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 564.675lm 100.00%
Rated Voltage(V):	Luminary EER(lm/W): 59.054	Up Lumens&Percent: 0.000lm 0.00%
Tested Power(W): 9.562	Max.Candela(cd): 3965.658	S/MH: C0_a180=0.313 C90_270=0.319
Lamps' Inside: 1	Max Cand@Ang.(°): C=90.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics(V,A,pf):240.4,0.043,0.912	Beam Angle(50%Imax): 18.5(°)	ErP Φuse(90°): 560.257lm
Lamp Size(W*L*H):0.000m*0.000m*0.000m	Left=-8.7° ,Right=9.8°	IRF(%): 1328.894

C Plane Distribution Diagram




C0 Space ISO Illuminance Curve



HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

2D Plane Light Intensity Distribution Curve

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03




HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Light Intensity Distribution Modal

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

3D Light Intensity Distribution Modal



Curves: 3D Model Fixture Vert. HUD Hori. HUD
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	3.76	3.76	0.67	0.67	47.0-48.0	0.00	564.67	0.00	100.00
1.0-2.0	11.12	14.88	1.97	2.63	48.0-49.0	0.00	564.67	0.00	100.00
2.0-3.0	18.02	32.90	3.19	5.83	49.0-50.0	0.00	564.67	0.00	100.00
3.0-4.0	24.16	57.06	4.28	10.11	50.0-51.0	0.00	564.67	0.00	100.00
4.0-5.0	29.23	86.29	5.18	15.28	51.0-52.0	0.00	564.67	0.00	100.00
5.0-6.0	32.96	119.24	5.84	21.12	52.0-53.0	0.00	564.67	0.00	100.00
6.0-7.0	35.21	154.45	6.24	27.35	53.0-54.0	0.00	564.67	0.00	100.00
7.0-8.0	36.03	190.48	6.38	33.73	54.0-55.0	0.00	564.67	0.00	100.00
8.0-9.0	35.55	226.03	6.30	40.03	55.0-56.0	0.00	564.67	0.00	100.00
9.0-10.0	34.14	260.17	6.05	46.08	56.0-57.0	0.00	564.67	0.00	100.00
10.0-11.0	32.14	292.31	5.69	51.77	57.0-58.0	0.00	564.67	0.00	100.00
11.0-12.0	29.84	322.16	5.29	57.05	58.0-59.0	0.00	564.67	0.00	100.00
12.0-13.0	27.50	349.65	4.87	61.92	59.0-60.0	0.00	564.67	0.00	100.00
13.0-14.0	25.17	374.83	4.46	66.38	60.0-61.0	0.00	564.67	0.00	100.00
14.0-15.0	22.87	397.69	4.05	70.43	61.0-62.0	0.00	564.67	0.00	100.00
15.0-16.0	20.63	418.32	3.65	74.08	62.0-63.0	0.00	564.67	0.00	100.00
16.0-17.0	18.49	436.81	3.27	77.36	63.0-64.0	0.00	564.67	0.00	100.00
17.0-18.0	16.49	453.31	2.92	80.28	64.0-65.0	0.00	564.67	0.00	100.00
18.0-19.0	14.67	467.98	2.60	82.88	65.0-66.0	0.00	564.67	0.00	100.00
19.0-20.0	13.05	481.03	2.31	85.19	66.0-67.0	0.00	564.67	0.00	100.00
20.0-21.0	11.60	492.63	2.05	87.24	67.0-68.0	0.00	564.67	0.00	100.00
21.0-22.0	10.30	502.93	1.82	89.07	68.0-69.0	0.00	564.67	0.00	100.00
22.0-23.0	9.11	512.04	1.61	90.68	69.0-70.0	0.00	564.67	0.00	100.00
23.0-24.0	8.03	520.07	1.42	92.10	70.0-71.0	0.00	564.67	0.00	100.00
24.0-25.0	7.04	527.12	1.25	93.35	71.0-72.0	0.00	564.67	0.00	100.00
25.0-26.0	6.15	533.27	1.09	94.44	72.0-73.0	0.00	564.67	0.00	100.00
26.0-27.0	5.34	538.61	0.94	95.38	73.0-74.0	0.00	564.67	0.00	100.00
27.0-28.0	4.58	543.19	0.81	96.20	74.0-75.0	0.00	564.67	0.00	100.00
28.0-29.0	3.91	547.10	0.69	96.89	75.0-76.0	0.00	564.67	0.00	100.00
29.0-30.0	3.33	550.44	0.59	97.48	76.0-77.0	0.00	564.67	0.00	100.00
30.0-31.0	2.83	553.27	0.50	97.98	77.0-78.0	0.00	564.67	0.00	100.00
31.0-32.0	2.40	555.66	0.42	98.41	78.0-79.0	0.00	564.67	0.00	100.00
32.0-33.0	2.03	557.70	0.36	98.76	79.0-80.0	0.00	564.67	0.00	100.00
33.0-34.0	1.70	559.40	0.30	99.07	80.0-81.0	0.00	564.67	0.00	100.00
34.0-35.0	1.41	560.80	0.25	99.32	81.0-82.0	0.00	564.67	0.00	100.00
35.0-36.0	1.13	561.94	0.20	99.52	82.0-83.0	0.00	564.67	0.00	100.00
36.0-37.0	0.88	562.81	0.16	99.67	83.0-84.0	0.00	564.67	0.00	100.00
37.0-38.0	0.65	563.46	0.11	99.79	84.0-85.0	0.00	564.67	0.00	100.00
38.0-39.0	0.46	563.92	0.08	99.87	85.0-86.0	0.00	564.67	0.00	100.00
39.0-40.0	0.33	564.25	0.06	99.93	86.0-87.0	0.00	564.67	0.00	100.00
40.0-41.0	0.22	564.47	0.04	99.96	87.0-88.0	0.00	564.67	0.00	100.00
41.0-42.0	0.13	564.60	0.02	99.99	88.0-89.0	0.00	564.67	0.00	100.00
42.0-43.0	0.06	564.66	0.01	100.00	89.0-90.0	0.00	564.67	0.00	100.00
43.0-44.0	0.02	564.67	0.00	100.00	90.0-91.0	0.00	564.67	0.00	100.00
44.0-45.0	0.00	564.67	0.00	100.00	91.0-92.0	0.00	564.67	0.00	100.00
45.0-46.0	0.00	564.67	0.00	100.00	92.0-93.0	0.00	564.67	0.00	100.00
46.0-47.0	0.00	564.67	0.00	100.00	93.0-94.0	0.00	564.67	0.00	100.00

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Zonal Flux Tabulation - (Cont.)


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	564.67	0.00	100.00
95.0-96.0	0.00	564.67	0.00	100.00
96.0-97.0	0.00	564.67	0.00	100.00
97.0-98.0	0.00	564.67	0.00	100.00
98.0-99.0	0.00	564.67	0.00	100.00
99.0-100.0	0.00	564.67	0.00	100.00
100.0-101.0	0.00	564.67	0.00	100.00
101.0-102.0	0.00	564.67	0.00	100.00
102.0-103.0	0.00	564.67	0.00	100.00
103.0-104.0	0.00	564.67	0.00	100.00
104.0-105.0	0.00	564.67	0.00	100.00
105.0-106.0	0.00	564.67	0.00	100.00
106.0-107.0	0.00	564.67	0.00	100.00
107.0-108.0	0.00	564.67	0.00	100.00
108.0-109.0	0.00	564.67	0.00	100.00
109.0-110.0	0.00	564.67	0.00	100.00
110.0-111.0	0.00	564.67	0.00	100.00
111.0-112.0	0.00	564.67	0.00	100.00
112.0-113.0	0.00	564.67	0.00	100.00
113.0-114.0	0.00	564.67	0.00	100.00
114.0-115.0	0.00	564.67	0.00	100.00
115.0-116.0	0.00	564.67	0.00	100.00
116.0-117.0	0.00	564.67	0.00	100.00
117.0-118.0	0.00	564.67	0.00	100.00
118.0-119.0	0.00	564.67	0.00	100.00
119.0-120.0	0.00	564.67	0.00	100.00
120.0-121.0	0.00	564.67	0.00	100.00
121.0-122.0	0.00	564.67	0.00	100.00
122.0-123.0	0.00	564.67	0.00	100.00
123.0-124.0	0.00	564.67	0.00	100.00
124.0-125.0	0.00	564.67	0.00	100.00
125.0-126.0	0.00	564.67	0.00	100.00
126.0-127.0	0.00	564.67	0.00	100.00
127.0-128.0	0.00	564.67	0.00	100.00
128.0-129.0	0.00	564.67	0.00	100.00
129.0-130.0	0.00	564.67	0.00	100.00
130.0-131.0	0.00	564.67	0.00	100.00
131.0-132.0	0.00	564.67	0.00	100.00
132.0-133.0	0.00	564.67	0.00	100.00
133.0-134.0	0.00	564.67	0.00	100.00
134.0-135.0	0.00	564.67	0.00	100.00
135.0-136.0	0.00	564.67	0.00	100.00
136.0-137.0	0.00	564.67	0.00	100.00
137.0-138.0	0.00	564.67	0.00	100.00
138.0-139.0	0.00	564.67	0.00	100.00
139.0-140.0	0.00	564.67	0.00	100.00
140.0-141.0	0.00	564.67	0.00	100.00

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
141.0-142.0	0.00	564.67	0.00	100.00
142.0-143.0	0.00	564.67	0.00	100.00
143.0-144.0	0.00	564.67	0.00	100.00
144.0-145.0	0.00	564.67	0.00	100.00
145.0-146.0	0.00	564.67	0.00	100.00
146.0-147.0	0.00	564.67	0.00	100.00
147.0-148.0	0.00	564.67	0.00	100.00
148.0-149.0	0.00	564.67	0.00	100.00
149.0-150.0	0.00	564.67	0.00	100.00
150.0-151.0	0.00	564.67	0.00	100.00
151.0-152.0	0.00	564.67	0.00	100.00
152.0-153.0	0.00	564.67	0.00	100.00
153.0-154.0	0.00	564.67	0.00	100.00
154.0-155.0	0.00	564.67	0.00	100.00
155.0-156.0	0.00	564.67	0.00	100.00
156.0-157.0	0.00	564.67	0.00	100.00
157.0-158.0	0.00	564.67	0.00	100.00
158.0-159.0	0.00	564.67	0.00	100.00
159.0-160.0	0.00	564.67	0.00	100.00
160.0-161.0	0.00	564.67	0.00	100.00
161.0-162.0	0.00	564.67	0.00	100.00
162.0-163.0	0.00	564.67	0.00	100.00
163.0-164.0	0.00	564.67	0.00	100.00
164.0-165.0	0.00	564.67	0.00	100.00
165.0-166.0	0.00	564.67	0.00	100.00
166.0-167.0	0.00	564.67	0.00	100.00
167.0-168.0	0.00	564.67	0.00	100.00
168.0-169.0	0.00	564.67	0.00	100.00
169.0-170.0	0.00	564.67	0.00	100.00
170.0-171.0	0.00	564.67	0.00	100.00
171.0-172.0	0.00	564.67	0.00	100.00
172.0-173.0	0.00	564.67	0.00	100.00
173.0-174.0	0.00	564.67	0.00	100.00
174.0-175.0	0.00	564.67	0.00	100.00
175.0-176.0	0.00	564.67	0.00	100.00
176.0-177.0	0.00	564.67	0.00	100.00
177.0-178.0	0.00	564.67	0.00	100.00
178.0-179.0	0.00	564.67	0.00	100.00
179.0-180.0	0.00	564.67	0.00	100.00

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Rectangle ISO Lighting Intensity Diagram

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03




Maximum Light Intensity(cd): 3965.66
Maximum Cand.@Angle: H=0.0°,V=1.0°

Plane ISO-Illuminance Diagram

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 440.43
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Plane ISO Illuminance Diagram

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

3D Plane Illuminance Modal




Curves: 3D Model 90% 80% 70% 60% 50% 40% 30% 20% 10%
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Space ISO Illuminance Diagram

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

Space ISO Illuminance Curve




Space Plane Maximum Illuminance and @Angle:3935.94lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:3937.741cd,0eg

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Illuminance-Distance Diagram

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03



Beam Angle:18.5

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminance Limiting Curves

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03


Glare Grade Table

GI	Quality	Using Illuminace							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	0	0	0	0	0	0	0	0	0
C90	0	0	0	0	0	0	0	0	0

Luminance Limiting Curve




Luminous Size: Length(m)=0.000 Width(m)=0.000 Height(m)=0.000 Area(m^2)=0.000000
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Budgetary Estimate Table

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Coefficient of Utilization Table

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC(%)	80				70				50			30			10			0
RhoW(%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97
2	112	109	106	104	110	107	105	102	104	102	100	101	100	98	99	97	96	95
3	109	105	101	99	107	103	100	98	101	98	96	99	97	95	97	95	94	92
4	106	101	98	95	104	100	97	94	98	95	93	96	94	92	95	93	91	90
5	103	98	94	92	102	97	94	91	96	93	90	94	92	90	93	91	89	88
6	101	95	91	89	100	94	91	88	93	90	88	92	89	87	91	89	87	86
7	98	93	89	86	97	92	89	86	91	88	86	90	87	85	89	87	85	84
8	96	90	87	84	95	90	86	84	89	86	84	88	85	83	87	85	83	82
9	94	88	84	82	93	88	84	82	87	84	82	86	83	81	86	83	81	80
10	92	86	83	80	91	86	82	80	85	82	80	85	82	80	84	81	80	79

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Unified Glare Rating Table

Lum.Name: HCP-1022122+HCP-1032122 5000K 15D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/12/03

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	-2.7	-1.9	-2.4	-1.5	-1.2	-2.7	-1.9	-2.4	-1.5	-1.2
	Y=3H	-3.0	-2.2	-2.6	-1.8	-1.5	-3.0	-2.2	-2.6	-1.8	-1.5
	Y=4H	-3.1	-2.4	-2.7	-2.0	-1.6	-3.1	-2.4	-2.7	-2.0	-1.6
	Y=6H	-3.2	-2.5	-2.8	-2.2	-1.8	-3.2	-2.5	-2.8	-2.2	-1.8
	Y=8H	-3.3	-2.6	-2.8	-2.2	-1.8	-3.3	-2.6	-2.8	-2.2	-1.8
	Y=12H	-3.3	-2.7	-2.9	-2.3	-1.9	-3.3	-2.7	-2.9	-2.3	-1.9
X=4H	Y=2H	-3.1	-2.4	-2.7	-2.0	-1.6	-3.1	-2.4	-2.7	-2.0	-1.6
	Y=3H	-3.3	-2.7	-2.9	-2.3	-1.9	-3.3	-2.7	-2.9	-2.3	-1.9
	Y=4H	-3.4	-2.9	-3.0	-2.5	-2.0	-3.4	-2.9	-3.0	-2.5	-2.0
	Y=6H	-3.6	-3.1	-3.1	-2.7	-2.2	-3.6	-3.1	-3.1	-2.7	-2.2
	Y=8H	-3.6	-3.2	-3.2	-2.8	-2.3	-3.6	-3.2	-3.2	-2.8	-2.3
	Y=12H	-3.7	-3.3	-3.2	-2.9	-2.4	-3.7	-3.3	-3.2	-2.9	-2.4
X=8H	Y=4H	-3.6	-3.2	-3.2	-2.8	-2.3	-3.6	-3.2	-3.2	-2.8	-2.3
	Y=6H	-3.8	-3.4	-3.3	-2.9	-2.4	-3.8	-3.4	-3.3	-2.9	-2.4
	Y=8H	-3.9	-3.6	-3.3	-3.0	-2.5	-3.9	-3.6	-3.3	-3.0	-2.5
	Y=12H	-3.9	-3.7	-3.4	-3.2	-2.6	-3.9	-3.7	-3.4	-3.2	-2.6
X=12H	Y=4H	-3.7	-3.3	-3.2	-2.9	-2.4	-3.7	-3.3	-3.2	-2.9	-2.4
	Y=6H	-3.8	-3.6	-3.3	-3.1	-2.5	-3.8	-3.6	-3.3	-3.1	-2.5
	Y=8H	-3.9	-3.7	-3.4	-3.2	-2.6	-3.9	-3.7	-3.4	-3.2	-2.6
Variations with the objerver position at spacings											
S=1.0H		0.0/0.0					0.0/0.0				
S=1.5H		0.0/0.0					0.0/0.0				
S=2.0H		0.0/0.0					0.0/0.0				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.0					0.0				

o the CIE Pub.117,data has been corrected,refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	3935.86	3935.86	3935.86	3935.86
γ 1.0	3937.74	3965.66	3858.17	3898.75
γ 2.0	3920.97	3906.11	3725.73	3782.56
γ 3.0	3845.32	3803.07	3532.13	3628.60
γ 4.0	3702.14	3656.75	3288.99	3412.83
γ 5.0	3499.21	3450.96	3016.84	3146.30
γ 6.0	3241.41	3190.68	2693.00	2845.97
γ 7.0	2951.13	2890.11	2341.57	2537.33
γ 8.0	2629.15	2560.00	2009.82	2216.19
γ 9.0	2304.92	2230.27	1710.50	1887.42
γ 10.0	1999.28	1923.40	1442.82	1590.84
γ 11.0	1717.56	1654.10	1202.46	1335.43
γ 12.0	1476.12	1419.61	992.36	1122.75
γ 13.0	1267.23	1226.44	815.02	948.65
γ 14.0	1078.61	1062.60	667.12	800.61
γ 15.0	911.71	921.05	547.42	673.70
γ 16.0	766.13	795.58	448.52	566.69
γ 17.0	640.50	686.34	369.98	475.72
γ 18.0	533.71	588.88	307.39	399.21
γ 19.0	447.80	505.40	256.11	335.34
γ 20.0	377.27	433.82	214.92	281.76
γ 21.0	320.21	371.37	180.94	236.75
γ 22.0	272.71	317.10	151.82	198.93
γ 23.0	232.39	269.85	127.39	166.79
γ 24.0	198.07	228.22	106.66	139.43
γ 25.0	168.74	193.03	88.95	116.18
γ 26.0	143.54	162.77	74.21	95.52
γ 27.0	121.50	135.75	61.39	77.69
γ 28.0	102.47	112.93	49.76	62.69
γ 29.0	86.28	93.86	39.97	50.35
γ 30.0	72.23	77.78	32.35	40.77
γ 31.0	59.98	64.55	26.23	32.82
γ 32.0	50.01	53.60	21.35	26.42
γ 33.0	41.99	44.41	16.81	21.07
γ 34.0	35.24	36.55	12.87	16.22
γ 35.0	29.39	29.51	9.15	12.16
γ 36.0	24.18	23.58	5.70	8.38
γ 37.0	19.53	18.11	2.86	5.01
γ 38.0	15.32	13.69	0.45	2.62
γ 39.0	11.77	9.86	0.00	0.57
γ 40.0	8.82	6.47	0.00	0.00
γ 41.0	6.00	3.50	0.00	0.00
γ 42.0	3.67	1.11	0.00	0.00
γ 43.0	1.71	0.00	0.00	0.00
γ 44.0	0.00	0.00	0.00	0.00
γ 45.0	0.00	0.00	0.00	0.00
γ 46.0	0.00	0.00	0.00	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	0.00	0.00	0.00	0.00
γ 48.0	0.00	0.00	0.00	0.00
γ 49.0	0.00	0.00	0.00	0.00
γ 50.0	0.00	0.00	0.00	0.00
γ 51.0	0.00	0.00	0.00	0.00
γ 52.0	0.00	0.00	0.00	0.00
γ 53.0	0.00	0.00	0.00	0.00
γ 54.0	0.00	0.00	0.00	0.00
γ 55.0	0.00	0.00	0.00	0.00
γ 56.0	0.00	0.00	0.00	0.00
γ 57.0	0.00	0.00	0.00	0.00
γ 58.0	0.00	0.00	0.00	0.00
γ 59.0	0.00	0.00	0.00	0.00
γ 60.0	0.00	0.00	0.00	0.00
γ 61.0	0.00	0.00	0.00	0.00
γ 62.0	0.00	0.00	0.00	0.00
γ 63.0	0.00	0.00	0.00	0.00
γ 64.0	0.00	0.00	0.00	0.00
γ 65.0	0.00	0.00	0.00	0.00
γ 66.0	0.00	0.00	0.00	0.00
γ 67.0	0.00	0.00	0.00	0.00
γ 68.0	0.00	0.00	0.00	0.00
γ 69.0	0.00	0.00	0.00	0.00
γ 70.0	0.00	0.00	0.00	0.00
γ 71.0	0.00	0.00	0.00	0.00
γ 72.0	0.00	0.00	0.00	0.00
γ 73.0	0.00	0.00	0.00	0.00
γ 74.0	0.00	0.00	0.00	0.00
γ 75.0	0.00	0.00	0.00	0.00
γ 76.0	0.00	0.00	0.00	0.00
γ 77.0	0.00	0.00	0.00	0.00
γ 78.0	0.00	0.00	0.00	0.00
γ 79.0	0.00	0.00	0.00	0.00
γ 80.0	0.00	0.00	0.00	0.00
γ 81.0	0.00	0.00	0.00	0.00
γ 82.0	0.00	0.00	0.00	0.00
γ 83.0	0.00	0.00	0.00	0.00
γ 84.0	0.00	0.00	0.00	0.00
γ 85.0	0.00	0.00	0.00	0.00
γ 86.0	0.00	0.00	0.00	0.00
γ 87.0	0.00	0.00	0.00	0.00
γ 88.0	0.00	0.00	0.00	0.00
γ 89.0	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00
γ 91.0	0.00	0.00	0.00	0.00
γ 92.0	0.00	0.00	0.00	0.00
γ 93.0	0.00	0.00	0.00	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 96.0	0.00	0.00	0.00	0.00
γ 97.0	0.00	0.00	0.00	0.00
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 131.0	0.00	0.00	0.00	0.00
γ 132.0	0.00	0.00	0.00	0.00
γ 133.0	0.00	0.00	0.00	0.00
γ 134.0	0.00	0.00	0.00	0.00
γ 135.0	0.00	0.00	0.00	0.00
γ 136.0	0.00	0.00	0.00	0.00
γ 137.0	0.00	0.00	0.00	0.00
γ 138.0	0.00	0.00	0.00	0.00
γ 139.0	0.00	0.00	0.00	0.00
γ 140.0	0.00	0.00	0.00	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00
γ 144.0	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.00	0.00	0.00
γ 146.0	0.00	0.00	0.00	0.00
γ 147.0	0.00	0.00	0.00	0.00
γ 148.0	0.00	0.00	0.00	0.00
γ 149.0	0.00	0.00	0.00	0.00
γ 150.0	0.00	0.00	0.00	0.00
γ 151.0	0.00	0.00	0.00	0.00
γ 152.0	0.00	0.00	0.00	0.00
γ 153.0	0.00	0.00	0.00	0.00
γ 154.0	0.00	0.00	0.00	0.00
γ 155.0	0.00	0.00	0.00	0.00
γ 156.0	0.00	0.00	0.00	0.00
γ 157.0	0.00	0.00	0.00	0.00
γ 158.0	0.00	0.00	0.00	0.00
γ 159.0	0.00	0.00	0.00	0.00
γ 160.0	0.00	0.00	0.00	0.00
γ 161.0	0.00	0.00	0.00	0.00
γ 162.0	0.00	0.00	0.00	0.00
γ 163.0	0.00	0.00	0.00	0.00
γ 164.0	0.00	0.00	0.00	0.00
γ 165.0	0.00	0.00	0.00	0.00
γ 166.0	0.00	0.00	0.00	0.00
γ 167.0	0.00	0.00	0.00	0.00
γ 168.0	0.00	0.00	0.00	0.00
γ 169.0	0.00	0.00	0.00	0.00
γ 170.0	0.00	0.00	0.00	0.00
γ 171.0	0.00	0.00	0.00	0.00
γ 172.0	0.00	0.00	0.00	0.00
γ 173.0	0.00	0.00	0.00	0.00
γ 174.0	0.00	0.00	0.00	0.00
γ 175.0	0.00	0.00	0.00	0.00
γ 176.0	0.00	0.00	0.00	0.00
γ 177.0	0.00	0.00	0.00	0.00
γ 178.0	0.00	0.00	0.00	0.00
γ 179.0	0.00	0.00	0.00	0.00
γ 180.0	0.00	0.00	0.00	0.00