
LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


DATA OF LAMP		PHOTOMETRIC DATA Eff: 5.13 lm/W			
MODEL	HCP-271914-5500K	Imax(cd)	10.87	S/MH(C0/180)	4.80
NOMINAL POWER(W)	6	LOR(%)	100.0	S/MH(C90/270)	4.53
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	28.475	η UP,DN(C0-180)	14.1,37.9
NOMINAL FLUX(lm)	28.4746	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	12.3,35.8
LAMPS INSIDE	1	η up(%)	26.4	CIBSE SHR NOM	2.00
TEST VOLTAGE(V)	23.997	η down(%)	73.6	CIBSE SHR MAX	2.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):217.8 DEG

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	0.5857	0.5470	0.5736	0.5342	0.5779	0.5779	0.5865	0.5866	0- 10	0.0513	0.0513	0.18,0.18
20	0.8856	0.8465	0.8378	0.8035	0.8908	0.8387	0.8474	0.8430	10- 20	0.2006	0.2519	0.88,0.88
30	1.545	1.328	1.376	1.237	1.473	1.277	1.347	1.256	20- 30	0.5095	0.7614	2.67,2.67
40	2.340	1.832	2.036	1.698	2.203	1.742	1.938	1.699	30- 40	1.041	1.802	6.33,6.33
50	3.217	2.193	2.766	2.041	2.985	2.116	2.585	2.042	40- 50	1.731	3.534	12.4,12.4
60	3.999	2.445	3.491	2.284	3.758	2.393	3.254	2.285	50- 60	2.482	6.015	21.1,21.1
70	5.227	2.692	4.494	2.545	4.775	2.719	4.376	2.611	60- 70	3.310	9.325	32.8,32.8
80	8.448	3.153	6.902	3.014	7.157	3.162	6.818	3.241	70- 80	4.774	14.10	49.5,49.5
90	10.72	3.445	8.747	3.379	9.224	3.300	8.358	3.421	80- 90	6.872	20.97	73.6,73.6
100	6.008	1.675	5.144	1.757	5.432	1.639	4.116	1.466	90-100	5.913	26.88	94.4,94.4
110	0.0620	0.0306	0.0799	0.0395	0.1379	0.0086	0.0519	0	100-110	1.577	28.46	100,100
120	0.0130	0	0.0043	0	0	0	0	0	110-120	0.0125	28.47	100,100
130	0	0	0	0	0	0	0	0	120-130	0.0010	28.47	100,100
140	0	0	0	0	0	0	0	0	130-140	0.0000	28.47	100,100
150	0	0	0	0	0	0	0	0	140-150	0	28.47	100,100
160	0	0	0	0	0	0	0	0	150-160	0	28.47	100,100
170	0	0	0	0	0	0	0	0	160-170	0	28.47	100,100
180	0	0	0	0	0	0	0	0	170-180	0	28.47	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28


γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

LUMINANCE LIMITATION CURVES

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

LUMINANCE LIMITATION CURVES

GLARE	CLASS	ILLUMINANCE (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	1177	949
80	486	397
75	252	213
70	153	131
65	106	92
60	80	70
55	63	54
50	50	43
45	40	34


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.13	1.13	1.13	1.07	1.07	1.07	.96	.96	.96	.87	.87	.87	.78	.78	.78	.74
1.0	.82	.74	.66	.77	.70	.63	.68	.62	.56	.59	.54	.49	.51	.47	.43	.39
2.0	.67	.56	.47	.62	.53	.44	.54	.46	.39	.47	.40	.34	.40	.34	.29	.25
3.0	.56	.45	.35	.52	.42	.33	.45	.36	.29	.39	.31	.25	.33	.27	.21	.18
4.0	.48	.37	.28	.45	.34	.26	.39	.30	.23	.33	.26	.20	.28	.22	.16	.13
5.0	.42	.31	.23	.39	.29	.21	.34	.25	.18	.29	.22	.16	.24	.18	.13	.10
6.0	.37	.26	.19	.35	.25	.18	.30	.22	.15	.26	.18	.13	.22	.16	.11	.08
7.0	.33	.23	.16	.31	.22	.15	.27	.19	.13	.23	.16	.11	.20	.14	.09	.06
8.0	.30	.20	.13	.28	.19	.13	.24	.17	.11	.21	.14	.09	.18	.12	.08	.05
9.0	.27	.18	.12	.25	.17	.11	.22	.15	.09	.19	.13	.08	.16	.11	.07	.04
10.0	.25	.16	.10	.23	.15	.10	.20	.13	.08	.18	.11	.07	.15	.10	.06	.04



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

WEC AND CCEC

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coeffcients(WEC)									
0.0																
1.0	.601	.342	.108	.585	.334	.106	.556	.319	.102	.529	.305	.098	.503	.292	.094	
2.0	.458	.251	.077	.443	.244	.075	.416	.231	.072	.391	.219	.069	.368	.208	.066	
3.0	.378	.201	.060	.365	.196	.059	.341	.185	.056	.318	.174	.053	.297	.164	.051	
4.0	.325	.169	.050	.313	.164	.048	.291	.154	.046	.270	.145	.044	.251	.136	.041	
5.0	.285	.145	.042	.275	.141	.041	.254	.132	.039	.235	.124	.037	.218	.116	.035	
6.0	.255	.128	.037	.245	.124	.036	.227	.116	.034	.209	.109	.032	.193	.102	.030	
7.0	.231	.114	.032	.222	.111	.031	.205	.104	.030	.189	.097	.028	.174	.090	.027	
8.0	.211	.103	.029	.203	.100	.028	.187	.093	.027	.172	.087	.025	.158	.081	.024	
9.0	.194	.094	.026	.186	.091	.025	.172	.085	.024	.158	.079	.023	.146	.074	.021	
10.0	.180	.086	.024	.173	.083	.023	.159	.078	.022	.147	.073	.021	.135	.068	.019	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.391	.391	.391	.334	.334	.334	.228	.228	.228	.131	.131	.131	.042	.042	.042	
1.0	.403	.356	.314	.345	.306	.270	.236	.210	.187	.136	.122	.109	.043	.039	.035	
2.0	.398	.335	.282	.341	.288	.244	.234	.199	.170	.135	.116	.100	.043	.038	.032	
3.0	.390	.320	.264	.335	.276	.229	.230	.192	.160	.133	.112	.095	.043	.036	.031	
4.0	.381	.308	.253	.327	.267	.220	.225	.186	.155	.130	.109	.092	.042	.035	.030	
5.0	.372	.299	.245	.320	.259	.214	.220	.181	.151	.128	.106	.089	.041	.035	.029	
6.0	.363	.292	.240	.312	.253	.209	.215	.177	.148	.125	.104	.088	.040	.034	.029	
7.0	.355	.285	.236	.305	.247	.206	.211	.173	.146	.123	.102	.087	.040	.033	.029	
8.0	.347	.280	.234	.299	.243	.204	.207	.170	.144	.120	.101	.086	.039	.033	.028	
9.0	.340	.275	.231	.293	.239	.202	.203	.168	.143	.118	.099	.085	.038	.033	.028	
10.0	.333	.271	.229	.287	.235	.200	.199	.166	.142	.116	.098	.085	.038	.032	.028	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

UGR(Unified Glare Rating) Table

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	14.4	15.9	15.0	16.6	17.4	12.3	13.8	12.9	14.5	15.3
	3H	19.1	20.5	19.7	21.2	22.0	16.9	18.3	17.5	19.0	19.8
	4H	22.0	23.3	22.6	24.0	24.9	19.9	21.2	20.5	21.9	22.8
	6H	25.5	26.8	26.2	27.5	28.4	23.4	24.7	24.1	25.5	26.3
	8H	27.4	28.7	28.1	29.4	30.3	25.4	26.7	26.1	27.4	28.3
	12H	29.6	30.8	30.3	31.5	32.4	27.6	28.9	28.3	29.6	30.5
4H	2H	14.9	16.3	15.6	17.0	17.9	13.4	14.7	14.0	15.4	16.3
	3H	19.9	21.2	20.6	21.9	22.8	17.7	18.9	18.4	19.6	20.5
	4H	23.2	24.3	23.9	25.1	26.0	20.6	21.8	21.3	22.5	23.4
	6H	26.9	28.0	27.7	28.8	29.7	24.3	25.4	25.1	26.1	27.1
	8H	29.0	30.0	29.7	30.8	31.7	26.5	27.5	27.2	28.3	29.2
	12H	31.2	32.2	32.0	33.0	33.9	28.8	29.8	29.6	30.6	31.6
8H	4H	23.5	24.5	24.2	25.3	26.2	21.3	22.3	22.1	23.1	24.1
	6H	27.6	28.5	28.4	29.3	30.3	24.9	25.8	25.7	26.6	27.6
	8H	30.0	30.8	30.8	31.7	32.7	27.2	28.0	27.9	28.8	29.8
	12H	32.6	33.3	33.4	34.2	35.2	29.7	30.5	30.6	31.3	32.3
12H	4H	23.5	24.5	24.3	25.3	26.3	22.0	22.9	22.8	23.7	24.7
	6H	27.7	28.5	28.5	29.4	30.4	25.3	26.1	26.1	27.0	28.0
	8H	30.2	30.9	31.0	31.8	32.8	27.5	28.2	28.3	29.1	30.1

Variations with the observer position at spacings:		
S = 1.0H	+ 0.1 / - 0.2	+ 0.1 / - 0.1
1.5H	+ 0.3 / - 0.3	+ 0.3 / - 0.3
2.0H	+ 0.4 / - 0.5	+ 0.4 / - 0.5

CIE Pub.117, 28.47 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -12.4)
Area: 0.1 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

UTILIZATION FACTORS TABLE

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	35	20	12	33	20	12	32	19	11	4
0.80	42	26	16	40	26	16	38	24	16	7
1.00	49	32	21	47	31	21	43	32	20	10
1.25	55	38	26	52	37	26	48	34	24	13
1.50	60	43	31	57	41	30	52	38	28	16
2.00	68	51	39	64	49	38	58	45	35	22
2.50	73	57	45	69	55	44	62	50	41	26
3.00	77	62	51	73	60	49	66	55	45	30
4.00	83	70	59	79	67	57	71	61	52	35
5.00	87	75	65	83	72	62	74	65	57	39
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004				Suspended					SHRNOM = 1.25	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

ISOCANDELA DIAGRAM

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

AAI CURVES

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

ISOLUX DIAGRAM

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

LED Avg.L Report

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	102
L_0~180(75)av	237
L_0~180(85)av	1083
L_90~270(65)av	90
L_90~270(75)av	211
L_90~270(85)av	939
L_45(65)av	59
L_45(75)av	111
L_45(85)av	388

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:23.997V I:0.2314A P:5.5529W PF:1.0000 Freq:50.00Hz Lamp Flux:28.4746x1 lm		
NAME: HCP-271914-5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

Table--1 UNIT: cd

γ (DEG) \ C(DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50			
5	0.53	0.53	0.53	0.54	0.53	0.53	0.54	0.54	0.53	0.53	0.54	0.53	0.53	0.53	0.54	0.53			
10	0.59	0.59	0.55	0.58	0.57	0.58	0.53	0.58	0.58	0.55	0.58	0.53	0.59	0.57	0.59	0.57			
15	0.70	0.72	0.66	0.69	0.65	0.69	0.65	0.69	0.70	0.66	0.69	0.65	0.68	0.65	0.69	0.66			
20	0.89	0.92	0.85	0.84	0.84	0.86	0.80	0.86	0.89	0.86	0.84	0.80	0.85	0.81	0.84	0.85			
25	1.17	1.19	1.08	1.04	1.08	1.09	1.01	1.06	1.14	1.12	1.04	1.00	1.07	1.09	1.03	1.08			
30	1.55	1.54	1.33	1.29	1.38	1.38	1.24	1.32	1.47	1.42	1.28	1.20	1.35	1.35	1.26	1.35			
35	1.94	1.92	1.56	1.54	1.71	1.71	1.49	1.58	1.82	1.75	1.52	1.44	1.64	1.63	1.49	1.59			
40	2.34	2.33	1.83	1.77	2.04	2.05	1.70	1.84	2.20	2.11	1.74	1.65	1.94	1.91	1.70	1.83			
45	2.80	2.75	2.03	1.99	2.40	2.41	1.91	2.09	2.59	2.48	1.94	1.85	2.26	2.24	1.89	2.07			
50	3.22	3.17	2.19	2.17	2.77	2.77	2.04	2.30	2.98	2.84	2.12	2.04	2.58	2.56	2.04	2.26			
55	3.63	3.56	2.32	2.33	3.11	3.13	2.19	2.48	3.38	3.22	2.26	2.19	2.90	2.88	2.17	2.41			
60	4.00	3.95	2.44	2.47	3.49	3.49	2.28	2.66	3.76	3.57	2.39	2.38	3.25	3.24	2.28	2.55			
65	4.48	4.39	2.55	2.63	3.89	3.90	2.40	2.85	4.18	3.99	2.55	2.56	3.70	3.68	2.42	2.74			
70	5.23	5.07	2.69	2.88	4.49	4.52	2.54	3.12	4.77	4.60	2.72	2.87	4.38	4.40	2.61	2.97			
75	6.53	6.21	2.90	3.31	5.51	5.61	2.74	3.57	5.75	5.58	2.92	3.28	5.43	5.59	2.90	3.46			
80	8.45	7.88	3.15	3.91	6.90	7.29	3.01	4.19	7.16	6.94	3.16	3.78	6.82	7.18	3.24	4.13			
85	10.3	9.56	3.39	4.52	8.27	9.07	3.30	4.83	8.62	8.28	3.35	4.19	8.09	8.57	3.48	4.80			
90	10.7	10.0	3.44	4.69	8.75	9.89	3.38	5.05	9.22	8.74	3.30	4.13	8.36	8.79	3.42	5.01			
95	8.84	8.57	2.76	3.84	7.47	8.53	2.81	4.24	7.99	7.40	2.68	3.32	6.85	6.94	2.65	4.03			
100	6.01	6.04	1.67	2.58	5.14	5.81	1.76	2.78	5.43	4.98	1.64	1.88	4.12	4.15	1.47	2.61			
105	1.55	1.76	0.32	0.77	1.72	2.24	0.49	1.08	2.35	1.90	0.44	0.46	1.30	1.24	0.32	0.52			
110	0.06	0.03	0.03	0.00	0.08	0.11	0.04	0.03	0.14	0.13	0.01	0.03	0.05	0.07	0.00	0.03			
115	0.02	0.00	0.00	0.00	0.02	0.00	0.01	0.00	0.03	0.03	0.00	0.00	0.00	0.02	0.00	0.01			
120	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.00	0.00	0.01	0.00	0.01			
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00			
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00			
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2025-11-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271914-Front Cover 5500K