
LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


DATA OF LAMP		PHOTOMETRIC DATA		Eff: 0.64 lm/W	
MODEL	HCP-271204 5500K	Imax(cd)	0.3474	S/MH(C0/180)	0.00
NOMINAL POWER(W)	1	LOR(%)	100.0	S/MH(C90/270)	6.54
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	0.7811	η UP,DN(C0-180)	0.0,50.8
NOMINAL FLUX(lm)	0.781107	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.2
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	23.997	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):180.0 DEG

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	0	0.0174	0.0130	0.0174	0	0.0174	0.0218	0.0217	0- 10	0.0013	0.0013	0.17,0.17
20	0	0.0174	0.0261	0.0174	0	0.0217	0.0434	0.0348	10- 20	0.0049	0.0062	0.80,0.80
30	0	0.0346	0.0477	0.0390	0	0.0391	0.0783	0.0435	20- 30	0.0126	0.0188	2.41,2.41
40	0	0.0391	0.1823	0.0477	0	0.0652	0.2085	0.0870	30- 40	0.0364	0.0552	7.06,7.06
50	0	0.0999	0.3039	0.1085	0	0.1087	0.3172	0.1434	40- 50	0.0851	0.1403	18,18
60	0	0.1085	0.3170	0.1607	0	0.1346	0.3474	0.1868	50- 60	0.1311	0.2714	34.7,34.7
70	0	0.1519	0.3344	0.1737	0	0.1346	0.3474	0.1954	60- 70	0.1596	0.4310	55.2,55.2
80	0	0.1737	0.3474	0.1737	0	0.1259	0.3344	0.1954	70- 80	0.1754	0.6064	77.6,77.6
90	0	0.1607	0.3127	0.1650	0	0.1086	0.3170	0.1954	80- 90	0.1747	0.7811	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13


γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

LUMINANCE LIMITATION CURVES

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	**TYPE:**	**WEIGHT:**
SPEC.:	**DIM.:**	**SERIAL No.:**
MFR.: ONIKE	**SUR.:**	**Shielding Angle:**

LUMINANCE LIMITATION CURVES

GLARE	CLASS	ILLUMINANCE (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	0	40
80	0	20
75	0	13
70	0	10
65	0	8
60	0	6
55	0	5
50	0	5
45	0	3


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	.87	.78	.70	.84	.76	.69	.80	.73	.67	.75	.70	.64	.71	.67	.62	.59
2.0	.69	.57	.47	.67	.56	.47	.63	.53	.45	.59	.51	.44	.55	.49	.43	.40
3.0	.56	.44	.34	.55	.43	.33	.51	.41	.32	.48	.39	.32	.45	.37	.31	.28
4.0	.47	.35	.25	.46	.34	.25	.43	.32	.24	.40	.31	.24	.38	.30	.23	.20
5.0	.41	.28	.19	.39	.28	.19	.37	.27	.19	.35	.25	.18	.32	.24	.18	.15
6.0	.35	.24	.15	.34	.23	.15	.32	.22	.15	.30	.21	.14	.28	.20	.14	.12
7.0	.31	.20	.12	.30	.20	.12	.29	.19	.12	.27	.18	.12	.25	.18	.12	.09
8.0	.28	.17	.10	.27	.17	.10	.26	.16	.10	.24	.16	.10	.23	.15	.10	.07
9.0	.25	.15	.08	.25	.15	.08	.23	.14	.08	.22	.14	.08	.21	.13	.08	.06
10.0	.23	.14	.07	.22	.13	.07	.21	.13	.07	.20	.12	.07	.19	.12	.07	.05



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

WEC AND CCEC

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coeffcients(WEC)									
0.0																
1.0	.632	.360	.114	.624	.356	.113	.609	.350	.112	.596	.344	.110	.583	.338	.109	
2.0	.498	.273	.084	.491	.270	.083	.477	.265	.082	.465	.261	.082	.453	.256	.081	
3.0	.417	.222	.066	.410	.220	.066	.398	.216	.066	.387	.212	.065	.376	.208	.064	
4.0	.359	.187	.055	.353	.185	.055	.342	.182	.054	.332	.179	.054	.323	.176	.053	
5.0	.315	.161	.047	.310	.159	.046	.301	.157	.046	.292	.154	.046	.284	.152	.046	
6.0	.281	.141	.040	.277	.140	.040	.268	.138	.040	.260	.135	.040	.253	.133	.040	
7.0	.254	.125	.036	.250	.124	.035	.242	.122	.035	.235	.121	.035	.229	.119	.035	
8.0	.231	.113	.032	.227	.112	.032	.221	.110	.031	.215	.109	.031	.209	.107	.031	
9.0	.212	.102	.029	.209	.102	.029	.203	.100	.028	.197	.099	.028	.192	.098	.028	
10.0	.196	.094	.026	.193	.093	.026	.188	.092	.026	.183	.091	.026	.178	.089	.026	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.203	.153	.109	.173	.132	.094	.119	.091	.065	.068	.052	.038	.022	.017	.012	
2.0	.200	.131	.073	.171	.113	.063	.117	.078	.044	.068	.045	.026	.022	.015	.008	
3.0	.193	.115	.054	.165	.099	.046	.113	.069	.033	.066	.040	.019	.021	.013	.006	
4.0	.184	.103	.042	.158	.089	.036	.109	.062	.026	.063	.036	.015	.020	.012	.005	
5.0	.174	.094	.035	.150	.081	.030	.103	.057	.021	.060	.033	.013	.019	.011	.004	
6.0	.165	.086	.029	.142	.075	.026	.098	.052	.018	.057	.031	.011	.018	.010	.004	
7.0	.156	.079	.026	.134	.069	.022	.093	.048	.016	.054	.028	.009	.017	.009	.003	
8.0	.148	.074	.023	.127	.064	.020	.088	.045	.014	.051	.026	.008	.017	.009	.003	
9.0	.140	.069	.021	.120	.060	.018	.083	.042	.013	.049	.025	.008	.016	.008	.003	
10.0	.132	.064	.019	.114	.056	.017	.079	.039	.012	.046	.023	.007	.015	.008	.002	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

UGR(Unified Glare Rating) Table

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	5.2	7.3	5.5	7.5	7.8	22.0	24.1	22.3	24.3	24.6
	3H	4.9	6.9	5.2	7.2	7.4	25.9	27.9	26.2	28.1	28.4
	4H	4.7	6.7	5.1	7.0	7.3	27.9	29.9	28.3	30.1	30.5
	6H	4.6	6.5	5.0	6.8	7.1	30.1	32.0	30.5	32.3	32.6
	8H	4.5	6.3	4.9	6.7	7.0	31.4	33.2	31.7	33.5	33.8
	12H	4.5	6.2	4.9	6.6	6.9	32.7	34.5	33.1	34.8	35.2
4H	2H	14.7	16.7	15.1	17.0	17.3	22.1	24.0	22.5	24.3	24.6
	3H	15.6	17.4	16.0	17.7	18.1	26.5	28.3	26.9	28.6	28.9
	4H	15.7	17.4	16.1	17.7	18.1	28.9	30.5	29.3	30.9	31.3
	6H	15.6	17.1	16.0	17.5	17.9	31.4	32.9	31.8	33.3	33.7
	8H	15.5	17.0	16.0	17.4	17.8	32.7	34.2	33.2	34.6	35.0
	12H	15.5	16.8	15.9	17.2	17.7	34.2	35.6	34.7	36.0	36.5
8H	4H	21.6	23.1	22.0	23.5	23.9	29.1	30.6	29.6	31.0	31.4
	6H	22.2	23.5	22.6	23.9	24.3	32.0	33.2	32.4	33.7	34.1
	8H	22.2	23.4	22.7	23.8	24.3	33.6	34.8	34.1	35.2	35.7
	12H	22.2	23.3	22.7	23.7	24.2	35.4	36.4	35.8	36.9	37.4
12H	4H	23.2	24.5	23.6	24.9	25.4	29.1	30.5	29.5	30.9	31.3
	6H	24.4	25.6	24.9	26.0	26.5	32.0	33.2	32.5	33.7	34.1
	8H	24.8	25.9	25.3	26.4	26.8	33.8	34.8	34.3	35.3	35.8

Variations with the observer position at spacings:		
S = 1.0H	+ 0.1 / - 0.1	+ 0.1 / - 0.1
1.5H	+ 0.1 / - 0.1	+ 0.2 / - 0.3
2.0H	+ 0.2 / - 0.2	+ 0.3 / - 0.4

CIE Pub.117, 0.7811 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -24.9)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

UTILIZATION FACTORS TABLE

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	37	22	13	36	22	13	35	21	12	4
0.80	46	29	19	44	29	19	42	28	18	9
1.00	53	37	26	52	36	25	49	39	25	14
1.25	60	44	33	58	43	32	55	41	31	20
1.50	66	50	38	64	49	38	60	47	37	25
2.00	75	60	48	72	58	48	68	56	46	34
2.50	81	67	56	78	65	55	73	62	53	41
3.00	85	72	62	83	71	61	77	67	59	47
4.00	92	80	71	89	78	70	83	74	67	55
5.00	96	86	77	93	84	76	87	79	73	60
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004				Suspended					SHRNOM = 1.25	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

ISOCANDELA DIAGRAM

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

AAI CURVES

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

ISOLUX DIAGRAM

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

LED Avg.L Report

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	0
L_0~180(75)av	0
L_0~180(85)av	0
L_90~270(65)av	8
L_90~270(75)av	13
L_90~270(85)av	38
L_45(65)av	4
L_45(75)av	7
L_45(85)av	19

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:23.997V I:0.0506A P:1.2142W PF:1.0000 Freq:50.00Hz Lamp Flux:0.781107x1 lm		
NAME: HCP-271204 5500K	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ONIKE	SUR.:	Shielding Angle:

Table--1 UNIT: cd

γ (DEG) \ C(DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5
0	0.00	0.00	0.02	0.02	0.01	0.02	0.02	0.02	0.00	0.00	0.02	0.02	0.01	0.02	0.02	0.02
5	0.00	0.00	0.02	0.02	0.01	0.02	0.02	0.02	0.00	0.00	0.02	0.02	0.02	0.02	0.02	0.02
10	0.00	0.00	0.02	0.03	0.01	0.03	0.02	0.02	0.00	0.00	0.02	0.02	0.02	0.02	0.02	0.02
15	0.00	0.00	0.02	0.03	0.01	0.03	0.02	0.03	0.00	0.00	0.02	0.02	0.03	0.02	0.03	0.02
20	0.00	0.00	0.02	0.04	0.03	0.05	0.02	0.02	0.00	0.00	0.02	0.02	0.04	0.02	0.03	0.02
25	0.00	0.00	0.02	0.06	0.03	0.06	0.03	0.02	0.00	0.00	0.03	0.03	0.06	0.03	0.04	0.02
30	0.00	0.00	0.03	0.08	0.05	0.09	0.04	0.02	0.00	0.00	0.04	0.03	0.08	0.03	0.04	0.02
35	0.00	0.00	0.04	0.13	0.12	0.14	0.04	0.03	0.00	0.00	0.05	0.05	0.14	0.09	0.06	0.02
40	0.00	0.00	0.04	0.18	0.18	0.20	0.05	0.03	0.00	0.00	0.07	0.10	0.21	0.12	0.09	0.02
45	0.00	0.00	0.06	0.23	0.24	0.25	0.10	0.03	0.00	0.00	0.09	0.16	0.27	0.19	0.11	0.02
50	0.00	0.00	0.10	0.27	0.30	0.30	0.11	0.03	0.00	0.00	0.11	0.22	0.32	0.24	0.14	0.02
55	0.00	0.00	0.10	0.29	0.31	0.31	0.12	0.04	0.00	0.00	0.13	0.24	0.35	0.26	0.17	0.02
60	0.00	0.00	0.11	0.30	0.32	0.32	0.16	0.04	0.00	0.00	0.13	0.24	0.35	0.30	0.19	0.03
65	0.00	0.00	0.13	0.31	0.33	0.32	0.17	0.04	0.00	0.00	0.13	0.25	0.35	0.31	0.20	0.03
70	0.00	0.00	0.15	0.31	0.33	0.32	0.17	0.04	0.00	0.00	0.13	0.26	0.35	0.31	0.20	0.04
75	0.00	0.00	0.17	0.31	0.34	0.32	0.17	0.04	0.00	0.00	0.13	0.28	0.34	0.31	0.20	0.04
80	0.00	0.00	0.17	0.29	0.35	0.32	0.17	0.03	0.00	0.00	0.13	0.30	0.33	0.31	0.20	0.04
85	0.00	0.00	0.18	0.26	0.35	0.30	0.17	0.02	0.00	0.00	0.12	0.30	0.32	0.32	0.20	0.04
90	0.00	0.00	0.16	0.25	0.31	0.27	0.17	0.02	0.00	0.00	0.11	0.28	0.32	0.30	0.20	0.03

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-12-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.003m [K=1.0000]
Remarks: HCP-271204 5500K