
LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:


DATA OF LAMP		PHOTOMETRIC DATA		Eff: 16.83 lm/W	
MODEL	HCP-3466350	Imax(cd)	20.13	S/MH(C0/180)	1.37
NOMINAL POWER(W)	12	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	74.568	η UP,DN(C0-180)	4.2,47.4
NOMINAL FLUX(lm)	74.5683	CIE CLASS	DIRECT	η UP,DN(C180-360)	4.2,44.3
LAMPS INSIDE	1	η up(%)	8.3	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	η down(%)	91.7	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(30%):146.8 DEG

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	19.70	19.98	20.13	20.00	19.73	19.43	19.23	19.39	0- 10	1.886	1.886	2.53,2.53
20	19.15	19.73	19.98	19.90	19.30	18.76	18.37	18.63	10- 20	5.520	7.406	9.93,9.93
30	18.07	18.88	19.14	19.27	18.36	17.78	17.17	17.53	20- 30	8.698	16.10	21.6,21.6
40	16.33	17.39	17.42	17.86	16.75	16.25	15.47	15.95	30- 40	11.02	27.13	36.4,36.4
50	13.97	15.03	14.76	15.52	14.49	14.11	13.15	13.79	40- 50	12.10	39.23	52.6,52.6
60	10.98	11.77	11.26	12.24	11.50	11.12	10.03	10.88	50- 60	11.59	50.82	68.1,68.1
70	7.439	7.799	7.026	8.126	7.856	7.384	6.222	7.242	60- 70	9.345	60.16	80.7,80.7
80	3.916	3.773	2.590	4.050	4.388	3.526	2.232	3.443	70- 80	5.759	65.92	88.4,88.4
90	1.883	1.467	0.0578	1.767	2.251	1.530	0.0001	1.320	80- 90	2.435	68.35	91.7,91.7
100	1.821	1.362	0	1.610	2.121	1.551	0	1.261	90-100	1.404	69.76	93.5,93.5
110	2.036	1.363	0	1.789	2.433	1.679	0	1.059	100-110	1.401	71.16	95.4,95.4
120	2.551	1.264	0	2.164	3.451	1.972	0	0.6833	110-120	1.414	72.57	97.3,97.3
130	2.152	0.6761	0	1.855	4.219	1.540	0	0.3107	120-130	1.353	73.93	99.1,99.1
140	0.1350	0	0	0.5238	1.251	0.4901	0	0.0030	130-140	0.5598	74.49	99.9,99.9
150	0	0	0	0.0829	0.1948	0.0817	0	0	140-150	0.0738	74.56	100,100
160	0	0	0	0	0	0.0088	0	0	150-160	0.0090	74.57	100,100
170	0	0	0	0	0	0	0	0	160-170	0.0001	74.57	100,100
180	0	0	0	0	0	0	0	0	170-180	0	74.57	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

0 - 60 DEG Zonal Flux:50.815 %lum: 68.1%
0 - 60 DEG Zonal Flux:50.815 %lum: 68.1%
All measured values may vary less than 35 %
from the average measured value in the 0 to 130 deg. zone: 14.2%
All measured values in the 0 to 130 deg. zone
may vary less than 50% from the average value of itself: 20.9%

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16


γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: HCP-3466350 B	**TYPE: 2835 B**	**WEIGHT:**
SPEC.:	**DIM.: 1* 0.01**	**SERIAL No.:**
MFR.: HAVIT COMMERCIAL	**SUR.:**	**Shielding Angle:**

LUMINANCE LIMITATION CURVES

GLARE	CLASS	ILLUMINANCE (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	306	103
80	226	149
75	217	184
70	218	205
65	219	218
60	220	225
55	219	229
50	217	230
45	215	229

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:


CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.17	1.17	1.17	1.13	1.13	1.13	1.06	1.06	1.06	1.00	1.00	1.00	.94	.94	.94	.92
1.0	1.01	.96	.92	.98	.93	.90	.92	.88	.85	.86	.84	.81	.81	.79	.77	.75
2.0	.87	.80	.74	.84	.78	.72	.79	.74	.69	.75	.70	.66	.71	.67	.64	.61
3.0	.76	.67	.60	.73	.66	.59	.69	.63	.57	.65	.60	.55	.62	.57	.53	.51
4.0	.67	.58	.51	.65	.56	.50	.61	.54	.48	.58	.52	.47	.55	.49	.45	.43
5.0	.59	.50	.43	.58	.49	.42	.54	.47	.41	.52	.45	.40	.49	.43	.39	.36
6.0	.53	.44	.37	.52	.43	.37	.49	.41	.36	.46	.40	.35	.44	.38	.34	.32
7.0	.48	.39	.33	.47	.38	.32	.44	.37	.31	.42	.36	.31	.40	.34	.30	.28
8.0	.43	.35	.29	.42	.34	.28	.40	.33	.28	.38	.32	.27	.37	.31	.26	.24
9.0	.40	.31	.26	.39	.31	.25	.37	.30	.25	.35	.29	.24	.34	.28	.24	.22
10.0	.37	.29	.23	.36	.28	.23	.34	.27	.22	.33	.26	.22	.31	.26	.21	.20

LAMPS

LUMINAIRE BUDGETARY DIAGRAM



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coeffcients(WEC)									
0.0																
1.0	.334	.190	.060	.324	.185	.059	.306	.175	.056	.289	.167	.054	.274	.159	.051	
2.0	.307	.168	.052	.298	.164	.051	.282	.157	.049	.267	.150	.047	.253	.143	.045	
3.0	.280	.149	.045	.273	.146	.044	.258	.140	.043	.245	.134	.041	.232	.129	.040	
4.0	.257	.134	.039	.250	.131	.039	.237	.126	.038	.225	.121	.036	.213	.116	.035	
5.0	.236	.120	.035	.230	.118	.034	.218	.114	.033	.207	.109	.033	.197	.105	.032	
6.0	.218	.109	.031	.213	.107	.031	.202	.103	.030	.192	.100	.029	.183	.096	.029	
7.0	.202	.100	.028	.197	.098	.028	.188	.095	.027	.179	.092	.027	.170	.088	.026	
8.0	.188	.092	.026	.184	.091	.026	.175	.087	.025	.167	.084	.024	.159	.082	.024	
9.0	.176	.085	.024	.172	.084	.024	.164	.081	.023	.156	.078	.022	.149	.076	.022	
10.0	.165	.079	.022	.162	.078	.022	.154	.076	.021	.147	.073	.021	.141	.071	.020	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.254	.254	.254	.217	.217	.217	.148	.148	.148	.085	.085	.085	.027	.027	.027	
1.0	.246	.220	.197	.210	.189	.169	.144	.130	.117	.083	.075	.068	.027	.024	.022	
2.0	.239	.196	.161	.204	.169	.139	.140	.117	.097	.081	.068	.057	.026	.022	.019	
3.0	.231	.179	.138	.198	.155	.119	.136	.107	.084	.079	.063	.049	.025	.020	.016	
4.0	.224	.166	.122	.192	.144	.106	.132	.100	.075	.076	.059	.044	.025	.019	.015	
5.0	.216	.156	.112	.186	.135	.097	.128	.094	.069	.074	.055	.041	.024	.018	.013	
6.0	.209	.148	.104	.180	.128	.091	.124	.090	.064	.072	.053	.038	.023	.017	.013	
7.0	.202	.141	.098	.174	.122	.086	.120	.086	.061	.070	.051	.036	.023	.017	.012	
8.0	.196	.136	.094	.169	.118	.082	.117	.083	.058	.068	.049	.035	.022	.016	.011	
9.0	.190	.131	.091	.163	.113	.079	.113	.080	.056	.066	.047	.034	.021	.015	.011	
10.0	.184	.127	.088	.159	.110	.077	.110	.077	.055	.064	.046	.033	.021	.015	.011	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.5	18.0	16.9	18.3	18.7	16.6	18.0	17.0	18.4	18.8
3H	18.2	19.6	18.7	20.0	20.4	18.2	19.5	18.6	19.9	20.3
4H	19.0	20.3	19.4	20.7	21.1	18.7	20.0	19.2	20.4	20.9
6H	19.6	20.8	20.1	21.2	21.7	19.1	20.3	19.6	20.7	21.2
8H	19.9	21.1	20.4	21.5	22.0	19.2	20.3	19.6	20.8	21.2
12H	20.2	21.3	20.7	21.8	22.2	19.2	20.3	19.7	20.8	21.2
4H 2H	17.2	18.5	17.7	18.9	19.3	17.3	18.5	17.7	18.9	19.4
3H	19.1	20.3	19.6	20.7	21.2	19.0	20.1	19.5	20.6	21.1
4H	20.0	21.0	20.5	21.5	22.0	19.7	20.8	20.2	21.2	21.7
6H	20.8	21.7	21.3	22.2	22.7	20.2	21.1	20.7	21.6	22.2
8H	21.2	22.0	21.7	22.5	23.1	20.4	21.2	20.9	21.7	22.3
12H	21.5	22.3	22.1	22.9	23.4	20.4	21.2	21.0	21.7	22.3
8H 4H	20.3	21.2	20.9	21.7	22.2	20.1	20.9	20.6	21.4	22.0
6H	21.3	22.0	21.9	22.6	23.2	20.7	21.4	21.3	22.0	22.6
8H	21.8	22.5	22.4	23.0	23.6	21.0	21.6	21.6	22.2	22.8
12H	22.4	22.9	23.0	23.5	24.2	21.1	21.7	21.7	22.3	22.9
12H 4H	20.3	21.1	20.9	21.6	22.2	20.1	20.9	20.7	21.4	22.0
6H	21.4	22.0	22.0	22.6	23.2	20.9	21.5	21.4	22.0	22.7
8H	22.0	22.5	22.6	23.1	23.8	21.2	21.7	21.8	22.3	22.9
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.5					+ 0.2 / - 0.4				

CIE Pub.117, 74.57 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -9.0)
Area: 0.1 m2

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	52	40	33	51	40	33	50	39	33	26
0.80	62	50	42	61	49	42	59	48	41	34
1.00	71	59	51	69	58	50	66	59	50	42
1.25	78	66	59	76	65	58	72	63	57	48
1.50	83	72	64	81	71	64	77	68	62	53
2.00	90	81	73	88	79	72	83	76	70	61
2.50	94	86	79	92	84	78	87	80	75	65
3.00	98	90	84	95	88	82	90	84	79	69
4.00	102	96	91	99	93	89	94	89	85	73
5.00	105	99	95	102	97	93	96	92	88	77
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004				Suspended					SHRNOM = 1.25	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

AAI Figure

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	225
L_0~180(75)av	224
L_0~180(85)av	331
L_90~270(65)av	206
L_90~270(75)av	173
L_90~270(85)av	89
L_45(65)av	230
L_45(75)av	218
L_45(85)av	266

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: HCP-3466350 B	TYPE: 2835 B	WEIGHT:
SPEC.:	DIM.: 1* 0.01	SERIAL No.:
MFR.: HAVIT COMMERCIAL	SUR.:	Shielding Angle:

Table--1 UNIT: cd

γ (DEG) \ C(DEG)	0	30	60	90	120	150	180	210	240	270	300	330							
0	19.8	19.8	19.8	19.8	19.8	19.8	19.8	19.8	19.8	19.8	19.8	19.8							
5	19.8	19.9	20.0	20.0	20.0	19.9	19.8	19.7	19.6	19.6	19.6	19.7							
10	19.7	19.9	20.1	20.1	20.1	19.9	19.7	19.5	19.3	19.2	19.3	19.5							
15	19.5	19.8	20.1	20.1	20.1	19.9	19.6	19.3	19.0	18.9	19.0	19.1							
20	19.1	19.5	20.0	20.0	20.1	19.7	19.3	18.9	18.6	18.4	18.5	18.7							
25	18.7	19.2	19.6	19.7	19.8	19.5	18.9	18.5	18.1	17.8	18.0	18.3							
30	18.1	18.7	19.0	19.1	19.4	19.1	18.4	18.0	17.6	17.2	17.4	17.7							
35	17.3	18.1	18.4	18.4	18.8	18.5	17.6	17.3	16.9	16.4	16.7	16.9							
40	16.3	17.3	17.5	17.4	18.0	17.7	16.8	16.4	16.1	15.5	15.8	16.1							
45	15.2	16.3	16.4	16.2	16.9	16.8	15.7	15.4	15.1	14.4	14.9	15.0							
50	14.0	15.0	15.1	14.8	15.5	15.5	14.5	14.2	14.0	13.1	13.8	13.8							
55	12.6	13.5	13.5	13.1	13.9	14.1	13.1	12.9	12.6	11.7	12.4	12.4							
60	11.0	11.9	11.7	11.3	12.1	12.4	11.5	11.3	10.9	10.0	10.8	10.9							
65	9.26	10.00	9.70	9.24	10.1	10.5	9.76	9.55	9.09	8.19	9.04	9.21							
70	7.44	8.00	7.60	7.03	7.86	8.40	7.86	7.63	7.14	6.22	7.09	7.40							
75	5.60	5.99	5.44	4.77	5.61	6.30	5.99	5.66	5.08	4.18	5.07	5.50							
80	3.92	4.14	3.40	2.59	3.54	4.56	4.39	3.90	3.15	2.23	3.18	3.71							
85	2.67	2.73	1.84	0.90	2.07	3.15	3.11	2.59	1.71	0.66	1.67	2.38							
90	1.88	1.81	1.12	0.06	1.34	2.20	2.25	1.94	1.12	0.00	0.97	1.67							
95	1.77	1.66	1.05	0.00	1.21	1.96	2.07	1.85	1.15	0.00	0.95	1.59							
100	1.82	1.66	1.06	0.00	1.22	2.00	2.12	1.90	1.20	0.00	0.95	1.57							
105	1.93	1.72	1.04	0.00	1.27	2.11	2.25	2.01	1.24	0.00	0.79	1.61							
110	2.04	1.83	0.90	0.00	1.27	2.31	2.43	2.17	1.18	0.00	0.55	1.57							
115	2.21	2.07	0.71	0.00	1.15	2.70	2.78	2.48	1.10	0.00	0.29	1.61							
120	2.55	2.32	0.21	0.00	0.87	3.46	3.45	3.02	0.92	0.00	0.06	1.30							
125	2.67	2.28	0.00	0.00	0.76	4.02	4.12	3.27	0.73	0.00	0.00	1.04							
130	2.15	1.35	0.00	0.00	0.56	3.14	4.22	2.59	0.49	0.00	0.00	0.62							
135	0.96	0.29	0.00	0.00	0.24	1.78	2.77	1.67	0.16	0.00	0.00	0.15							
140	0.14	0.00	0.00	0.00	0.11	0.94	1.25	0.92	0.06	0.00	0.00	0.01							
145	0.00	0.00	0.00	0.00	0.04	0.36	0.36	0.35	0.01	0.00	0.00	0.00							
150	0.00	0.00	0.00	0.00	0.02	0.15	0.19	0.16	0.00	0.00	0.00	0.00							
155	0.00	0.00	0.00	0.00	0.00	0.05	0.08	0.07	0.00	0.00	0.00	0.00							
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.00	0.00	0.00							
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00							
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00							
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00							
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00							

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:zhuo
Test Date:2022-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:6.070m [K=1.0000]
Remarks: