HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminaire Photometric Data


Description Information

Luminary Name: HCP-813024-2700K RA90 40D		Lum. Catelog:	Test ID: 01
Lamp Name:		Lamp Catelog: LED	Test Date: 2020/09/27
Manufacture: Havit Commercial		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency(Hz):	Lamp CCT(K): Ra:
Lum.Size(W*L*H):0.050m*0.000m*0.080m		Lum.Area(m2):0.016	Lum.W(kg): 0.000
Test System: C,γ	Test Step: C=90.0 γ=1.0	Temp.(℃): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 811.340	Luminary Flux(lm): 811.339	Field Angle(10%Imax): 87.3(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 802.259lm 98.88%
Rated Voltage(V):	Luminary EER(lm/W): 64.752	Up Lumens&Percent: 9.080lm 1.12%
Tested Power(W): 12.530	Max.Candela(cd): 1184.889	S/MH: C0_a180=0.622 C90_270=0.610
Lamps' Inside: 1	Max Cand@Ang.(°): C=0.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics(V,A,pf):240.2,0.055,0.945	Beam Angle(50%Imax): 40.3(°)	ErP Φuse(90°): 729.007lm
Lamp Size(W*L*H):0.050m*0.000m*0.080m	Left=-19.7° ,Right=20.6°	IRF(%): 316.346

C Plane Distribution Diagram




C0 Space ISO Illuminance Curve



HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

2D Plane Light Intensity Distribution Curve

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27




C Plane	[50%MaxAng.]	[10%MaxAng.]	Unit:cd
C0.0_180.0 :	40.3	87.3	
C90.0_270.0 :	39.6	87.2	

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Light Intensity Distribution Modal

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

3D Light Intensity Distribution Modal



Curves: 3D Model Fixture Vert. HUD Hori. HUD
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	1.13	1.13	0.14	0.14	47.0-48.0	4.34	756.63	0.53	93.26
1.0-2.0	3.36	4.48	0.41	0.55	48.0-49.0	3.57	760.20	0.44	93.70
2.0-3.0	5.55	10.03	0.68	1.24	49.0-50.0	3.03	763.24	0.37	94.07
3.0-4.0	7.67	17.70	0.94	2.18	50.0-51.0	2.68	765.91	0.33	94.40
4.0-5.0	9.68	27.37	1.19	3.37	51.0-52.0	2.42	768.33	0.30	94.70
5.0-6.0	11.55	38.92	1.42	4.80	52.0-53.0	2.22	770.55	0.27	94.97
6.0-7.0	13.25	52.17	1.63	6.43	53.0-54.0	2.08	772.63	0.26	95.23
7.0-8.0	14.77	66.94	1.82	8.25	54.0-55.0	1.97	774.60	0.24	95.47
8.0-9.0	16.10	83.04	1.98	10.24	55.0-56.0	1.87	776.47	0.23	95.70
9.0-10.0	17.25	100.29	2.13	12.36	56.0-57.0	1.77	778.24	0.22	95.92
10.0-11.0	18.22	118.52	2.25	14.61	57.0-58.0	1.68	779.91	0.21	96.13
11.0-12.0	19.06	137.58	2.35	16.96	58.0-59.0	1.58	781.49	0.19	96.32
12.0-13.0	19.78	157.36	2.44	19.39	59.0-60.0	1.49	782.98	0.18	96.50
13.0-14.0	20.38	177.73	2.51	21.91	60.0-61.0	1.40	784.38	0.17	96.68
14.0-15.0	20.88	198.61	2.57	24.48	61.0-62.0	1.32	785.70	0.16	96.84
15.0-16.0	21.30	219.91	2.63	27.10	62.0-63.0	1.23	786.93	0.15	96.99
16.0-17.0	21.64	241.55	2.67	29.77	63.0-64.0	1.15	788.07	0.14	97.13
17.0-18.0	21.89	263.44	2.70	32.47	64.0-65.0	1.07	789.14	0.13	97.26
18.0-19.0	22.07	285.51	2.72	35.19	65.0-66.0	0.99	790.13	0.12	97.39
19.0-20.0	22.16	307.67	2.73	37.92	66.0-67.0	0.91	791.04	0.11	97.50
20.0-21.0	22.17	329.84	2.73	40.65	67.0-68.0	0.85	791.89	0.10	97.60
21.0-22.0	22.10	351.94	2.72	43.38	68.0-69.0	0.79	792.68	0.10	97.70
22.0-23.0	21.95	373.89	2.71	46.08	69.0-70.0	0.75	793.43	0.09	97.79
23.0-24.0	21.74	395.63	2.68	48.76	70.0-71.0	0.71	794.14	0.09	97.88
24.0-25.0	21.46	417.09	2.64	51.41	71.0-72.0	0.67	794.81	0.08	97.96
25.0-26.0	21.11	438.20	2.60	54.01	72.0-73.0	0.63	795.44	0.08	98.04
26.0-27.0	20.70	458.89	2.55	56.56	73.0-74.0	0.60	796.05	0.07	98.11
27.0-28.0	20.24	479.13	2.49	59.05	74.0-75.0	0.57	796.62	0.07	98.19
28.0-29.0	19.77	498.91	2.44	61.49	75.0-76.0	0.55	797.16	0.07	98.25
29.0-30.0	19.33	518.24	2.38	63.87	76.0-77.0	0.52	797.68	0.06	98.32
30.0-31.0	18.93	537.17	2.33	66.21	77.0-78.0	0.50	798.18	0.06	98.38
31.0-32.0	18.57	555.74	2.29	68.50	78.0-79.0	0.48	798.66	0.06	98.44
32.0-33.0	18.24	573.98	2.25	70.75	79.0-80.0	0.45	799.11	0.06	98.49
33.0-34.0	17.94	591.92	2.21	72.96	80.0-81.0	0.43	799.54	0.05	98.55
34.0-35.0	17.59	609.51	2.17	75.12	81.0-82.0	0.41	799.95	0.05	98.60
35.0-36.0	17.15	626.67	2.11	77.24	82.0-83.0	0.39	800.34	0.05	98.64
36.0-37.0	16.61	643.27	2.05	79.29	83.0-84.0	0.36	800.70	0.04	98.69
37.0-38.0	15.91	659.18	1.96	81.25	84.0-85.0	0.34	801.04	0.04	98.73
38.0-39.0	15.05	674.24	1.86	83.10	85.0-86.0	0.31	801.35	0.04	98.77
39.0-40.0	14.06	688.30	1.73	84.84	86.0-87.0	0.28	801.64	0.04	98.80
40.0-41.0	12.96	701.26	1.60	86.43	87.0-88.0	0.25	801.88	0.03	98.83
41.0-42.0	11.75	713.01	1.45	87.88	88.0-89.0	0.21	802.09	0.03	98.86
42.0-43.0	10.46	723.47	1.29	89.17	89.0-90.0	0.17	802.26	0.02	98.88
43.0-44.0	9.14	732.61	1.13	90.30	90.0-91.0	0.15	802.41	0.02	98.90
44.0-45.0	7.81	740.42	0.96	91.26	91.0-92.0	0.14	802.55	0.02	98.92
45.0-46.0	6.53	746.95	0.80	92.06	92.0-93.0	0.13	802.68	0.02	98.93
46.0-47.0	5.35	752.29	0.66	92.72	93.0-94.0	0.12	802.80	0.01	98.95

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au


Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.11	802.91	0.01	98.96
95.0-96.0	0.11	803.02	0.01	98.97
96.0-97.0	0.10	803.12	0.01	98.99
97.0-98.0	0.09	803.21	0.01	99.00
98.0-99.0	0.09	803.30	0.01	99.01
99.0-100.0	0.08	803.38	0.01	99.02
100.0-101.0	0.08	803.45	0.01	99.03
101.0-102.0	0.07	803.53	0.01	99.04
102.0-103.0	0.07	803.59	0.01	99.05
103.0-104.0	0.06	803.66	0.01	99.05
104.0-105.0	0.06	803.72	0.01	99.06
105.0-106.0	0.06	803.78	0.01	99.07
106.0-107.0	0.06	803.84	0.01	99.08
107.0-108.0	0.06	803.89	0.01	99.08
108.0-109.0	0.05	803.95	0.01	99.09
109.0-110.0	0.05	804.00	0.01	99.10
110.0-111.0	0.05	804.05	0.01	99.10
111.0-112.0	0.05	804.10	0.01	99.11
112.0-113.0	0.05	804.16	0.01	99.11
113.0-114.0	0.05	804.21	0.01	99.12
114.0-115.0	0.05	804.27	0.01	99.13
115.0-116.0	0.06	804.32	0.01	99.13
116.0-117.0	0.06	804.38	0.01	99.14
117.0-118.0	0.06	804.44	0.01	99.15
118.0-119.0	0.06	804.50	0.01	99.16
119.0-120.0	0.06	804.56	0.01	99.16
120.0-121.0	0.07	804.63	0.01	99.17
121.0-122.0	0.07	804.70	0.01	99.18
122.0-123.0	0.07	804.77	0.01	99.19
123.0-124.0	0.08	804.85	0.01	99.20
124.0-125.0	0.08	804.93	0.01	99.21
125.0-126.0	0.08	805.01	0.01	99.22
126.0-127.0	0.09	805.10	0.01	99.23
127.0-128.0	0.09	805.19	0.01	99.24
128.0-129.0	0.10	805.29	0.01	99.25
129.0-130.0	0.10	805.39	0.01	99.27
130.0-131.0	0.11	805.50	0.01	99.28
131.0-132.0	0.11	805.61	0.01	99.29
132.0-133.0	0.11	805.72	0.01	99.31
133.0-134.0	0.12	805.84	0.01	99.32
134.0-135.0	0.12	805.96	0.02	99.34
135.0-136.0	0.13	806.09	0.02	99.35
136.0-137.0	0.13	806.23	0.02	99.37
137.0-138.0	0.14	806.36	0.02	99.39
138.0-139.0	0.14	806.51	0.02	99.40
139.0-140.0	0.15	806.65	0.02	99.42
140.0-141.0	0.15	806.80	0.02	99.44
141.0-142.0	0.15	806.95	0.02	99.46
142.0-143.0	0.16	807.11	0.02	99.48
143.0-144.0	0.16	807.27	0.02	99.50
144.0-145.0	0.16	807.43	0.02	99.52
145.0-146.0	0.16	807.59	0.02	99.54
146.0-147.0	0.16	807.75	0.02	99.56
147.0-148.0	0.16	807.92	0.02	99.58
148.0-149.0	0.16	808.08	0.02	99.60
149.0-150.0	0.16	808.24	0.02	99.62
150.0-151.0	0.16	808.41	0.02	99.64
151.0-152.0	0.16	808.57	0.02	99.66
152.0-153.0	0.16	808.73	0.02	99.68
153.0-154.0	0.16	808.89	0.02	99.70
154.0-155.0	0.16	809.05	0.02	99.72
155.0-156.0	0.15	809.20	0.02	99.74
156.0-157.0	0.15	809.36	0.02	99.76
157.0-158.0	0.15	809.51	0.02	99.77
158.0-159.0	0.15	809.65	0.02	99.79
159.0-160.0	0.14	809.79	0.02	99.81
160.0-161.0	0.14	809.93	0.02	99.83
161.0-162.0	0.13	810.06	0.02	99.84
162.0-163.0	0.13	810.19	0.02	99.86
163.0-164.0	0.12	810.31	0.02	99.87
164.0-165.0	0.12	810.43	0.01	99.89
165.0-166.0	0.11	810.54	0.01	99.90
166.0-167.0	0.10	810.64	0.01	99.91
167.0-168.0	0.10	810.74	0.01	99.93
168.0-169.0	0.09	810.84	0.01	99.94
169.0-170.0	0.08	810.92	0.01	99.95
170.0-171.0	0.08	811.00	0.01	99.96
171.0-172.0	0.07	811.07	0.01	99.97
172.0-173.0	0.06	811.13	0.01	99.97
173.0-174.0	0.05	811.18	0.01	99.98
174.0-175.0	0.05	811.23	0.01	99.99
175.0-176.0	0.04	811.27	0.00	99.99
176.0-177.0	0.03	811.30	0.00	100.00
177.0-178.0	0.02	811.32	0.00	100.00
178.0-179.0	0.01	811.33	0.00	100.00
179.0-180.0	0.00	811.34	0.00	100.00

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Rectangle ISO Lighting Intensity Diagram

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27




Maximum Light Intensity(cd): 1184.89
Maximum Cand.@Angle: H=1.0°,V=0.0°

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Plane ISO-Illuminance Diagram

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 131.59
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Plane ISO Illuminance Diagram

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

3D Plane Illuminance Modal




Curves: 3D Model 90% 80% 70% 60% 50% 40% 30% 20% 10%
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Space ISO Illuminance Diagram

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

Space ISO Illuminance Curve




Space Plane Maximum Illuminance and @Angle:1184.35lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:1184.889cd,0eg

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Illuminance-Distance Diagram

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

Illuminance-Distance Curve



Beam Angle:40.3

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminance Limiting Curves

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27


Glare Grade Table

GI	Quality	Using Illuminace							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	9239	3826	2653	2186	1800	1521	1497	1712	2505
C90	6414	2830	2200	1781	1374	1147	1095	1253	1733

Luminance Limiting Curve




Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.080 Area(m^2)=0.015708
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Budgetary Estimate Table

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Coefficient of Utilization Table

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC(%)	80				70				50			30			10			0
RhoW(%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	110	110	110	106	106	106	101	101	101	99
1	113	110	107	105	110	107	105	103	103	101	100	99	98	96	96	94	93	91
2	107	102	97	94	104	100	96	92	96	93	90	93	90	88	90	88	86	84
3	101	94	89	85	99	93	88	84	90	86	82	87	84	81	85	82	80	78
4	96	88	82	77	94	86	81	77	84	79	76	82	78	75	80	77	74	72
5	91	82	76	71	89	81	75	71	79	74	70	77	73	69	75	72	69	67
6	86	77	70	66	84	76	70	66	74	69	65	73	68	65	71	67	64	62
7	82	72	66	61	80	71	65	61	70	64	61	68	64	60	67	63	60	58
8	77	68	61	57	76	67	61	57	66	61	57	65	60	56	64	59	56	55
9	74	64	58	54	73	63	57	54	62	57	53	61	56	53	60	56	53	51
10	70	60	54	50	69	60	54	50	59	54	50	58	53	50	57	53	50	48

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Unified Glare Rating Table

Lum.Name: HCP-813024-2700K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/09/27

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	16.0	17.1	16.4	17.4	17.8	15.0	16.1	15.4	16.4	16.8
	Y=3H	16.0	17.0	16.4	17.3	17.7	15.0	15.9	15.4	16.3	16.7
	Y=4H	16.0	16.9	16.4	17.3	17.7	15.0	15.8	15.4	16.2	16.6
	Y=6H	16.0	16.8	16.5	17.2	17.7	14.9	15.8	15.4	16.2	16.6
	Y=8H	16.0	16.8	16.5	17.2	17.7	14.9	15.7	15.4	16.1	16.6
	Y=12H	16.1	16.8	16.5	17.2	17.7	15.0	15.7	15.4	16.1	16.6
X=4H	Y=2H	15.8	16.7	16.3	17.1	17.5	14.8	15.7	15.3	16.1	16.5
	Y=3H	15.9	16.6	16.3	17.0	17.5	14.9	15.6	15.3	16.0	16.4
	Y=4H	15.9	16.6	16.4	17.0	17.5	14.9	15.5	15.3	16.0	16.4
	Y=6H	16.0	16.6	16.5	17.1	17.5	14.9	15.5	15.4	16.0	16.5
	Y=8H	16.1	16.6	16.6	17.1	17.6	14.9	15.5	15.4	16.0	16.5
	Y=12H	16.2	16.6	16.7	17.1	17.7	15.0	15.5	15.5	16.0	16.5
X=8H	Y=4H	15.8	16.4	16.3	16.8	17.3	14.8	15.3	15.3	15.8	16.3
	Y=6H	16.0	16.4	16.5	16.9	17.5	14.9	15.3	15.4	15.8	16.4
	Y=8H	16.1	16.5	16.7	17.0	17.6	15.0	15.4	15.5	15.9	16.4
	Y=12H	16.3	16.7	16.9	17.2	17.8	15.1	15.5	15.7	16.0	16.6
X=12H	Y=4H	15.8	16.3	16.3	16.8	17.3	14.7	15.2	15.2	15.7	16.2
	Y=6H	16.0	16.4	16.5	16.9	17.4	14.9	15.3	15.4	15.8	16.3
	Y=8H	16.1	16.5	16.7	17.0	17.6	15.0	15.3	15.5	15.9	16.5
Variations with the observer position at spacings											
S=1.0H		0.2/-0.2					0.2/-0.3				
S=1.5H		0.4/-0.4					0.4/-0.5				
S=2.0H		0.7/-0.6					0.8/-0.7				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.7					0.6				

o the CIE Pub.117,data has been corrected,refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1178.94	1178.94	1178.94	1178.94
γ 1.0	1184.89	1156.96	1180.89	1172.29
γ 2.0	1179.21	1143.33	1170.48	1170.69
γ 3.0	1169.83	1126.76	1156.22	1160.60
γ 4.0	1157.15	1104.22	1137.29	1147.93
γ 5.0	1134.50	1075.54	1110.89	1129.99
γ 6.0	1106.09	1044.14	1078.25	1109.21
γ 7.0	1071.26	1007.28	1041.92	1081.74
γ 8.0	1034.96	967.37	1002.04	1047.82
γ 9.0	994.71	929.72	960.39	1010.83
γ 10.0	953.75	884.16	918.72	972.85
γ 11.0	912.42	843.58	877.25	932.82
γ 12.0	871.86	804.34	838.92	893.89
γ 13.0	833.45	766.73	802.49	854.29
γ 14.0	797.92	729.81	767.90	814.84
γ 15.0	763.98	697.15	734.33	777.20
γ 16.0	731.73	665.39	702.08	742.95
γ 17.0	699.83	634.41	670.65	711.15
γ 18.0	668.58	605.66	641.08	679.76
γ 19.0	639.11	577.78	612.20	649.19
γ 20.0	610.43	550.91	583.20	620.27
γ 21.0	582.66	524.10	555.47	591.10
γ 22.0	555.51	498.38	528.17	563.19
γ 23.0	529.22	473.60	501.36	535.53
γ 24.0	503.03	449.75	475.30	509.22
γ 25.0	477.66	425.37	450.29	484.45
γ 26.0	452.39	402.29	426.10	458.70
γ 27.0	427.20	380.35	402.54	434.15
γ 28.0	402.97	360.06	380.60	410.02
γ 29.0	380.71	341.54	360.12	387.15
γ 30.0	360.96	325.20	341.73	366.11
γ 31.0	343.63	310.89	324.73	347.83
γ 32.0	327.67	297.15	309.81	331.31
γ 33.0	313.83	284.68	296.70	315.93
γ 34.0	301.24	272.26	284.07	302.27
γ 35.0	288.16	257.54	270.29	289.90
γ 36.0	274.58	241.76	256.48	276.16
γ 37.0	260.02	224.19	241.43	262.04
γ 38.0	243.12	205.90	223.89	246.16
γ 39.0	224.73	186.94	204.46	228.74
γ 40.0	205.54	167.27	184.59	210.82
γ 41.0	185.29	146.61	163.58	192.04
γ 42.0	164.22	126.74	142.20	172.66
γ 43.0	143.21	106.97	121.17	152.79
γ 44.0	122.32	88.46	100.77	132.61
γ 45.0	102.62	71.25	81.88	112.86
γ 46.0	84.09	56.28	64.90	93.94

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	67.22	44.37	50.42	76.52
γ 48.0	53.80	36.13	40.07	60.78
γ 49.0	44.84	31.51	33.09	47.37
γ 50.0	38.63	28.58	28.99	38.15
γ 51.0	34.11	25.85	26.01	32.79
γ 52.0	30.43	23.92	23.50	28.81
γ 53.0	27.39	22.54	21.83	25.81
γ 54.0	25.59	21.11	20.50	23.90
γ 55.0	23.91	19.82	19.14	22.45
γ 56.0	22.40	18.65	17.92	21.04
γ 57.0	21.03	17.36	16.74	19.78
γ 58.0	19.75	16.07	15.59	18.56
γ 59.0	18.39	14.96	14.43	17.36
γ 60.0	17.17	13.99	13.43	16.10
γ 61.0	16.12	13.01	12.51	15.04
γ 62.0	15.08	11.90	11.59	14.08
γ 63.0	13.99	10.93	10.61	13.16
γ 64.0	12.87	10.08	9.76	12.15
γ 65.0	11.95	9.12	9.00	11.19
γ 66.0	11.00	8.31	8.17	10.41
γ 67.0	10.06	7.67	7.47	9.57
γ 68.0	9.35	7.11	6.97	8.81
γ 69.0	8.73	6.60	6.52	8.24
γ 70.0	8.17	6.16	6.12	7.72
γ 71.0	7.68	5.74	5.77	7.29
γ 72.0	7.22	5.38	5.47	6.91
γ 73.0	6.80	5.03	5.17	6.56
γ 74.0	6.43	4.74	4.91	6.22
γ 75.0	6.09	4.45	4.64	5.91
γ 76.0	5.75	4.21	4.40	5.64
γ 77.0	5.45	3.98	4.19	5.40
γ 78.0	5.20	3.78	4.00	5.20
γ 79.0	4.93	3.60	3.77	4.95
γ 80.0	4.67	3.42	3.56	4.71
γ 81.0	4.43	3.24	3.34	4.47
γ 82.0	4.20	3.05	3.16	4.25
γ 83.0	3.93	2.84	2.94	4.04
γ 84.0	3.73	2.58	2.75	3.81
γ 85.0	3.43	2.37	2.53	3.62
γ 86.0	3.20	2.13	2.32	3.36
γ 87.0	2.90	1.67	2.09	3.13
γ 88.0	2.47	1.19	1.70	2.91
γ 89.0	2.00	1.00	1.30	2.43
γ 90.0	1.67	0.93	1.17	1.93
γ 91.0	1.57	0.86	1.09	1.71
γ 92.0	1.47	0.79	1.01	1.61
γ 93.0	1.39	0.73	0.94	1.52

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	1.31	0.67	0.89	1.43
γ 95.0	1.23	0.62	0.83	1.35
γ 96.0	1.15	0.56	0.76	1.27
γ 97.0	1.09	0.52	0.71	1.20
γ 98.0	1.02	0.46	0.67	1.13
γ 99.0	0.96	0.44	0.62	1.08
γ 100.0	0.91	0.40	0.59	1.02
γ 101.0	0.86	0.38	0.56	0.97
γ 102.0	0.82	0.34	0.53	0.92
γ 103.0	0.78	0.32	0.50	0.88
γ 104.0	0.75	0.31	0.48	0.83
γ 105.0	0.70	0.29	0.47	0.80
γ 106.0	0.69	0.29	0.45	0.77
γ 107.0	0.66	0.28	0.45	0.75
γ 108.0	0.65	0.28	0.45	0.73
γ 109.0	0.62	0.27	0.45	0.72
γ 110.0	0.62	0.28	0.45	0.70
γ 111.0	0.61	0.28	0.46	0.70
γ 112.0	0.60	0.29	0.47	0.69
γ 113.0	0.61	0.31	0.50	0.70
γ 114.0	0.61	0.32	0.50	0.70
γ 115.0	0.62	0.34	0.53	0.71
γ 116.0	0.63	0.37	0.57	0.72
γ 117.0	0.64	0.39	0.60	0.74
γ 118.0	0.65	0.43	0.64	0.76
γ 119.0	0.69	0.46	0.68	0.79
γ 120.0	0.71	0.50	0.72	0.81
γ 121.0	0.74	0.54	0.76	0.85
γ 122.0	0.77	0.60	0.82	0.88
γ 123.0	0.80	0.64	0.87	0.93
γ 124.0	0.85	0.69	0.94	0.97
γ 125.0	0.90	0.76	0.99	1.01
γ 126.0	0.95	0.82	1.05	1.06
γ 127.0	1.00	0.88	1.12	1.11
γ 128.0	1.06	0.95	1.19	1.17
γ 129.0	1.12	1.02	1.26	1.22
γ 130.0	1.19	1.09	1.34	1.29
γ 131.0	1.26	1.18	1.42	1.36
γ 132.0	1.34	1.26	1.51	1.41
γ 133.0	1.40	1.34	1.59	1.49
γ 134.0	1.49	1.43	1.69	1.57
γ 135.0	1.57	1.53	1.77	1.65
γ 136.0	1.65	1.62	1.87	1.73
γ 137.0	1.75	1.72	1.97	1.82
γ 138.0	1.84	1.82	2.08	1.91
γ 139.0	1.93	1.90	2.18	2.00
γ 140.0	2.02	2.00	2.27	2.10

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	2.11	2.09	2.37	2.18
γ 142.0	2.20	2.20	2.47	2.27
γ 143.0	2.29	2.28	2.56	2.36
γ 144.0	2.38	2.39	2.65	2.46
γ 145.0	2.48	2.46	2.75	2.54
γ 146.0	2.56	2.57	2.85	2.63
γ 147.0	2.66	2.65	2.93	2.72
γ 148.0	2.74	2.73	3.02	2.79
γ 149.0	2.82	2.82	3.09	2.88
γ 150.0	2.91	2.91	3.18	2.95
γ 151.0	2.99	2.98	3.26	3.03
γ 152.0	3.08	3.07	3.33	3.11
γ 153.0	3.16	3.14	3.42	3.19
γ 154.0	3.24	3.21	3.49	3.26
γ 155.0	3.32	3.30	3.56	3.32
γ 156.0	3.39	3.36	3.63	3.39
γ 157.0	3.47	3.43	3.71	3.46
γ 158.0	3.54	3.49	3.78	3.52
γ 159.0	3.61	3.56	3.84	3.59
γ 160.0	3.68	3.63	3.91	3.65
γ 161.0	3.74	3.70	3.96	3.70
γ 162.0	3.81	3.76	4.03	3.77
γ 163.0	3.88	3.83	4.07	3.82
γ 164.0	3.94	3.88	4.14	3.88
γ 165.0	4.01	3.94	4.19	3.94
γ 166.0	4.05	4.00	4.25	3.98
γ 167.0	4.11	4.05	4.29	4.03
γ 168.0	4.18	4.12	4.33	4.07
γ 169.0	4.22	4.15	4.38	4.12
γ 170.0	4.26	4.20	4.42	4.17
γ 171.0	4.32	4.24	4.45	4.21
γ 172.0	4.36	4.29	4.50	4.25
γ 173.0	4.40	4.33	4.53	4.29
γ 174.0	4.45	4.36	4.55	4.32
γ 175.0	4.48	4.39	4.59	4.35
γ 176.0	4.50	4.42	4.60	4.38
γ 177.0	4.53	4.45	4.62	4.41
γ 178.0	4.54	4.46	4.63	4.43
γ 179.0	4.56	4.47	4.65	4.45
γ 180.0	4.56	4.56	4.56	4.56