

Indoor Luminaire Photometric Data


Description Information

Luminary Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2020/10/12
Manufacture: Havit Commercial	Shld. Ang(°):	Test Machine: GON-2000
Test Lab: Quality Department	Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H): 0.050m*0.000m*0.080m	Lum. Area (m2): 0.016	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity (%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 956.880	Luminary Flux(lm): 956.878	Field Angle(10%Imax): 83.5(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 943.752lm 98.63%
Rated Voltage(V):	Luminary EER(lm/W): 59.397	Up Lumens&Percent: 13.126lm 1.37%
Tested Power(W): 16.110	Max. Candela(cd): 1831.594	S/MH: C0_a180=0.440 C90_270=0.434
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=2.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf): 240.2, 0.069, 0.968	Beam Angle(50%Imax): 26.8(°)	ErP Φ use(90°): 846.696lm
Lamp Size (W*L*H): 0.050m*0.000m*0.080m	Left=-11.4°, Right=15.4°	IRF (%): 399.355

C Plane Distribution Diagram




C0 Space ISO Illuminance Curve



2D Plane Light Intensity Distribution Curve

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12


C Plane Distribution Diagram



3D Light Intensity Distribution Modal

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	1.73	1.73	0.18	0.18	47.0-48.0	5.28	887.51	0.55	92.75
1.0-2.0	5.13	6.85	0.54	0.72	48.0-49.0	4.37	891.88	0.46	93.21
2.0-3.0	8.34	15.19	0.87	1.59	49.0-50.0	3.71	895.59	0.39	93.59
3.0-4.0	11.27	26.46	1.18	2.77	50.0-51.0	3.26	898.85	0.34	93.94
4.0-5.0	13.86	40.32	1.45	4.21	51.0-52.0	2.94	901.79	0.31	94.24
5.0-6.0	16.05	56.37	1.68	5.89	52.0-53.0	2.69	904.47	0.28	94.52
6.0-7.0	17.86	74.23	1.87	7.76	53.0-54.0	2.48	906.96	0.26	94.78
7.0-8.0	19.31	93.54	2.02	9.78	54.0-55.0	2.31	909.27	0.24	95.02
8.0-9.0	20.44	113.98	2.14	11.91	55.0-56.0	2.16	911.43	0.23	95.25
9.0-10.0	21.31	135.29	2.23	14.14	56.0-57.0	2.03	913.47	0.21	95.46
10.0-11.0	21.95	157.24	2.29	16.43	57.0-58.0	1.92	915.39	0.20	95.66
11.0-12.0	22.46	179.70	2.35	18.78	58.0-59.0	1.82	917.20	0.19	95.85
12.0-13.0	22.90	202.60	2.39	21.17	59.0-60.0	1.72	918.92	0.18	96.03
13.0-14.0	23.29	225.89	2.43	23.61	60.0-61.0	1.64	920.56	0.17	96.20
14.0-15.0	23.64	249.53	2.47	26.08	61.0-62.0	1.56	922.12	0.16	96.37
15.0-16.0	23.94	273.48	2.50	28.58	62.0-63.0	1.48	923.60	0.16	96.52
16.0-17.0	24.21	297.68	2.53	31.11	63.0-64.0	1.41	925.01	0.15	96.67
17.0-18.0	24.45	322.13	2.56	33.66	64.0-65.0	1.34	926.35	0.14	96.81
18.0-19.0	24.63	346.76	2.57	36.24	65.0-66.0	1.27	927.62	0.13	96.94
19.0-20.0	24.75	371.52	2.59	38.83	66.0-67.0	1.19	928.81	0.12	97.07
20.0-21.0	24.82	396.33	2.59	41.42	67.0-68.0	1.12	929.93	0.12	97.18
21.0-22.0	24.80	421.13	2.59	44.01	68.0-69.0	1.05	930.98	0.11	97.29
22.0-23.0	24.69	445.82	2.58	46.59	69.0-70.0	0.99	931.98	0.10	97.40
23.0-24.0	24.50	470.32	2.56	49.15	70.0-71.0	0.94	932.92	0.10	97.50
24.0-25.0	24.23	494.55	2.53	51.68	71.0-72.0	0.89	933.81	0.09	97.59
25.0-26.0	23.89	518.44	2.50	54.18	72.0-73.0	0.85	934.67	0.09	97.68
26.0-27.0	23.48	541.92	2.45	56.63	73.0-74.0	0.81	935.48	0.09	97.76
27.0-28.0	23.03	564.96	2.41	59.04	74.0-75.0	0.78	936.26	0.08	97.84
28.0-29.0	22.59	587.54	2.36	61.40	75.0-76.0	0.74	937.00	0.08	97.92
29.0-30.0	22.17	609.71	2.32	63.72	76.0-77.0	0.70	937.70	0.07	98.00
30.0-31.0	21.79	631.49	2.28	66.00	77.0-78.0	0.67	938.37	0.07	98.07
31.0-32.0	21.45	652.94	2.24	68.24	78.0-79.0	0.63	939.00	0.07	98.13
32.0-33.0	21.15	674.10	2.21	70.45	79.0-80.0	0.60	939.60	0.06	98.19
33.0-34.0	20.85	694.95	2.18	72.63	80.0-81.0	0.56	940.16	0.06	98.25
34.0-35.0	20.50	715.45	2.14	74.77	81.0-82.0	0.53	940.69	0.06	98.31
35.0-36.0	20.01	735.46	2.09	76.86	82.0-83.0	0.50	941.20	0.05	98.36
36.0-37.0	19.36	754.82	2.02	78.88	83.0-84.0	0.47	941.67	0.05	98.41
37.0-38.0	18.54	773.35	1.94	80.82	84.0-85.0	0.44	942.11	0.05	98.46
38.0-39.0	17.54	790.89	1.83	82.65	85.0-86.0	0.41	942.52	0.04	98.50
39.0-40.0	16.37	807.26	1.71	84.36	86.0-87.0	0.37	942.89	0.04	98.54
40.0-41.0	15.08	822.34	1.58	85.94	87.0-88.0	0.33	943.22	0.03	98.57
41.0-42.0	13.68	836.02	1.43	87.37	88.0-89.0	0.29	943.50	0.03	98.60
42.0-43.0	12.20	848.22	1.28	88.64	89.0-90.0	0.25	943.75	0.03	98.63
43.0-44.0	10.68	858.90	1.12	89.76	90.0-91.0	0.22	943.98	0.02	98.65
44.0-45.0	9.18	868.08	0.96	90.72	91.0-92.0	0.21	944.18	0.02	98.67
45.0-46.0	7.74	875.81	0.81	91.53	92.0-93.0	0.19	944.38	0.02	98.69
46.0-47.0	6.42	882.23	0.67	92.20	93.0-94.0	0.18	944.56	0.02	98.71


Zonal Flux Tabulation - (Cont.)

Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.18	944.74	0.02	98.73	141.0-142.0	0.21	951.17	0.02	99.40
95.0-96.0	0.17	944.90	0.02	98.75	142.0-143.0	0.21	951.38	0.02	99.43
96.0-97.0	0.16	945.06	0.02	98.76	143.0-144.0	0.21	951.60	0.02	99.45
97.0-98.0	0.15	945.21	0.02	98.78	144.0-145.0	0.21	951.81	0.02	99.47
98.0-99.0	0.14	945.35	0.01	98.80	145.0-146.0	0.22	952.03	0.02	99.49
99.0-100.0	0.14	945.49	0.01	98.81	146.0-147.0	0.22	952.24	0.02	99.52
100.0-101.0	0.13	945.62	0.01	98.82	147.0-148.0	0.22	952.46	0.02	99.54
101.0-102.0	0.13	945.75	0.01	98.84	148.0-149.0	0.22	952.68	0.02	99.56
102.0-103.0	0.12	945.87	0.01	98.85	149.0-150.0	0.22	952.90	0.02	99.58
103.0-104.0	0.12	945.99	0.01	98.86	150.0-151.0	0.21	953.11	0.02	99.61
104.0-105.0	0.11	946.10	0.01	98.87	151.0-152.0	0.21	953.32	0.02	99.63
105.0-106.0	0.11	946.21	0.01	98.88	152.0-153.0	0.21	953.54	0.02	99.65
106.0-107.0	0.11	946.32	0.01	98.90	153.0-154.0	0.21	953.74	0.02	99.67
107.0-108.0	0.11	946.42	0.01	98.91	154.0-155.0	0.21	953.95	0.02	99.69
108.0-109.0	0.10	946.53	0.01	98.92	155.0-156.0	0.20	954.15	0.02	99.71
109.0-110.0	0.10	946.63	0.01	98.93	156.0-157.0	0.20	954.35	0.02	99.74
110.0-111.0	0.10	946.73	0.01	98.94	157.0-158.0	0.19	954.54	0.02	99.76
111.0-112.0	0.10	946.84	0.01	98.95	158.0-159.0	0.19	954.73	0.02	99.77
112.0-113.0	0.10	946.94	0.01	98.96	159.0-160.0	0.18	954.91	0.02	99.79
113.0-114.0	0.10	947.04	0.01	98.97	160.0-161.0	0.18	955.09	0.02	99.81
114.0-115.0	0.10	947.15	0.01	98.98	161.0-162.0	0.17	955.26	0.02	99.83
115.0-116.0	0.11	947.25	0.01	98.99	162.0-163.0	0.16	955.42	0.02	99.85
116.0-117.0	0.11	947.36	0.01	99.00	163.0-164.0	0.16	955.58	0.02	99.86
117.0-118.0	0.11	947.47	0.01	99.02	164.0-165.0	0.15	955.72	0.02	99.88
118.0-119.0	0.11	947.58	0.01	99.03	165.0-166.0	0.14	955.87	0.01	99.89
119.0-120.0	0.11	947.69	0.01	99.04	166.0-167.0	0.13	956.00	0.01	99.91
120.0-121.0	0.11	947.80	0.01	99.05	167.0-168.0	0.13	956.13	0.01	99.92
121.0-122.0	0.12	947.92	0.01	99.06	168.0-169.0	0.12	956.24	0.01	99.93
122.0-123.0	0.12	948.04	0.01	99.08	169.0-170.0	0.11	956.35	0.01	99.94
123.0-124.0	0.12	948.17	0.01	99.09	170.0-171.0	0.10	956.45	0.01	99.95
124.0-125.0	0.13	948.29	0.01	99.10	171.0-172.0	0.09	956.54	0.01	99.96
125.0-126.0	0.13	948.43	0.01	99.12	172.0-173.0	0.08	956.62	0.01	99.97
126.0-127.0	0.14	948.56	0.01	99.13	173.0-174.0	0.07	956.68	0.01	99.98
127.0-128.0	0.14	948.70	0.01	99.15	174.0-175.0	0.06	956.74	0.01	99.99
128.0-129.0	0.14	948.85	0.02	99.16	175.0-176.0	0.05	956.79	0.01	99.99
129.0-130.0	0.15	949.00	0.02	99.18	176.0-177.0	0.04	956.83	0.00	99.99
130.0-131.0	0.15	949.15	0.02	99.19	177.0-178.0	0.03	956.86	0.00	100.00
131.0-132.0	0.16	949.31	0.02	99.21	178.0-179.0	0.02	956.87	0.00	100.00
132.0-133.0	0.16	949.47	0.02	99.23	179.0-180.0	0.01	956.88	0.00	100.00
133.0-134.0	0.17	949.64	0.02	99.24					
134.0-135.0	0.17	949.82	0.02	99.26					
135.0-136.0	0.18	950.00	0.02	99.28					
136.0-137.0	0.18	950.18	0.02	99.30					
137.0-138.0	0.19	950.37	0.02	99.32					
138.0-139.0	0.19	950.57	0.02	99.34					
139.0-140.0	0.20	950.76	0.02	99.36					
140.0-141.0	0.20	950.97	0.02	99.38					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

ISO Lighting Intensity Curve




Maximum Light Intensity(cd): 1831.59

Maximum Cand.@Angle: H=2.0°,V=0.0°

Plane ISO-Illuminance Diagram

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 203.14

Working Plane Maximum Illuminance Position(d/h): H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

3D Plane Illuminance Model




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

Space ISO Illuminance Curve



Curves:

[Unit: lx]

[E_{Max}] = 1828.249

— [E_{Max}*90%]=1645.424

— [E_{Max}*80%]=1462.599

— [E_{Max}*70%]=1279.774

— [E_{Max}*60%]=1096.949

— [E_{Max}*50%]=914.124

— [E_{Max}*40%]=731.300

— [E_{Max}*30%]=548.475

— [E_{Max}*20%]=365.650

— [E_{Max}*10%]=182.825


Space Plane Maximum Illuminance and @Angle:1828.25lx,2.0deg

Plane Maximum Lighting Intensity and @Angle:1831.594cd,0deg

Illuminance-Distance Diagram

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

Illuminance-Distance Curve



Indoor Luminance Limiting Curves

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	13805	5432	3397	2774	2449	2157	2083	2334	3419
C90	8809	3649	2628	2103	1800	1517	1487	1600	2229

Luminance Limiting Curve




Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.080 Area(m^2)=0.015708

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101	99
1	113	110	107	105	110	107	105	103	103	101	99	99	98	96	95	94	93	91
2	107	102	97	94	104	100	96	92	96	93	90	93	90	88	90	88	86	84
3	101	94	89	85	99	93	88	84	90	86	82	87	84	81	85	82	80	78
4	96	88	82	78	94	87	81	77	84	80	76	82	78	75	80	77	74	72
5	91	82	76	71	89	81	75	71	79	74	70	77	73	70	75	72	69	67
6	86	77	71	66	84	76	70	66	74	69	65	73	68	65	71	67	64	63
7	82	72	66	62	80	71	66	61	70	65	61	69	64	61	67	63	60	59
8	78	68	62	58	77	67	62	58	66	61	57	65	60	57	64	60	57	55
9	74	64	58	54	73	64	58	54	63	57	54	62	57	54	61	56	53	52
10	71	61	55	51	70	60	55	51	60	54	51	59	54	51	58	54	50	49

Unified Glare Rating Table

Lum. Name: HCP-817024-2700K RA90 28D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/10/12

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	17.2	18.3	17.6	18.6	19.0	15.8	16.9	16.2	17.3	17.6
	17.2	18.2	17.6	18.6	19.0	15.8	16.8	16.2	17.2	17.6
	17.2	18.1	17.7	18.5	19.0	15.8	16.7	16.2	17.1	17.5
	17.3	18.1	17.7	18.5	18.9	15.8	16.7	16.3	17.1	17.5
	17.3	18.1	17.8	18.5	19.0	15.8	16.6	16.3	17.0	17.5
	17.3	18.1	17.8	18.5	19.0	15.8	16.6	16.3	17.0	17.5
X=4H Y=2H	17.0	17.9	17.5	18.3	18.7	15.7	16.6	16.1	17.0	17.4
	17.1	17.9	17.5	18.3	18.7	15.7	16.5	16.2	16.9	17.3
	17.2	17.8	17.6	18.3	18.8	15.7	16.4	16.2	16.9	17.4
	17.3	17.9	17.8	18.3	18.8	15.8	16.4	16.3	16.9	17.4
	17.3	17.9	17.8	18.4	18.9	15.9	16.4	16.3	16.9	17.4
	17.5	17.9	18.0	18.5	19.0	15.9	16.4	16.4	16.9	17.4
X=8H Y=4H	17.1	17.6	17.6	18.1	18.6	15.7	16.2	16.2	16.7	17.2
	17.3	17.7	17.8	18.2	18.8	15.8	16.3	16.3	16.8	17.4
	17.4	17.8	18.0	18.4	18.9	15.9	16.3	16.5	16.9	17.4
	17.6	18.0	18.2	18.5	19.1	16.1	16.4	16.6	16.9	17.5
X=12H Y=4H	17.0	17.5	17.6	18.0	18.6	15.6	16.1	16.2	16.6	17.1
	17.3	17.7	17.8	18.2	18.7	15.8	16.2	16.4	16.7	17.3
	17.4	17.8	18.0	18.3	18.9	15.9	16.3	16.5	16.8	17.4
Variations with the observer position at spacings										
S=1.0H	0.2/−0.2					0.3/−0.3				
S=1.5H	0.4/−0.4					0.5/−0.5				
S=2.0H	0.7/−0.6					0.8/−0.7				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.8					0.7				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1805.91	1805.91	1805.91	1805.91
γ 1.0	1827.10	1823.26	1738.15	1820.15
γ 2.0	1831.59	1788.91	1665.67	1788.82
γ 3.0	1814.88	1729.75	1579.48	1745.01
γ 4.0	1779.42	1650.39	1486.84	1684.60
γ 5.0	1730.73	1558.91	1391.80	1601.80
γ 6.0	1664.05	1465.11	1298.70	1504.54
γ 7.0	1580.13	1376.58	1210.14	1408.91
γ 8.0	1484.33	1288.07	1127.97	1317.01
γ 9.0	1387.14	1199.70	1056.95	1228.53
γ 10.0	1293.36	1111.49	994.21	1145.84
γ 11.0	1206.36	1031.24	937.15	1068.91
γ 12.0	1126.89	962.69	883.75	1001.77
γ 13.0	1055.65	908.32	836.62	942.15
γ 14.0	991.95	858.97	795.48	890.50
γ 15.0	934.14	815.04	758.88	843.75
γ 16.0	882.15	774.46	724.81	802.20
γ 17.0	838.37	738.48	692.51	764.57
γ 18.0	798.91	704.98	662.39	731.24
γ 19.0	762.42	672.59	632.50	698.42
γ 20.0	729.08	643.05	604.85	666.96
γ 21.0	697.13	615.09	577.72	635.82
γ 22.0	666.61	586.68	549.94	606.71
γ 23.0	637.39	559.09	521.93	578.36
γ 24.0	608.39	531.94	494.45	550.55
γ 25.0	580.72	505.15	468.13	523.15
γ 26.0	552.64	478.66	442.97	497.11
γ 27.0	524.55	452.62	419.11	471.62
γ 28.0	497.64	428.03	398.87	446.71
γ 29.0	472.62	405.35	380.41	423.59
γ 30.0	447.86	386.42	364.54	402.96
γ 31.0	424.48	370.08	349.69	385.35
γ 32.0	404.94	354.72	336.47	369.05
γ 33.0	388.07	340.91	323.34	354.57
γ 34.0	371.98	327.57	308.94	341.09
γ 35.0	358.28	313.48	291.02	327.49
γ 36.0	345.26	296.10	270.32	312.10
γ 37.0	332.72	275.93	247.92	293.81
γ 38.0	317.23	255.25	224.05	274.35
γ 39.0	298.85	232.82	199.14	253.45
γ 40.0	277.59	209.94	174.77	231.16
γ 41.0	254.20	186.96	149.67	209.15
γ 42.0	230.17	163.63	125.89	186.32
γ 43.0	204.17	140.91	102.90	163.55
γ 44.0	178.35	118.53	82.73	140.96
γ 45.0	153.34	97.84	65.22	118.31
γ 46.0	128.50	78.45	52.63	96.86

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	105.64	61.77	44.44	77.21
γ 48.0	84.28	49.37	38.88	60.80
γ 49.0	67.00	41.85	34.19	49.07
γ 50.0	54.84	36.84	29.99	42.17
γ 51.0	46.98	33.08	26.73	37.60
γ 52.0	41.79	29.91	24.20	33.56
γ 53.0	37.44	27.53	22.40	30.33
γ 54.0	33.61	25.50	20.82	27.80
γ 55.0	30.61	23.68	19.31	25.75
γ 56.0	28.39	22.00	18.03	23.81
γ 57.0	26.53	20.35	16.85	22.08
γ 58.0	24.78	19.01	15.71	20.66
γ 59.0	23.15	17.67	14.87	19.47
γ 60.0	21.78	16.52	14.09	18.26
γ 61.0	20.38	15.58	13.30	17.26
γ 62.0	19.21	14.63	12.58	16.38
γ 63.0	18.25	13.72	11.79	15.45
γ 64.0	17.23	12.82	11.13	14.65
γ 65.0	16.26	11.95	10.30	13.79
γ 66.0	15.32	11.11	9.66	13.06
γ 67.0	14.36	10.26	8.90	12.21
γ 68.0	13.45	9.41	8.42	11.50
γ 69.0	12.46	8.66	8.03	10.72
γ 70.0	11.59	8.15	7.65	10.13
γ 71.0	10.66	7.67	7.32	9.68
γ 72.0	10.04	7.21	6.96	9.26
γ 73.0	9.48	6.81	6.63	8.87
γ 74.0	8.96	6.41	6.30	8.48
γ 75.0	8.47	6.05	5.99	8.10
γ 76.0	8.01	5.68	5.66	7.74
γ 77.0	7.57	5.33	5.34	7.38
γ 78.0	7.14	5.01	5.03	7.03
γ 79.0	6.75	4.68	4.72	6.67
γ 80.0	6.37	4.36	4.44	6.32
γ 81.0	5.99	4.09	4.19	5.97
γ 82.0	5.63	3.83	3.95	5.67
γ 83.0	5.29	3.59	3.67	5.37
γ 84.0	4.97	3.31	3.37	5.17
γ 85.0	4.68	3.05	3.05	4.85
γ 86.0	4.37	2.71	2.64	4.53
γ 87.0	4.05	2.36	2.04	4.20
γ 88.0	3.73	2.00	1.83	3.79
γ 89.0	3.39	1.69	1.73	2.80
γ 90.0	2.94	1.53	1.63	2.44
γ 91.0	2.48	1.45	1.54	2.30
γ 92.0	2.26	1.37	1.47	2.19
γ 93.0	2.15	1.30	1.39	2.08

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	2.05	1.23	1.32	1.98
γ 95.0	1.96	1.16	1.26	1.88
γ 96.0	1.86	1.10	1.19	1.79
γ 97.0	1.77	1.04	1.14	1.71
γ 98.0	1.68	0.99	1.10	1.63
γ 99.0	1.62	0.94	1.05	1.57
γ 100.0	1.54	0.90	1.02	1.49
γ 101.0	1.48	0.87	0.99	1.45
γ 102.0	1.41	0.83	0.97	1.39
γ 103.0	1.35	0.80	0.95	1.35
γ 104.0	1.31	0.78	0.94	1.30
γ 105.0	1.27	0.76	0.92	1.27
γ 106.0	1.23	0.74	0.93	1.24
γ 107.0	1.20	0.73	0.92	1.22
γ 108.0	1.17	0.74	0.93	1.20
γ 109.0	1.15	0.73	0.94	1.19
γ 110.0	1.13	0.73	0.96	1.18
γ 111.0	1.12	0.74	0.97	1.18
γ 112.0	1.11	0.75	1.00	1.18
γ 113.0	1.10	0.75	1.02	1.18
γ 114.0	1.10	0.77	1.06	1.20
γ 115.0	1.10	0.79	1.10	1.22
γ 116.0	1.10	0.81	1.14	1.23
γ 117.0	1.10	0.84	1.17	1.25
γ 118.0	1.12	0.87	1.23	1.28
γ 119.0	1.13	0.91	1.28	1.31
γ 120.0	1.14	0.94	1.33	1.36
γ 121.0	1.18	0.99	1.39	1.40
γ 122.0	1.20	1.03	1.45	1.43
γ 123.0	1.24	1.08	1.52	1.48
γ 124.0	1.27	1.14	1.59	1.54
γ 125.0	1.32	1.21	1.66	1.59
γ 126.0	1.36	1.28	1.74	1.66
γ 127.0	1.42	1.35	1.83	1.71
γ 128.0	1.48	1.43	1.91	1.78
γ 129.0	1.54	1.52	2.00	1.85
γ 130.0	1.61	1.59	2.09	1.93
γ 131.0	1.68	1.68	2.19	2.00
γ 132.0	1.77	1.77	2.31	2.09
γ 133.0	1.85	1.87	2.41	2.18
γ 134.0	1.94	1.98	2.53	2.29
γ 135.0	2.03	2.08	2.65	2.37
γ 136.0	2.13	2.19	2.77	2.47
γ 137.0	2.22	2.31	2.89	2.59
γ 138.0	2.33	2.41	3.02	2.70
γ 139.0	2.43	2.54	3.16	2.82
γ 140.0	2.54	2.66	3.27	2.94

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	2.66	2.78	3.39	3.06
γ 142.0	2.77	2.91	3.50	3.17
γ 143.0	2.89	3.03	3.61	3.29
γ 144.0	3.01	3.14	3.72	3.39
γ 145.0	3.13	3.26	3.83	3.50
γ 146.0	3.23	3.37	3.93	3.60
γ 147.0	3.35	3.48	4.02	3.71
γ 148.0	3.46	3.57	4.12	3.81
γ 149.0	3.57	3.67	4.20	3.90
γ 150.0	3.67	3.79	4.29	3.99
γ 151.0	3.78	3.88	4.37	4.08
γ 152.0	3.88	3.98	4.46	4.17
γ 153.0	3.97	4.07	4.55	4.25
γ 154.0	4.08	4.16	4.62	4.32
γ 155.0	4.18	4.25	4.70	4.42
γ 156.0	4.27	4.33	4.79	4.49
γ 157.0	4.36	4.41	4.86	4.57
γ 158.0	4.44	4.49	4.93	4.64
γ 159.0	4.54	4.57	5.01	4.72
γ 160.0	4.62	4.66	5.08	4.78
γ 161.0	4.70	4.72	5.14	4.84
γ 162.0	4.78	4.80	5.20	4.92
γ 163.0	4.87	4.88	5.26	4.98
γ 164.0	4.93	4.95	5.31	5.03
γ 165.0	5.01	5.02	5.38	5.09
γ 166.0	5.08	5.09	5.43	5.15
γ 167.0	5.14	5.16	5.48	5.21
γ 168.0	5.22	5.23	5.52	5.27
γ 169.0	5.28	5.28	5.57	5.33
γ 170.0	5.33	5.34	5.60	5.38
γ 171.0	5.40	5.38	5.64	5.41
γ 172.0	5.44	5.43	5.66	5.46
γ 173.0	5.49	5.47	5.68	5.50
γ 174.0	5.54	5.50	5.70	5.53
γ 175.0	5.57	5.53	5.71	5.57
γ 176.0	5.60	5.56	5.73	5.59
γ 177.0	5.63	5.58	5.74	5.62
γ 178.0	5.64	5.62	5.74	5.63
γ 179.0	5.66	5.63	5.75	5.64
γ 180.0	5.69	5.69	5.69	5.69