HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminaire Photometric Data

Description Information

Luminary Name: HCP-817024-5000K RA90 40D		Lum. Catelog:	Test ID: 01
Lamp Name:		Lamp Catelog: LED	Test Date: 2020/10/12
Manufacture: Havit Commercial		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency(Hz):	Lamp CCT(K): Ra:
Lum.Size(W*L*H):0.050m*0.000m*0.080m		Lum.Area(m2):0.016	Lum.W(kg): 0.000
Test System: C,γ	Test Step: C=90.0 γ=1.0	Temp.(℃): 25	Humidity(%): 50.0

Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 1170.150	Luminary Flux(lm): 1170.151	Field Angle(10%Imax): 86.7(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 1151.110lm 98.37%
Rated Voltage(V):	Luminary EER(lm/W): 73.089	Up Lumens&Percent: 19.041lm 1.63%
Tested Power(W): 16.010	Max.Candela(cd): 1688.920	S/MH: C0_a180=0.623 C90_270=0.619
Lamps' Inside: 1	Max Cand@Ang.(°): C=270.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics(V,A,pf):240.3,0.068,0.967	Beam Angle(50%Imax): 40.1(°)	ErP Φuse(90°): 1035.435lm
Lamp Size(W*L*H):0.050m*0.000m*0.080m	Left=-19.8° ,Right=20.2°	IRF(%): 302.437

C Plane Distribution Diagram



C Plane	[50%MaxAng.]	[10%MaxAng.]
C270.0_90.0 :	40.1	86.7
C0.0_180.0 :	40.3	87.3
C90.0_270.0 :	40.1	86.7

C0 Space ISO Illuminance Curve



HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

2D Plane Light Intensity Distribution Curve

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12



C Plane	[50%MaxAng.]	[10%MaxAng.]	Unit:cd
C270.0_90.0 :	40.1	86.7	
C0.0_180.0 :	40.3	87.3	
C90.0_270.0 :	40.1	86.7	

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Light Intensity Distribution Modal

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

3D Light Intensity Distribution Modal



Curves: 3D Model Fixture Vert. HUD Hori. HUD
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	1.60	1.60	0.14	0.14	47.0-48.0	6.11	1080.63	0.52	92.35
1.0-2.0	4.79	6.40	0.41	0.55	48.0-49.0	5.14	1085.77	0.44	92.79
2.0-3.0	7.92	14.31	0.68	1.22	49.0-50.0	4.43	1090.20	0.38	93.17
3.0-4.0	10.93	25.25	0.93	2.16	50.0-51.0	3.91	1094.11	0.33	93.50
4.0-5.0	13.81	39.05	1.18	3.34	51.0-52.0	3.56	1097.68	0.30	93.81
5.0-6.0	16.49	55.54	1.41	4.75	52.0-53.0	3.32	1101.00	0.28	94.09
6.0-7.0	18.93	74.47	1.62	6.36	53.0-54.0	3.12	1104.11	0.27	94.36
7.0-8.0	21.10	95.57	1.80	8.17	54.0-55.0	2.95	1107.06	0.25	94.61
8.0-9.0	23.01	118.57	1.97	10.13	55.0-56.0	2.81	1109.87	0.24	94.85
9.0-10.0	24.67	143.24	2.11	12.24	56.0-57.0	2.67	1112.54	0.23	95.08
10.0-11.0	26.11	169.35	2.23	14.47	57.0-58.0	2.54	1115.07	0.22	95.29
11.0-12.0	27.33	196.68	2.34	16.81	58.0-59.0	2.40	1117.48	0.21	95.50
12.0-13.0	28.35	225.02	2.42	19.23	59.0-60.0	2.27	1119.75	0.19	95.69
13.0-14.0	29.20	254.22	2.50	21.73	60.0-61.0	2.15	1121.89	0.18	95.88
14.0-15.0	29.94	284.16	2.56	24.28	61.0-62.0	2.02	1123.92	0.17	96.05
15.0-16.0	30.56	314.73	2.61	26.90	62.0-63.0	1.90	1125.82	0.16	96.21
16.0-17.0	31.06	345.78	2.65	29.55	63.0-64.0	1.78	1127.59	0.15	96.36
17.0-18.0	31.42	377.20	2.69	32.24	64.0-65.0	1.66	1129.26	0.14	96.51
18.0-19.0	31.66	408.86	2.71	34.94	65.0-66.0	1.55	1130.80	0.13	96.64
19.0-20.0	31.79	440.65	2.72	37.66	66.0-67.0	1.45	1132.25	0.12	96.76
20.0-21.0	31.81	472.46	2.72	40.38	67.0-68.0	1.36	1133.61	0.12	96.88
21.0-22.0	31.69	504.15	2.71	43.08	68.0-69.0	1.28	1134.89	0.11	96.99
22.0-23.0	31.46	535.61	2.69	45.77	69.0-70.0	1.21	1136.09	0.10	97.09
23.0-24.0	31.15	566.77	2.66	48.44	70.0-71.0	1.15	1137.24	0.10	97.19
24.0-25.0	30.75	597.51	2.63	51.06	71.0-72.0	1.09	1138.34	0.09	97.28
25.0-26.0	30.24	627.76	2.58	53.65	72.0-73.0	1.05	1139.38	0.09	97.37
26.0-27.0	29.65	657.41	2.53	56.18	73.0-74.0	1.00	1140.38	0.09	97.46
27.0-28.0	29.01	686.42	2.48	58.66	74.0-75.0	0.96	1141.34	0.08	97.54
28.0-29.0	28.36	714.79	2.42	61.09	75.0-76.0	0.91	1142.25	0.08	97.62
29.0-30.0	27.72	742.51	2.37	63.45	76.0-77.0	0.88	1143.13	0.07	97.69
30.0-31.0	27.15	769.67	2.32	65.77	77.0-78.0	0.84	1143.97	0.07	97.76
31.0-32.0	26.62	796.29	2.28	68.05	78.0-79.0	0.80	1144.77	0.07	97.83
32.0-33.0	26.12	822.41	2.23	70.28	79.0-80.0	0.76	1145.53	0.07	97.90
33.0-34.0	25.62	848.03	2.19	72.47	80.0-81.0	0.73	1146.26	0.06	97.96
34.0-35.0	25.09	873.12	2.14	74.62	81.0-82.0	0.70	1146.96	0.06	98.02
35.0-36.0	24.45	897.56	2.09	76.70	82.0-83.0	0.66	1147.62	0.06	98.07
36.0-37.0	23.64	921.20	2.02	78.73	83.0-84.0	0.63	1148.25	0.05	98.13
37.0-38.0	22.62	943.82	1.93	80.66	84.0-85.0	0.59	1148.84	0.05	98.18
38.0-39.0	21.37	965.20	1.83	82.49	85.0-86.0	0.55	1149.39	0.05	98.23
39.0-40.0	19.89	985.09	1.70	84.18	86.0-87.0	0.50	1149.89	0.04	98.27
40.0-41.0	18.26	1003.35	1.56	85.75	87.0-88.0	0.45	1150.35	0.04	98.31
41.0-42.0	16.50	1019.85	1.41	87.16	88.0-89.0	0.40	1150.75	0.03	98.34
42.0-43.0	14.65	1034.50	1.25	88.41	89.0-90.0	0.36	1151.11	0.03	98.37
43.0-44.0	12.74	1047.24	1.09	89.50	90.0-91.0	0.33	1151.44	0.03	98.40
44.0-45.0	10.84	1058.08	0.93	90.42	91.0-92.0	0.30	1151.74	0.03	98.43
45.0-46.0	9.03	1067.11	0.77	91.19	92.0-93.0	0.29	1152.03	0.02	98.45
46.0-47.0	7.41	1074.52	0.63	91.83	93.0-94.0	0.28	1152.30	0.02	98.47

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.27	1152.57	0.02	98.50
95.0-96.0	0.25	1152.82	0.02	98.52
96.0-97.0	0.25	1153.07	0.02	98.54
97.0-98.0	0.24	1153.30	0.02	98.56
98.0-99.0	0.23	1153.53	0.02	98.58
99.0-100.0	0.22	1153.75	0.02	98.60
100.0-101.0	0.21	1153.96	0.02	98.62
101.0-102.0	0.21	1154.17	0.02	98.63
102.0-103.0	0.20	1154.37	0.02	98.65
103.0-104.0	0.19	1154.56	0.02	98.67
104.0-105.0	0.19	1154.75	0.02	98.68
105.0-106.0	0.19	1154.94	0.02	98.70
106.0-107.0	0.18	1155.12	0.02	98.72
107.0-108.0	0.18	1155.30	0.02	98.73
108.0-109.0	0.18	1155.48	0.02	98.75
109.0-110.0	0.18	1155.65	0.02	98.76
110.0-111.0	0.17	1155.83	0.01	98.78
111.0-112.0	0.17	1156.00	0.01	98.79
112.0-113.0	0.17	1156.18	0.01	98.81
113.0-114.0	0.17	1156.35	0.01	98.82
114.0-115.0	0.17	1156.53	0.01	98.84
115.0-116.0	0.18	1156.70	0.02	98.85
116.0-117.0	0.18	1156.88	0.02	98.87
117.0-118.0	0.18	1157.06	0.02	98.88
118.0-119.0	0.18	1157.24	0.02	98.90
119.0-120.0	0.18	1157.42	0.02	98.91
120.0-121.0	0.19	1157.61	0.02	98.93
121.0-122.0	0.19	1157.80	0.02	98.94
122.0-123.0	0.19	1158.00	0.02	98.96
123.0-124.0	0.20	1158.19	0.02	98.98
124.0-125.0	0.20	1158.40	0.02	99.00
125.0-126.0	0.21	1158.60	0.02	99.01
126.0-127.0	0.21	1158.81	0.02	99.03
127.0-128.0	0.22	1159.03	0.02	99.05
128.0-129.0	0.22	1159.25	0.02	99.07
129.0-130.0	0.23	1159.48	0.02	99.09
130.0-131.0	0.23	1159.71	0.02	99.11
131.0-132.0	0.24	1159.95	0.02	99.13
132.0-133.0	0.24	1160.19	0.02	99.15
133.0-134.0	0.25	1160.44	0.02	99.17
134.0-135.0	0.25	1160.69	0.02	99.19
135.0-136.0	0.26	1160.95	0.02	99.21
136.0-137.0	0.26	1161.21	0.02	99.24
137.0-138.0	0.27	1161.48	0.02	99.26
138.0-139.0	0.27	1161.76	0.02	99.28
139.0-140.0	0.28	1162.03	0.02	99.31
140.0-141.0	0.28	1162.31	0.02	99.33
141.0-142.0	0.28	1162.60	0.02	99.35
142.0-143.0	0.29	1162.88	0.02	99.38
143.0-144.0	0.29	1163.17	0.02	99.40
144.0-145.0	0.29	1163.46	0.02	99.43
145.0-146.0	0.29	1163.76	0.02	99.45
146.0-147.0	0.29	1164.05	0.02	99.48
147.0-148.0	0.29	1164.34	0.02	99.50
148.0-149.0	0.29	1164.63	0.02	99.53
149.0-150.0	0.29	1164.92	0.02	99.55
150.0-151.0	0.29	1165.20	0.02	99.58
151.0-152.0	0.28	1165.48	0.02	99.60
152.0-153.0	0.28	1165.76	0.02	99.63
153.0-154.0	0.28	1166.04	0.02	99.65
154.0-155.0	0.27	1166.31	0.02	99.67
155.0-156.0	0.27	1166.57	0.02	99.69
156.0-157.0	0.26	1166.83	0.02	99.72
157.0-158.0	0.25	1167.09	0.02	99.74
158.0-159.0	0.25	1167.33	0.02	99.76
159.0-160.0	0.24	1167.57	0.02	99.78
160.0-161.0	0.23	1167.81	0.02	99.80
161.0-162.0	0.22	1168.03	0.02	99.82
162.0-163.0	0.21	1168.24	0.02	99.84
163.0-164.0	0.21	1168.45	0.02	99.85
164.0-165.0	0.20	1168.64	0.02	99.87
165.0-166.0	0.19	1168.83	0.02	99.89
166.0-167.0	0.17	1169.00	0.01	99.90
167.0-168.0	0.16	1169.17	0.01	99.92
168.0-169.0	0.15	1169.32	0.01	99.93
169.0-170.0	0.14	1169.46	0.01	99.94
170.0-171.0	0.13	1169.59	0.01	99.95
171.0-172.0	0.12	1169.70	0.01	99.96
172.0-173.0	0.10	1169.81	0.01	99.97
173.0-174.0	0.09	1169.90	0.01	99.98
174.0-175.0	0.08	1169.97	0.01	99.98
175.0-176.0	0.06	1170.04	0.01	99.99
176.0-177.0	0.05	1170.09	0.00	99.99
177.0-178.0	0.04	1170.12	0.00	100.00
178.0-179.0	0.02	1170.14	0.00	100.00
179.0-180.0	0.01	1170.15	0.00	100.00

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Rectangle ISO Lighting Intensity Diagram

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12



Maximum Light Intensity(cd): 1688.92
Maximum Cand.@Angle: H=-0.0°,V=-1.0°

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Plane ISO-Illuminance Diagram

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 187.57
Working Plane Maximum Illuminance Position(d/h):H-0.0 V-0.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

3D Plane ISO Illuminance Diagram

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

3D Plane Illuminance Modal



Curves: 3D Model 90% 80% 70% 60% 50% 40% 30% 20% 10%
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Space ISO Illuminance Diagram

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:1680.05lx,2.0deg
Plane Maximum Lighting Intensity and @Angle:1683.124cd,0eg

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Illuminance-Distance Diagram

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Illuminance-Distance Curve



Beam Angle:40.1

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Luminance Limiting Curves

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Glare Grade Table

GI	Quality	Using Illuminace							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	16716	6837	4293	3639	3036	2576	2540	2967	4765
C90	9824	4366	3469	2869	2300	1933	1887	2162	3129

Luminance Limiting Curve



Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.080 Area(m^2)=0.015708
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Budgetary Estimate Table

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Indoor Coefficient of Utilization Table

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC(%)	80				70				50			30			10			0
RhoW(%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101	98
1	113	110	107	104	110	107	105	103	103	101	99	99	97	96	95	94	93	91
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	87	86	84
3	101	94	89	84	99	92	87	84	89	85	82	87	83	80	84	81	79	77
4	95	87	81	77	93	86	81	76	84	79	75	81	77	74	79	76	73	72
5	90	81	75	71	89	80	75	70	78	73	70	77	72	69	75	71	68	67
6	86	76	70	66	84	75	69	65	74	68	65	72	68	64	71	67	63	62
7	81	72	65	61	80	71	65	61	69	64	60	68	63	60	67	63	59	58
8	77	67	61	57	76	67	61	57	65	60	56	64	60	56	63	59	56	54
9	74	64	57	53	72	63	57	53	62	57	53	61	56	53	60	56	52	51
10	70	60	54	50	69	60	54	50	59	53	50	58	53	50	57	53	49	48

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel：02 9381 8383
E-mail:sales@havitcommercial.com.au

Unified Glare Rating Table

Lum.Name: HCP-817024-5000K RA90 40D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine:GON-2000	Test Date: 2020/10/12

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	17.9	18.9	18.3	19.3	19.6	16.6	17.7	17.0	18.0	18.4
	Y=3H	17.9	18.8	18.3	19.2	19.6	16.6	17.5	17.0	17.9	18.3
	Y=4H	17.9	18.8	18.3	19.2	19.6	16.6	17.5	17.0	17.8	18.3
	Y=6H	17.9	18.8	18.4	19.2	19.6	16.6	17.4	17.0	17.8	18.2
	Y=8H	18.0	18.7	18.4	19.2	19.6	16.6	17.4	17.1	17.8	18.3
	Y=12H	18.0	18.8	18.5	19.2	19.7	16.6	17.4	17.1	17.8	18.3
X=4H	Y=2H	17.7	18.6	18.1	19.0	19.4	16.4	17.3	16.9	17.7	18.1
	Y=3H	17.8	18.5	18.2	18.9	19.4	16.5	17.2	16.9	17.6	18.1
	Y=4H	17.8	18.5	18.3	18.9	19.4	16.5	17.2	17.0	17.6	18.1
	Y=6H	17.9	18.5	18.4	19.0	19.5	16.6	17.2	17.1	17.7	18.2
	Y=8H	18.0	18.6	18.5	19.1	19.6	16.7	17.2	17.2	17.7	18.2
	Y=12H	18.2	18.7	18.7	19.2	19.7	16.8	17.2	17.3	17.8	18.3
X=8H	Y=4H	17.7	18.3	18.2	18.8	19.3	16.4	17.0	16.9	17.5	18.0
	Y=6H	17.9	18.4	18.5	18.9	19.5	16.6	17.1	17.1	17.6	18.2
	Y=8H	18.1	18.5	18.7	19.1	19.6	16.7	17.1	17.3	17.7	18.2
	Y=12H	18.4	18.7	18.9	19.3	19.9	16.9	17.3	17.5	17.8	18.4
X=12H	Y=4H	17.7	18.2	18.2	18.7	19.2	16.4	16.9	16.9	17.4	17.9
	Y=6H	17.9	18.3	18.5	18.8	19.4	16.6	17.0	17.2	17.5	18.1
	Y=8H	18.2	18.5	18.7	19.0	19.6	16.8	17.1	17.3	17.7	18.3

Variations with the observer position at spacings		
S=1.0H	0.1/-0.1	0.2/-0.2
S=1.5H	0.3/-0.3	0.4/-0.4
S=2.0H	0.6/-0.5	0.7/-0.6

Reduced UGR Table:		
Nordic Standard Table:	BK0	BK0
Correction Value	0.9	0.8

o the CIE Pub.117,data has been corrected,refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1676.53	1676.53	1676.53	1676.53
γ 1.0	1677.48	1684.10	1652.71	1688.92
γ 2.0	1683.12	1671.77	1628.95	1674.30
γ 3.0	1682.10	1649.84	1596.38	1652.16
γ 4.0	1673.58	1624.36	1558.24	1628.82
γ 5.0	1655.73	1589.87	1510.82	1595.47
γ 6.0	1633.54	1550.60	1458.49	1554.47
γ 7.0	1598.96	1496.93	1400.46	1504.11
γ 8.0	1558.24	1439.95	1343.53	1449.53
γ 9.0	1508.90	1379.27	1283.67	1391.50
γ 10.0	1456.51	1320.00	1227.11	1335.35
γ 11.0	1402.12	1261.82	1172.56	1276.42
γ 12.0	1344.02	1204.04	1120.86	1219.21
γ 13.0	1283.65	1148.88	1069.76	1163.71
γ 14.0	1225.29	1098.16	1021.16	1114.67
γ 15.0	1172.36	1051.00	973.53	1067.38
γ 16.0	1121.08	1004.35	929.71	1023.66
γ 17.0	1072.63	959.29	886.41	980.22
γ 18.0	1025.20	917.06	844.96	936.98
γ 19.0	978.57	876.25	804.24	895.03
γ 20.0	936.37	836.71	765.61	854.74
γ 21.0	893.14	797.55	727.96	813.61
γ 22.0	850.40	758.27	692.23	774.78
γ 23.0	810.48	720.09	655.52	736.49
γ 24.0	771.82	684.05	621.16	700.12
γ 25.0	733.13	647.13	587.63	663.63
γ 26.0	696.90	613.17	555.26	628.26
γ 27.0	660.59	576.90	524.86	592.22
γ 28.0	625.68	544.63	498.39	560.57
γ 29.0	590.69	513.95	474.01	528.73
γ 30.0	558.47	487.49	452.14	501.86
γ 31.0	528.85	465.11	430.90	478.04
γ 32.0	502.53	443.94	411.56	456.30
γ 33.0	478.33	424.45	392.01	437.09
γ 34.0	456.64	407.58	370.25	420.02
γ 35.0	437.45	390.13	346.74	402.45
γ 36.0	417.76	369.88	322.05	384.73
γ 37.0	396.80	347.20	295.84	364.91
γ 38.0	374.33	321.28	268.76	342.04
γ 39.0	348.97	293.74	241.00	314.60
γ 40.0	323.33	260.54	213.38	285.88
γ 41.0	296.33	229.88	185.40	255.84
γ 42.0	268.51	198.96	158.09	223.84
γ 43.0	241.25	167.60	131.35	192.31
γ 44.0	213.36	137.25	106.67	160.77
γ 45.0	185.67	109.11	84.10	131.48
γ 46.0	158.67	84.14	65.49	104.90

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	133.05	65.11	52.16	81.96
γ 48.0	108.92	53.56	45.06	64.64
γ 49.0	87.01	47.43	40.34	53.72
γ 50.0	69.03	44.08	35.77	47.43
γ 51.0	57.13	40.57	33.53	42.40
γ 52.0	50.87	37.23	31.68	38.57
γ 53.0	46.10	35.29	29.69	35.83
γ 54.0	41.12	33.23	27.96	33.84
γ 55.0	38.68	31.26	26.31	31.77
γ 56.0	36.49	29.36	24.64	29.94
γ 57.0	34.37	27.69	22.85	28.19
γ 58.0	32.43	25.78	21.42	26.55
γ 59.0	30.49	24.06	20.06	24.68
γ 60.0	28.58	22.53	18.76	23.20
γ 61.0	26.64	21.05	17.27	21.82
γ 62.0	25.05	19.56	15.99	20.48
γ 63.0	23.50	17.91	14.85	18.99
γ 64.0	21.88	16.57	13.64	17.66
γ 65.0	20.16	15.27	12.59	16.47
γ 66.0	18.75	13.85	11.81	15.22
γ 67.0	17.42	12.80	11.15	14.08
γ 68.0	15.96	11.91	10.54	13.28
γ 69.0	14.80	11.13	10.01	12.58
γ 70.0	13.84	10.38	9.52	11.97
γ 71.0	12.98	9.74	9.07	11.44
γ 72.0	12.20	9.15	8.68	10.96
γ 73.0	11.49	8.60	8.38	10.48
γ 74.0	10.87	8.13	8.03	10.04
γ 75.0	10.33	7.67	7.64	9.63
γ 76.0	9.80	7.28	7.28	9.24
γ 77.0	9.34	6.94	6.94	8.85
γ 78.0	8.89	6.57	6.60	8.47
γ 79.0	8.48	6.22	6.25	8.10
γ 80.0	8.09	5.90	5.94	7.73
γ 81.0	7.75	5.61	5.60	7.36
γ 82.0	7.42	5.31	5.27	7.03
γ 83.0	7.13	5.03	4.93	6.66
γ 84.0	6.82	4.68	4.59	6.35
γ 85.0	6.52	4.28	4.22	5.96
γ 86.0	6.17	3.96	3.61	5.56
γ 87.0	5.86	3.53	2.98	5.16
γ 88.0	5.44	3.07	2.69	4.44
γ 89.0	4.79	2.62	2.58	3.76
γ 90.0	4.20	2.44	2.46	3.35
γ 91.0	3.39	2.34	2.38	3.20
γ 92.0	3.14	2.24	2.28	3.07
γ 93.0	3.01	2.15	2.20	2.96

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	2.89	2.06	2.12	2.84
γ 95.0	2.77	1.98	2.03	2.73
γ 96.0	2.67	1.90	1.98	2.63
γ 97.0	2.56	1.83	1.91	2.53
γ 98.0	2.46	1.76	1.85	2.44
γ 99.0	2.38	1.70	1.80	2.37
γ 100.0	2.29	1.64	1.76	2.29
γ 101.0	2.21	1.60	1.72	2.22
γ 102.0	2.15	1.55	1.69	2.17
γ 103.0	2.08	1.52	1.66	2.11
γ 104.0	2.02	1.49	1.64	2.07
γ 105.0	1.98	1.46	1.63	2.03
γ 106.0	1.93	1.44	1.61	2.00
γ 107.0	1.88	1.43	1.61	1.96
γ 108.0	1.85	1.43	1.62	1.95
γ 109.0	1.83	1.41	1.63	1.93
γ 110.0	1.80	1.42	1.65	1.92
γ 111.0	1.79	1.43	1.66	1.92
γ 112.0	1.77	1.43	1.70	1.93
γ 113.0	1.78	1.46	1.73	1.94
γ 114.0	1.77	1.47	1.76	1.95
γ 115.0	1.78	1.50	1.80	1.97
γ 116.0	1.78	1.52	1.85	1.99
γ 117.0	1.80	1.56	1.91	2.03
γ 118.0	1.82	1.60	1.97	2.06
γ 119.0	1.84	1.64	2.04	2.11
γ 120.0	1.87	1.69	2.10	2.15
γ 121.0	1.91	1.75	2.17	2.21
γ 122.0	1.95	1.81	2.25	2.26
γ 123.0	1.99	1.89	2.33	2.32
γ 124.0	2.05	1.96	2.41	2.39
γ 125.0	2.11	2.04	2.51	2.46
γ 126.0	2.17	2.12	2.60	2.54
γ 127.0	2.23	2.20	2.70	2.63
γ 128.0	2.30	2.29	2.82	2.71
γ 129.0	2.39	2.40	2.93	2.80
γ 130.0	2.47	2.49	3.05	2.90
γ 131.0	2.55	2.61	3.17	2.99
γ 132.0	2.67	2.73	3.29	3.10
γ 133.0	2.78	2.84	3.42	3.22
γ 134.0	2.88	2.95	3.56	3.32
γ 135.0	2.99	3.09	3.68	3.44
γ 136.0	3.11	3.22	3.83	3.57
γ 137.0	3.24	3.35	3.96	3.70
γ 138.0	3.35	3.48	4.10	3.83
γ 139.0	3.47	3.62	4.24	3.97
γ 140.0	3.59	3.76	4.37	4.10

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	3.73	3.89	4.51	4.24
γ 142.0	3.86	4.05	4.64	4.37
γ 143.0	4.00	4.18	4.77	4.50
γ 144.0	4.13	4.32	4.90	4.64
γ 145.0	4.26	4.44	5.03	4.76
γ 146.0	4.39	4.58	5.15	4.89
γ 147.0	4.52	4.70	5.26	5.01
γ 148.0	4.66	4.83	5.38	5.13
γ 149.0	4.78	4.95	5.48	5.24
γ 150.0	4.90	5.08	5.59	5.36
γ 151.0	5.03	5.20	5.70	5.47
γ 152.0	5.15	5.32	5.81	5.57
γ 153.0	5.26	5.43	5.91	5.68
γ 154.0	5.38	5.53	6.01	5.78
γ 155.0	5.49	5.65	6.11	5.89
γ 156.0	5.62	5.76	6.20	5.99
γ 157.0	5.72	5.86	6.29	6.09
γ 158.0	5.84	5.97	6.39	6.19
γ 159.0	5.95	6.07	6.47	6.27
γ 160.0	6.06	6.17	6.54	6.35
γ 161.0	6.16	6.25	6.63	6.44
γ 162.0	6.25	6.36	6.71	6.52
γ 163.0	6.35	6.45	6.78	6.61
γ 164.0	6.45	6.53	6.84	6.68
γ 165.0	6.53	6.62	6.91	6.77
γ 166.0	6.62	6.70	6.98	6.83
γ 167.0	6.70	6.79	7.04	6.92
γ 168.0	6.77	6.86	7.10	6.98
γ 169.0	6.86	6.94	7.15	7.05
γ 170.0	6.93	7.01	7.20	7.11
γ 171.0	7.01	7.06	7.25	7.18
γ 172.0	7.07	7.12	7.30	7.23
γ 173.0	7.15	7.19	7.32	7.28
γ 174.0	7.20	7.23	7.36	7.33
γ 175.0	7.25	7.28	7.39	7.38
γ 176.0	7.31	7.33	7.41	7.42
γ 177.0	7.35	7.37	7.43	7.45
γ 178.0	7.39	7.41	7.45	7.49
γ 179.0	7.43	7.43	7.46	7.50
γ 180.0	7.45	7.45	7.45	7.45