Report No.: Test Time: 2024-03-13 14:19


Luminaire Property

Luminaire Manufacturer:
Luminaire Description: HCP-81321000 5700K
Lamp Catalog: COB
Lamp Description: 1616
Number of Lamps: 1
Luminous Length (mm): -36
Luminous Width (mm): -36
Voltage: 230.4 V
Current: 0.042 A
Power: 8.82 W
Power Factor: 0.916


Photometric Results

CIE Class: Direct
Total Rated Lamp Lumens: 513.6 lm
Measurement Flux: 513.6 lm
Efficiency: 100%
Downward Ratio: 100%
Upward Ratio: 0%
Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 69.9, 69.9, 69.9, 70.1
Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 54.4, 54.3, 54.4, 54.4
Luminaire Efficacy Rating (LER): 58.28
Central Intensity: 732.84 cd
Max. Intensity: 736.1 cd
Pos of Max. Intensity: H225 V6
S/MH(C0/C180): 0.85
S/MH(C90/C270): 0.85

Picture Of Luminaire



Luminous Intensity Distribution Curve




C Plane (°):0.0-360.0: 45.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab: NINGBO LED LIGHTING
Test Device: GPM-1600L
Test Type: TYPE C
Distance: 6.500 m
Temperature: 25°C
Humidity:
Operator: DING LI
Inspector:

Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	102	100	99	98	97	96	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89
3	104	98	94	90	102	97	93	90	94	91	88	92	89	87	90	87	85	84
4	100	93	88	84	98	92	87	83	89	86	82	88	84	81	86	83	81	79
5	95	88	82	78	94	87	82	78	85	81	77	83	80	77	82	79	76	75
6	91	83	77	74	90	82	77	73	81	76	73	79	75	72	78	75	72	71
7	87	79	73	69	86	78	73	69	77	72	69	76	71	68	75	71	68	67
8	83	75	69	65	82	74	69	65	73	68	65	72	68	65	71	67	65	63
9	80	71	66	62	79	71	65	62	70	65	62	69	65	61	68	64	61	60
10	76	68	62	59	76	67	62	59	66	62	59	66	61	58	65	61	58	57

Spacing Criteria (0-180): 0.85
Spacing Criteria (90-270): 0.85
Spacing Criteria (Diagonal): 0.81


Curves of Luminaires vs Lighting Area



C Plane (°):0.0-360.0: 45.0
Test Lab: NINGBO LED LIGHTING
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.500 m
Humidity:
Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 7.3 lx


(5%): 0.4 lx
(15%): 1.1 lx
(25%): 1.8 lx
(35%): 2.6 lx
(45%): 3.3 lx
(55%): 4.0 lx
(65%): 4.8 lx

C Plane (°):0.0-360.0: 45.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab: NINGBO LED LIGHTING
Test Device: GPM-1600L
Test Type: TYPE C
Distance: 6.500 m
Temperature: 25°C
Humidity:
Operator: DING LI
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h






L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	14408	9369	5498	2122	651	0	0	0	0
C90	13894	9140	4899	2378	814	0	0	0	0
C180	15881	10745	6834	2810	1279	0	0	0	0
C270	17895	11784	7656	3163	1743	0	0	0	0

C Plane (°):0.0-360.0: 45.0
Test Lab: NINGBO LED LIGHTING
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.500 m
Humidity:
Inspector:


Illuminance at a Distance



C Plane (°):0.0-360.0: 45.0
Test Lab: NINGBO LED LIGHTING
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.500 m
Humidity:
Inspector:

Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 732.8 lx

(5%): 36.6 lx
(15%): 109.9 lx
(25%): 183.2 lx
(35%): 256.5 lx
(45%): 329.8 lx
(55%): 403.1 lx
(65%): 476.3 lx

C Plane (°):0.0-360.0: 45.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab: NINGBO LED LIGHTING
Test Device: GPM-1600L
Test Type: TYPE C
Distance: 6.500 m
Temperature: 25°C
Humidity:
Operator: DING LI
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	241	46.9
FL (0°-30°)	208	40.6
FM (30°-60°)	32	6.3
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	273	53.1
BL (0°-30°)	226	44.0
BM (30°-60°)	46	9.0
BH (60°-80°)	0	0.1
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(**B**acklight,**U**plight,**G**lare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-360.0: 45.0
Test Lab: NINGBO LED LIGHTING
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.500 m
Humidity:
Inspector: