

IES Indoor Report

Photometric Filename: HV5528T 5500K RA80 90D.IES



Indoor Luminaire Photometric Data

Description Information

Luminary Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Date: 2019/06/22
Manufacture: Havit Lighting	Shld. Ang(°):	Test Machine: GON-2000
Test Lab: QC Department	Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H): 0.100m*0.100m*0.060m	Lum. Area (m2): 0.016	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity (%): 50.0

Character Parameter


Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 931.000	Luminary Flux(lm): 745.827	Field Angle(10%Imax): 124.9(°)
Rated Power(W):	Luminary Efficiency: 80.11%	Down Lumens&Percent: 719.459lm 96.46%
Rated Voltage(V):	Luminary EER(lm/W): 81.333	Up Lumens&Percent: 26.368lm 3.54%
Tested Power(W): 9.170	Max. Candela(cd): 359.659	S/MH: C0_a180=1.192 C90_270=1.190
Lamps' Inside: 1	Max Cand@Ang. (°): C=180.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics(V, A, pf): 240.1, 0.041, 0.917	Beam Angle(50%Imax): 93.8(°)	ErP Φuse(120°): 664.108lm
Lamp Size(W*L*H): 0.100m*0.100m*0.060m	Left=-46.8°, Right=47.0°	IRF(%): 125.598



2D Plane Light Intensity Distribution Curve

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22


C Plane Distribution Diagram



3D Light Intensity Distribution Modal

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation


Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.34	0.34	0.04	0.04	47.0-48.0	14.04	557.61	1.51	59.89
1.0-2.0	1.03	1.37	0.11	0.15	48.0-49.0	13.48	571.09	1.45	61.34
2.0-3.0	1.71	3.09	0.18	0.33	49.0-50.0	12.86	583.95	1.38	62.72
3.0-4.0	2.40	5.49	0.26	0.59	50.0-51.0	12.17	596.13	1.31	64.03
4.0-5.0	3.07	8.56	0.33	0.92	51.0-52.0	11.42	607.54	1.23	65.26
5.0-6.0	3.75	12.31	0.40	1.32	52.0-53.0	10.60	618.15	1.14	66.40
6.0-7.0	4.41	16.72	0.47	1.80	53.0-54.0	9.74	627.88	1.05	67.44
7.0-8.0	5.07	21.79	0.54	2.34	54.0-55.0	8.85	636.73	0.95	68.39
8.0-9.0	5.72	27.52	0.61	2.96	55.0-56.0	7.96	644.69	0.86	69.25
9.0-10.0	6.37	33.88	0.68	3.64	56.0-57.0	7.10	651.79	0.76	70.01
10.0-11.0	7.00	40.88	0.75	4.39	57.0-58.0	6.29	658.09	0.68	70.69
11.0-12.0	7.62	48.50	0.82	5.21	58.0-59.0	5.56	663.64	0.60	71.28
12.0-13.0	8.22	56.72	0.88	6.09	59.0-60.0	4.91	668.56	0.53	71.81
13.0-14.0	8.81	65.53	0.95	7.04	60.0-61.0	4.36	672.91	0.47	72.28
14.0-15.0	9.39	74.92	1.01	8.05	61.0-62.0	3.89	676.80	0.42	72.70
15.0-16.0	9.95	84.88	1.07	9.12	62.0-63.0	3.49	680.30	0.38	73.07
16.0-17.0	10.50	95.38	1.13	10.24	63.0-64.0	3.15	683.45	0.34	73.41
17.0-18.0	11.02	106.40	1.18	11.43	64.0-65.0	2.86	686.31	0.31	73.72
18.0-19.0	11.53	117.93	1.24	12.67	65.0-66.0	2.60	688.91	0.28	74.00
19.0-20.0	12.02	129.95	1.29	13.96	66.0-67.0	2.39	691.30	0.26	74.25
20.0-21.0	12.49	142.44	1.34	15.30	67.0-68.0	2.23	693.53	0.24	74.49
21.0-22.0	12.93	155.37	1.39	16.69	68.0-69.0	2.10	695.63	0.23	74.72
22.0-23.0	13.36	168.73	1.43	18.12	69.0-70.0	1.99	697.61	0.21	74.93
23.0-24.0	13.75	182.48	1.48	19.60	70.0-71.0	1.88	699.49	0.20	75.13
24.0-25.0	14.13	196.61	1.52	21.12	71.0-72.0	1.78	701.27	0.19	75.32
25.0-26.0	14.47	211.08	1.55	22.67	72.0-73.0	1.67	702.94	0.18	75.50
26.0-27.0	14.80	225.89	1.59	24.26	73.0-74.0	1.58	704.52	0.17	75.67
27.0-28.0	15.10	240.99	1.62	25.88	74.0-75.0	1.48	706.00	0.16	75.83
28.0-29.0	15.37	256.36	1.65	27.54	75.0-76.0	1.39	707.40	0.15	75.98
29.0-30.0	15.62	271.98	1.68	29.21	76.0-77.0	1.31	708.70	0.14	76.12
30.0-31.0	15.83	287.81	1.70	30.91	77.0-78.0	1.22	709.93	0.13	76.25
31.0-32.0	16.01	303.82	1.72	32.63	78.0-79.0	1.14	711.07	0.12	76.38
32.0-33.0	16.17	319.99	1.74	34.37	79.0-80.0	1.07	712.14	0.11	76.49
33.0-34.0	16.29	336.28	1.75	36.12	80.0-81.0	1.00	713.14	0.11	76.60
34.0-35.0	16.39	352.67	1.76	37.88	81.0-82.0	0.93	714.07	0.10	76.70
35.0-36.0	16.46	369.13	1.77	39.65	82.0-83.0	0.86	714.93	0.09	76.79
36.0-37.0	16.49	385.62	1.77	41.42	83.0-84.0	0.80	715.74	0.09	76.88
37.0-38.0	16.49	402.11	1.77	43.19	84.0-85.0	0.74	716.48	0.08	76.96
38.0-39.0	16.46	418.57	1.77	44.96	85.0-86.0	0.69	717.17	0.07	77.03
39.0-40.0	16.38	434.95	1.76	46.72	86.0-87.0	0.64	717.81	0.07	77.10
40.0-41.0	16.26	451.21	1.75	48.47	87.0-88.0	0.59	718.40	0.06	77.16
41.0-42.0	16.10	467.31	1.73	50.19	88.0-89.0	0.55	718.94	0.06	77.22
42.0-43.0	15.88	483.20	1.71	51.90	89.0-90.0	0.51	719.46	0.06	77.28
43.0-44.0	15.62	498.81	1.68	53.58	90.0-91.0	0.49	719.95	0.05	77.33
44.0-45.0	15.30	514.12	1.64	55.22	91.0-92.0	0.48	720.43	0.05	77.38
45.0-46.0	14.94	529.06	1.60	56.83	92.0-93.0	0.47	720.91	0.05	77.43
46.0-47.0	14.52	543.58	1.56	58.39	93.0-94.0	0.47	721.37	0.05	77.48

Zonal Flux Tabulation - (Cont.)

Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.46	721.83	0.05	77.53	141.0-142.0	0.30	739.19	0.03	79.40
95.0-96.0	0.45	722.28	0.05	77.58	142.0-143.0	0.30	739.49	0.03	79.43
96.0-97.0	0.44	722.73	0.05	77.63	143.0-144.0	0.29	739.78	0.03	79.46
97.0-98.0	0.44	723.16	0.05	77.68	144.0-145.0	0.29	740.07	0.03	79.49
98.0-99.0	0.43	723.60	0.05	77.72	145.0-146.0	0.29	740.36	0.03	79.52
99.0-100.0	0.43	724.02	0.05	77.77	146.0-147.0	0.28	740.64	0.03	79.55
100.0-101.0	0.42	724.45	0.05	77.81	147.0-148.0	0.28	740.91	0.03	79.58
101.0-102.0	0.42	724.86	0.04	77.86	148.0-149.0	0.27	741.18	0.03	79.61
102.0-103.0	0.41	725.28	0.04	77.90	149.0-150.0	0.26	741.45	0.03	79.64
103.0-104.0	0.41	725.68	0.04	77.95	150.0-151.0	0.26	741.71	0.03	79.67
104.0-105.0	0.40	726.09	0.04	77.99	151.0-152.0	0.25	741.96	0.03	79.70
105.0-106.0	0.40	726.49	0.04	78.03	152.0-153.0	0.25	742.21	0.03	79.72
106.0-107.0	0.40	726.88	0.04	78.08	153.0-154.0	0.24	742.45	0.03	79.75
107.0-108.0	0.39	727.28	0.04	78.12	154.0-155.0	0.23	742.69	0.03	79.77
108.0-109.0	0.39	727.67	0.04	78.16	155.0-156.0	0.23	742.91	0.02	79.80
109.0-110.0	0.39	728.05	0.04	78.20	156.0-157.0	0.22	743.13	0.02	79.82
110.0-111.0	0.38	728.44	0.04	78.24	157.0-158.0	0.21	743.35	0.02	79.84
111.0-112.0	0.38	728.82	0.04	78.28	158.0-159.0	0.21	743.56	0.02	79.87
112.0-113.0	0.38	729.20	0.04	78.32	159.0-160.0	0.20	743.76	0.02	79.89
113.0-114.0	0.38	729.57	0.04	78.36	160.0-161.0	0.19	743.95	0.02	79.91
114.0-115.0	0.37	729.95	0.04	78.40	161.0-162.0	0.18	744.13	0.02	79.93
115.0-116.0	0.37	730.32	0.04	78.44	162.0-163.0	0.18	744.31	0.02	79.95
116.0-117.0	0.37	730.69	0.04	78.48	163.0-164.0	0.17	744.47	0.02	79.96
117.0-118.0	0.37	731.06	0.04	78.52	164.0-165.0	0.16	744.63	0.02	79.98
118.0-119.0	0.37	731.42	0.04	78.56	165.0-166.0	0.15	744.78	0.02	80.00
119.0-120.0	0.36	731.79	0.04	78.60	166.0-167.0	0.14	744.92	0.02	80.01
120.0-121.0	0.36	732.15	0.04	78.64	167.0-168.0	0.13	745.05	0.01	80.03
121.0-122.0	0.36	732.51	0.04	78.68	168.0-169.0	0.12	745.18	0.01	80.04
122.0-123.0	0.36	732.87	0.04	78.72	169.0-170.0	0.11	745.29	0.01	80.05
123.0-124.0	0.36	733.22	0.04	78.76	170.0-171.0	0.10	745.39	0.01	80.06
124.0-125.0	0.35	733.58	0.04	78.79	171.0-172.0	0.09	745.48	0.01	80.07
125.0-126.0	0.35	733.93	0.04	78.83	172.0-173.0	0.08	745.56	0.01	80.08
126.0-127.0	0.35	734.28	0.04	78.87	173.0-174.0	0.07	745.63	0.01	80.09
127.0-128.0	0.35	734.63	0.04	78.91	174.0-175.0	0.06	745.69	0.01	80.10
128.0-129.0	0.35	734.97	0.04	78.94	175.0-176.0	0.05	745.74	0.01	80.10
129.0-130.0	0.34	735.32	0.04	78.98	176.0-177.0	0.04	745.78	0.00	80.11
130.0-131.0	0.34	735.66	0.04	79.02	177.0-178.0	0.03	745.81	0.00	80.11
131.0-132.0	0.34	735.99	0.04	79.05	178.0-179.0	0.02	745.82	0.00	80.11
132.0-133.0	0.33	736.33	0.04	79.09	179.0-180.0	0.01	745.83	0.00	80.11
133.0-134.0	0.33	736.66	0.04	79.13					
134.0-135.0	0.33	736.99	0.04	79.16					
135.0-136.0	0.33	737.32	0.03	79.20					
136.0-137.0	0.32	737.64	0.03	79.23					
137.0-138.0	0.32	737.96	0.03	79.26					
138.0-139.0	0.31	738.27	0.03	79.30					
139.0-140.0	0.31	738.58	0.03	79.33					
140.0-141.0	0.31	738.89	0.03	79.37					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22




Maximum Light Intensity(cd): 359.66
Maximum Cand.@Angle: H=-1.0°,V=0.0°

Plane ISO-Illuminance Diagram

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
 Working Plane Maximum Illuminance(lx): 39.94
 Working Plane Maximum Illuminance Position(d/h):H0.0 V-0.0

3D Plane ISO Illuminance Diagram

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

Space ISO Illuminance Curve




Space Plane Maximum Illuminance and @Angle:359.18lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:359.345cd,0deg

Illuminance-Distance Diagram

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

Illuminance-Distance Curve



Indoor Luminance Limiting Curves

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	17242	14464	10064	5968	4079	3553	3411	3592	4889
C90	16212	13032	8451	5016	3453	3083	2915	3002	3969


Luminance Limiting Curve



Luminous Size: Length(m)=0.100 Width(m)=0.100 Height(m)=0.060 Area(m^2)=0.016000
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
 Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
 Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	95	95	95	95	92	92	92	92	87	87	87	83	83	83	79	79	79	77
1	88	85	82	80	86	83	81	78	79	77	75	76	74	73	72	71	70	68
2	82	76	72	68	80	75	71	67	71	68	65	69	66	63	66	64	62	60
3	76	69	63	59	74	67	62	58	65	60	57	62	59	56	60	57	54	53
4	70	62	56	51	68	61	55	51	58	54	50	56	52	49	54	51	48	46
5	65	56	50	45	63	55	49	45	53	48	44	51	47	43	50	46	43	41
6	61	51	45	40	59	50	44	40	49	43	39	47	42	39	46	42	38	37
7	56	47	40	36	55	46	40	36	45	39	35	43	38	35	42	38	35	33
8	53	43	37	33	51	42	36	32	41	36	32	40	35	32	39	35	31	30
9	49	40	34	30	48	39	33	29	38	33	29	37	32	29	36	32	29	27
10	46	37	31	27	45	36	31	27	35	30	27	34	30	26	33	29	26	25

Unified Glare Rating Table

Lum. Name: HV5528T-5500K	Lum. Catalog:	Test ID: zhang jin cheng
Lamp Name:	Lamp Catalog: LED	Test Lab: QC Department
Manufacture: Havit Lighting	Test Machine: GON-2000	Test Date: 2019/06/22

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	20.9	22.0	21.4	22.4	22.8	20.4	21.5	20.8	21.9	22.3
	21.1	22.0	21.6	22.4	22.9	20.6	21.5	21.0	21.9	22.3
	21.2	22.0	21.7	22.5	22.9	20.7	21.5	21.1	21.9	22.4
	21.4	22.0	21.8	22.5	23.0	20.8	21.4	21.2	21.9	22.4
	21.4	22.0	21.9	22.5	23.0	20.8	21.4	21.3	21.9	22.4
	21.5	22.1	22.0	22.5	23.0	20.8	21.4	21.4	21.9	22.4
X=4H Y=2H	21.1	21.8	21.5	22.3	22.8	20.5	21.3	21.0	21.7	22.2
	21.4	21.9	21.9	22.4	22.9	20.8	21.4	21.3	21.8	22.3
	21.6	22.0	22.1	22.5	23.0	21.0	21.4	21.5	21.9	22.4
	21.8	22.1	22.3	22.6	23.2	21.2	21.4	21.7	22.0	22.5
	21.9	22.1	22.4	22.6	23.2	21.2	21.5	21.8	22.0	22.6
	22.0	22.1	22.6	22.7	23.3	21.3	21.5	21.9	22.0	22.6
X=8H Y=4H	21.6	21.8	22.2	22.3	22.9	21.0	21.2	21.6	21.8	22.3
	21.9	22.0	22.5	22.6	23.1	21.3	21.4	21.9	21.9	22.5
	22.1	22.1	22.7	22.7	23.3	21.5	21.5	22.1	22.1	22.7
	22.4	22.3	23.0	22.9	23.5	21.7	21.6	22.3	22.2	22.9
X=12H Y=4H	21.6	21.7	22.2	22.3	22.8	21.0	21.1	21.6	21.7	22.3
	21.9	21.9	22.6	22.5	23.1	21.3	21.3	21.9	21.9	22.5
	22.2	22.1	22.8	22.7	23.4	21.5	21.5	22.1	22.0	22.7
Variations with the objerver position at spacings										
S=1.0H	0.2/−0.2					0.3/−0.3				
S=1.5H	0.5/−0.5					0.6/−0.6				
S=2.0H	0.8/−0.8					0.8/−0.8				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	1.0					1.0				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	359.07	359.07	359.07	359.07
γ 1.0	359.35	358.20	359.66	358.44
γ 2.0	359.05	357.86	359.30	358.41
γ 3.0	358.72	357.33	358.93	358.21
γ 4.0	358.14	356.57	358.33	357.97
γ 5.0	357.58	355.41	357.54	357.42
γ 6.0	356.52	354.57	356.58	356.55
γ 7.0	355.32	353.25	355.72	355.74
γ 8.0	353.99	351.88	354.56	354.99
γ 9.0	352.76	350.48	353.00	353.58
γ 10.0	351.38	348.61	351.50	352.45
γ 11.0	349.43	346.80	350.08	350.82
γ 12.0	347.63	344.80	347.98	349.18
γ 13.0	345.52	342.65	345.94	347.48
γ 14.0	343.20	340.13	343.91	345.59
γ 15.0	341.13	337.80	341.58	343.26
γ 16.0	338.55	335.21	338.95	340.92
γ 17.0	335.75	332.28	336.41	338.52
γ 18.0	332.80	329.22	333.78	335.82
γ 19.0	330.01	325.92	330.71	333.03
γ 20.0	326.71	322.85	327.29	330.00
γ 21.0	323.48	319.06	324.19	327.22
γ 22.0	320.01	315.73	320.85	323.86
γ 23.0	316.55	311.82	317.22	320.26
γ 24.0	312.63	308.04	313.18	316.75
γ 25.0	308.66	303.61	309.35	313.03
γ 26.0	304.58	299.30	305.15	309.15
γ 27.0	300.33	295.10	301.25	305.13
γ 28.0	296.07	290.59	296.65	300.92
γ 29.0	291.57	285.65	292.18	296.75
γ 30.0	286.69	280.93	287.48	292.22
γ 31.0	281.93	275.81	282.83	287.39
γ 32.0	276.89	270.42	277.68	282.81
γ 33.0	271.80	265.09	272.61	277.87
γ 34.0	266.55	259.56	267.41	272.82
γ 35.0	261.24	254.10	262.07	267.58
γ 36.0	255.72	248.08	256.56	262.25
γ 37.0	249.90	242.08	250.91	256.91
γ 38.0	244.12	235.92	245.13	251.33
γ 39.0	238.11	229.38	239.25	245.47
γ 40.0	231.65	222.34	232.87	239.59
γ 41.0	225.07	215.28	226.25	233.43
γ 42.0	218.09	207.83	219.54	226.96
γ 43.0	210.78	199.99	212.13	219.98
γ 44.0	203.04	192.02	204.52	212.81
γ 45.0	195.07	183.42	196.64	205.32
γ 46.0	186.86	174.58	188.43	197.65

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	178.16	165.42	179.76	189.55
γ 48.0	168.82	155.41	170.71	180.99
γ 49.0	159.11	144.95	160.93	172.19
γ 50.0	148.75	134.03	150.87	162.95
γ 51.0	138.15	122.70	140.35	153.04
γ 52.0	126.94	111.15	129.37	142.60
γ 53.0	115.41	99.59	118.01	131.78
γ 54.0	103.76	88.27	106.45	120.44
γ 55.0	92.36	77.55	95.00	109.02
γ 56.0	81.49	67.77	84.02	97.56
γ 57.0	71.40	59.12	73.53	86.33
γ 58.0	62.32	51.63	64.16	75.77
γ 59.0	54.42	45.37	55.78	66.13
γ 60.0	47.74	40.13	48.73	57.54
γ 61.0	42.27	35.73	42.85	50.24
γ 62.0	37.66	31.90	37.94	44.28
γ 63.0	33.82	28.60	33.81	39.31
γ 64.0	30.43	25.71	30.22	35.09
γ 65.0	27.58	23.35	27.02	31.46
γ 66.0	25.15	21.56	24.27	28.25
γ 67.0	23.29	20.26	22.01	25.57
γ 68.0	21.87	19.11	20.42	23.42
γ 69.0	20.65	17.96	19.23	21.84
γ 70.0	19.44	16.87	18.10	20.56
γ 71.0	18.26	15.82	17.00	19.39
γ 72.0	17.17	14.82	15.94	18.22
γ 73.0	16.10	13.85	14.92	17.09
γ 74.0	15.08	12.95	13.95	16.03
γ 75.0	14.13	12.07	13.05	15.03
γ 76.0	13.22	11.24	12.19	14.07
γ 77.0	12.33	10.47	11.35	13.17
γ 78.0	11.51	9.72	10.59	12.28
γ 79.0	10.73	9.01	9.87	11.50
γ 80.0	9.98	8.34	9.19	10.74
γ 81.0	9.27	7.71	8.55	10.01
γ 82.0	8.61	7.11	7.94	9.34
γ 83.0	7.97	6.56	7.37	8.71
γ 84.0	7.38	6.03	6.84	8.12
γ 85.0	6.82	5.53	6.33	7.54
γ 86.0	6.29	5.09	5.85	7.00
γ 87.0	5.80	4.67	5.41	6.51
γ 88.0	5.34	4.28	5.00	6.04
γ 89.0	4.94	4.10	4.63	5.60
γ 90.0	4.73	4.03	4.31	5.19
γ 91.0	4.64	3.97	4.23	4.86
γ 92.0	4.55	3.92	4.17	4.76
γ 93.0	4.47	3.86	4.12	4.69

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	4.39	3.81	4.06	4.62
γ 95.0	4.32	3.77	4.02	4.54
γ 96.0	4.26	3.72	3.97	4.48
γ 97.0	4.19	3.69	3.93	4.41
γ 98.0	4.14	3.65	3.90	4.35
γ 99.0	4.09	3.63	3.86	4.30
γ 100.0	4.05	3.60	3.83	4.24
γ 101.0	4.01	3.57	3.80	4.20
γ 102.0	3.97	3.56	3.77	4.15
γ 103.0	3.94	3.54	3.75	4.11
γ 104.0	3.91	3.53	3.73	4.08
γ 105.0	3.89	3.52	3.71	4.05
γ 106.0	3.86	3.51	3.69	4.02
γ 107.0	3.85	3.51	3.69	4.00
γ 108.0	3.84	3.51	3.68	3.98
γ 109.0	3.83	3.52	3.68	3.96
γ 110.0	3.82	3.51	3.66	3.95
γ 111.0	3.82	3.52	3.67	3.94
γ 112.0	3.82	3.54	3.69	3.93
γ 113.0	3.81	3.54	3.68	3.93
γ 114.0	3.81	3.55	3.70	3.93
γ 115.0	3.82	3.57	3.70	3.93
γ 116.0	3.83	3.59	3.71	3.93
γ 117.0	3.84	3.60	3.73	3.93
γ 118.0	3.85	3.63	3.74	3.94
γ 119.0	3.86	3.64	3.76	3.96
γ 120.0	3.88	3.67	3.78	3.96
γ 121.0	3.89	3.69	3.81	3.97
γ 122.0	3.91	3.72	3.83	3.99
γ 123.0	3.94	3.74	3.85	4.00
γ 124.0	3.95	3.78	3.88	4.03
γ 125.0	3.97	3.81	3.90	4.05
γ 126.0	4.00	3.84	3.92	4.06
γ 127.0	4.03	3.87	3.96	4.09
γ 128.0	4.06	3.91	3.98	4.11
γ 129.0	4.07	3.93	4.01	4.14
γ 130.0	4.10	3.96	4.05	4.15
γ 131.0	4.13	4.00	4.07	4.19
γ 132.0	4.15	4.03	4.11	4.22
γ 133.0	4.18	4.06	4.14	4.24
γ 134.0	4.21	4.11	4.17	4.27
γ 135.0	4.24	4.14	4.20	4.30
γ 136.0	4.27	4.17	4.23	4.33
γ 137.0	4.29	4.21	4.26	4.35
γ 138.0	4.33	4.24	4.30	4.40
γ 139.0	4.37	4.29	4.33	4.42
γ 140.0	4.40	4.32	4.37	4.45

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	4.43	4.36	4.40	4.48
γ 142.0	4.46	4.40	4.44	4.52
γ 143.0	4.51	4.45	4.47	4.55
γ 144.0	4.53	4.49	4.51	4.57
γ 145.0	4.58	4.52	4.55	4.62
γ 146.0	4.62	4.57	4.59	4.66
γ 147.0	4.65	4.62	4.63	4.70
γ 148.0	4.69	4.66	4.68	4.74
γ 149.0	4.74	4.69	4.71	4.77
γ 150.0	4.79	4.74	4.76	4.81
γ 151.0	4.83	4.79	4.81	4.85
γ 152.0	4.87	4.84	4.85	4.90
γ 153.0	4.91	4.89	4.89	4.93
γ 154.0	4.96	4.93	4.94	4.98
γ 155.0	5.00	4.99	4.98	5.03
γ 156.0	5.04	5.03	5.03	5.06
γ 157.0	5.09	5.07	5.07	5.10
γ 158.0	5.14	5.12	5.11	5.15
γ 159.0	5.17	5.16	5.16	5.18
γ 160.0	5.22	5.21	5.20	5.24
γ 161.0	5.26	5.25	5.25	5.28
γ 162.0	5.30	5.29	5.29	5.32
γ 163.0	5.34	5.33	5.33	5.35
γ 164.0	5.39	5.39	5.37	5.40
γ 165.0	5.43	5.42	5.42	5.44
γ 166.0	5.46	5.45	5.46	5.47
γ 167.0	5.56	5.48	5.50	5.51
γ 168.0	5.61	5.52	5.57	5.54
γ 169.0	5.56	5.56	5.64	5.57
γ 170.0	5.61	5.58	5.61	5.60
γ 171.0	5.62	5.60	5.61	5.62
γ 172.0	5.64	5.63	5.63	5.66
γ 173.0	5.66	5.66	5.65	5.68
γ 174.0	5.68	5.68	5.68	5.70
γ 175.0	5.69	5.69	5.70	5.72
γ 176.0	5.71	5.70	5.71	5.72
γ 177.0	5.72	5.73	5.73	5.75
γ 178.0	5.73	5.73	5.73	5.76
γ 179.0	5.74	5.73	5.75	5.77
γ 180.0	5.75	5.75	5.75	5.75