IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Indoor Luminaire Photometric Data


Description Information

Luminary Name: MD21-06-XX-02 2700K RA90 25D		Lum. Catelog:	Test ID: 01
Lamp Name:		Lamp Catelog: LED	Test Date: 2022/10/13
Manufacture: Shenzhen Norming Lightin		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Qualty Departmnt		Frequency(Hz):	Lamp CCT(K): Ra:
Lum.Size(W*L*H):0.041m*-0.041m*0.000m		Lum.Area(m2):0.001	Lum.W(kg): 0.000
Test System: C,γ	Test Step: C=90.0 γ=5.0	Temp.(℃): 25	Humidity(%):


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 550.880	Luminary Flux(lm): 550.876	Field Angle(10%Imax): 81.6(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 550.876lm 100.00%
Rated Voltage(V):	Luminary EER(lm/W): 75.041	Up Lumens&Percent: 0.000lm 0.00%
Tested Power(W): 7.341	Max.Candela(cd): 1298.821	S/MH: C0_a180=0.425 C90_270=0.443
Lamps' Inside: 1	Max Cand@Ang.(°): C=0.0 γ=5.0	CIE Type: Semi-Direct
Tested Electrics(V,A,pf):24.0,0.305	Beam Angle(50%Imax): 25.3(°)	ErP Φuse(90°): 503.696lm
Lamp Size(W*L*H):0.041m*-0.041m*0.000m	Left=-9.4° ,Right=15.9°	IRF(%): 454.295

C Plane Distribution Diagram



C0 Space ISO Illuminance Curve





IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

2D Plane Light Intensity Distribution Curve

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

C Plane Distribution Diagram






C Plane	[50%MaxAng.]	[10%MaxAng.]	Unit:cd
C0.0_180.0 :	25.3	81.6	
C90.0_270.0 :	26.1	82.1	

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

3D Light Intensity Distribution Modal

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

3D Light Intensity Distribution Modal



Curves: 3D Model Fixture Vert. HUD Hori. HUD

View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES


Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-5.0	29.69	29.69	5.39	5.39
5.0-10.0	73.25	102.95	13.30	18.69
10.0-15.0	81.61	184.56	14.81	33.50
15.0-20.0	68.79	253.34	12.49	45.99
20.0-25.0	59.36	312.71	10.78	56.76
25.0-30.0	57.85	370.56	10.50	67.27
30.0-35.0	58.39	428.95	10.60	77.87
35.0-40.0	54.47	483.42	9.89	87.75
40.0-45.0	38.48	521.90	6.99	94.74
45.0-50.0	17.39	539.29	3.16	97.90
50.0-55.0	5.93	545.22	1.08	98.97
55.0-60.0	2.83	548.06	0.51	99.49
60.0-65.0	1.53	549.59	0.28	99.77
65.0-70.0	0.77	550.36	0.14	99.90
70.0-75.0	0.36	550.71	0.06	99.97
75.0-80.0	0.14	550.85	0.03	99.99
80.0-85.0	0.02	550.88	0.00	100.00
85.0-90.0	0.00	550.88	0.00	100.00
90.0-95.0	0.00	550.88	0.00	100.00
95.0-100.0	0.00	550.88	0.00	100.00
100.0-105.0	0.00	550.88	0.00	100.00
105.0-110.0	0.00	550.88	0.00	100.00
110.0-115.0	0.00	550.88	0.00	100.00
115.0-120.0	0.00	550.88	0.00	100.00
120.0-125.0	0.00	550.88	0.00	100.00
125.0-130.0	0.00	550.88	0.00	100.00
130.0-135.0	0.00	550.88	0.00	100.00
135.0-140.0	0.00	550.88	0.00	100.00
140.0-145.0	0.00	550.88	0.00	100.00
145.0-150.0	0.00	550.88	0.00	100.00
150.0-155.0	0.00	550.88	0.00	100.00
155.0-160.0	0.00	550.88	0.00	100.00
160.0-165.0	0.00	550.88	0.00	100.00
165.0-170.0	0.00	550.88	0.00	100.00
170.0-175.0	0.00	550.88	0.00	100.00
175.0-180.0	0.00	550.88	0.00	100.00

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Rectangle ISO Lighting Intensity Diagram

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13




Maximum Light Intensity(cd): 1298.82
Maximum Cand.@Angle: H=5.0°,V=0.0°

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Plane ISO-Illuminance Diagram

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 144.11
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

3D Plane ISO Illuminance Diagram

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

3D Plane Illuminance Modal



Curves: 3D Model 90% 80% 70% 60% 50% 40% 30% 20% 10%


View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Space ISO Illuminance Diagram

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

Space ISO Illuminance Curve




Space Plane Maximum Illuminance and @Angle:1296.97lx,0.0deg
Plane Maximum Lighting Intensity and @Angle:1298.821cd,0eg

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Illuminance-Distance Diagram

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

Illuminance-Distance Curve



Beam Angle:25.3

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Indoor Luminance Limiting Curves

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13


Glare Grade Table

GI	Quality	Using Illuminace							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	128912	47143	17562	10545	6190	4436	2561	515	0
C90	66742	18367	11473	6970	4312	2491	1299	811	0

Luminance Limiting Curve




Luminous Size: Length(m)=-0.041 Width(m)=-0.041 Height(m)=0.000 Area(m^2)=0.001320
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Indoor Budgetary Estimate Table

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Indoor Coefficient of Utilization Table

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC(%)	80				70				50			30			10			0
RhoW(%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94
2	108	103	99	96	106	102	98	95	98	96	93	95	93	91	93	91	89	87
3	103	97	92	88	101	95	91	87	93	89	86	90	87	84	88	85	83	82
4	98	91	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	71
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	69	67
7	85	76	70	66	83	75	70	66	74	69	65	73	68	65	71	68	65	63
8	81	72	66	62	80	71	66	62	70	65	62	69	65	61	68	64	61	60
9	77	68	62	59	76	68	62	58	67	62	58	66	61	58	65	61	58	57
10	74	65	59	56	73	64	59	56	64	59	55	63	58	55	62	58	55	54

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Unified Glare Rating Table

Lum.Name: MD21-06-XX-02 2700K RA90 25D	Lum.Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Qualty Departmnt
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/10/13

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	24.5	25.6	24.9	25.9	26.2	22.9	24.0	23.3	24.3	24.6
	Y=3H	24.4	25.3	24.7	25.7	26.0	22.8	23.7	23.1	24.1	24.4
	Y=4H	24.3	25.2	24.7	25.5	25.9	22.7	23.6	23.1	23.9	24.3
	Y=6H	24.2	25.0	24.6	25.4	25.8	22.5	23.4	23.0	23.8	24.1
	Y=8H	24.1	24.9	24.5	25.3	25.7	22.5	23.3	22.9	23.7	24.1
	Y=12H	24.0	24.8	24.5	25.2	25.6	22.4	23.2	22.9	23.6	24.0
X=4H	Y=2H	24.3	25.2	24.7	25.5	25.9	22.7	23.6	23.1	23.9	24.3
	Y=3H	24.1	24.8	24.5	25.2	25.6	22.5	23.2	22.9	23.6	24.0
	Y=4H	24.0	24.6	24.4	25.1	25.5	22.4	23.0	22.8	23.5	23.9
	Y=6H	23.8	24.4	24.3	24.9	25.4	22.2	22.8	22.7	23.3	23.8
	Y=8H	23.8	24.3	24.3	24.8	25.3	22.2	22.7	22.6	23.2	23.7
	Y=12H	23.7	24.2	24.2	24.7	25.2	22.1	22.6	22.6	23.1	23.6
X=8H	Y=4H	23.8	24.3	24.3	24.8	25.3	22.2	22.7	22.6	23.2	23.7
	Y=6H	23.7	24.1	24.2	24.6	25.1	22.0	22.5	22.6	23.0	23.5
	Y=8H	23.6	24.0	24.1	24.5	25.0	22.0	22.4	22.5	22.9	23.4
	Y=12H	23.5	23.9	24.0	24.4	25.0	21.9	22.3	22.4	22.8	23.4
X=12H	Y=4H	23.7	24.2	24.2	24.7	25.2	22.1	22.6	22.6	23.1	23.6
	Y=6H	23.6	24.0	24.1	24.5	25.0	22.0	22.4	22.5	22.9	23.4
	Y=8H	23.5	23.9	24.0	24.4	25.0	21.9	22.3	22.4	22.8	23.4
Variations with the objerver position at spacings											
S=1.0H		1.7/-2.4					1.0/-1.2				
S=1.5H		2.5/-3.7					2.3/-2.6				
S=2.0H		3.3/-5.1					3.8/-5.3				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.0					0.0				

o the CIE Pub.117,data has been corrected,refers to the lamp's lumens 8.2flm.

IES Indoor Report
Photometric Filename:MD21-06-XX-02 2700K RA90 25D.IES

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1296.97	1296.97	1296.97	1296.97
γ 5.0	1298.82	1222.03	989.91	1236.50
γ 10.0	1079.39	882.33	604.33	877.73
γ 15.0	704.02	511.17	350.68	493.26
γ 20.0	402.43	314.34	257.01	305.69
γ 25.0	280.07	247.59	216.68	240.25
γ 30.0	232.76	212.93	190.65	207.66
γ 35.0	203.15	188.87	165.64	184.40
γ 40.0	178.93	145.25	90.42	149.20
γ 45.0	120.35	62.31	19.73	65.21
γ 50.0	40.01	15.59	8.69	12.42
γ 55.0	13.30	8.69	4.02	6.36
γ 60.0	6.96	4.60	1.39	3.73
γ 65.0	3.45	2.41	0.43	2.16
γ 70.0	2.00	1.13	0.00	0.59
γ 75.0	0.88	0.44	0.00	0.42
γ 80.0	0.12	0.19	0.00	0.04
γ 85.0	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 135.0	0.00	0.00	0.00	0.00
γ 140.0	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.00	0.00	0.00
γ 150.0	0.00	0.00	0.00	0.00
γ 155.0	0.00	0.00	0.00	0.00
γ 160.0	0.00	0.00	0.00	0.00
γ 165.0	0.00	0.00	0.00	0.00
γ 170.0	0.00	0.00	0.00	0.00
γ 175.0	0.00	0.00	0.00	0.00
γ 180.0	0.00	0.00	0.00	0.00