HCP-81XX2213 SERIES

13W Recessed LED Downlight

Aluminium · Black or White

13 W MAX WATTAGE	1089 lm UP TO
90+ CRI	60° BEAM ANGLE
<19 UGR	IP65 FRONT OF FITTING

WARRANTY T&CS

WEBSITE

Havit Commercial

www.havitcommercial.com.au · 02 9381 8383
sales@havitcommercial.com.au
8/133 Beauchamp Road, Matraville, N.S.W., 2036



ALUMINIUM BLACK

HCP-81222213 TRIAC
HCP-81242213 DALI



ALUMINIUM WHITE

HCP-81322213 TRIAC
HCP-81342213 DALI

TRIAC DIMMING

IP65 INDOOR/OUTDOOR WEATHERPROOF

IC-4

01 PRODUCT SPECIFICATIONS

MATERIAL	Aluminium
COLOUR / FINISH	Black or White
INSTALLATION TYPE	Ceiling – Recessed
CUT OUT	Ø80mm
COLOUR TEMP	2700K · 3000K · 4000K · 5000K · 5700K
LUMENS	980lm · 965lm · 959lm · 1072lm · 1089lm
INPUT VOLTAGE	240V (supplied with flex & plug)
PROTECTION CLASS	2 (no earth required)
LAMP BASE	Built in LED
MAX WATTAGE	13W
DIMMING	TRIAC or DALI 2
CRI	90+
BEAM ANGLE	60° (other beam angles available)
IP RATING	IP65 (front of fitting only)
IK RATING	IK02
LAMP EXPECTANCY	>50,000hrs*
SDCM	<3
UGR	<19
IC RATING	IC-4
TILT	No tilt
WARRANTY	5 years replacement*

02 PRODUCT ORDERING


	ORDER CODE	FINISH	LAMP	DIMMING	BARCODE
	**HCP-81222213**	Aluminium Black	13W built in LED · 5 colour	TRIAC dimmable	9350418098337
	**HCP-81242213**	Aluminium Black	13W built in LED · 5 colour	DALI dimmable	9350418098474
	**HCP-81322213**	Aluminium White	13W built in LED · 5 colour	TRIAC dimmable	9350418098405
	**HCP-81342213**	Aluminium White	13W built in LED · 5 colour	DALI dimmable	9350418098542

SELECTABLE COLOUR TEMP

- **2700K** 980lm
- **3000K** 965lm
- **4000K** 959lm
- **5000K** 1072lm
- **5700K** 1089lm

03 DIMENSIONS

CUT OUT = Ø80MM




*See Warranty Terms & Conditions for more information.

04 BEAM ANGLE OPTIONS

BEAM DIAMETER AT FLOOR LEVEL*

60°


Standard optic
SUPPLIED AS STANDARD



2.4 m ceiling	**Ø2.77 m**
2.7 m ceiling	**Ø3.12 m**
3.0 m ceiling	**Ø3.46 m**

40°


HCP-80090-40
OPTIONAL REFLECTOR



2.4 m ceiling	**Ø1.75 m**
2.7 m ceiling	**Ø1.97 m**
3.0 m ceiling	**Ø2.18 m**

28°


HCP-80090-28
OPTIONAL REFLECTOR



2.4 m ceiling	**Ø1.20 m**
2.7 m ceiling	**Ø1.35 m**
3.0 m ceiling	**Ø1.50 m**


15°

HCP-80090-15
OPTIONAL REFLECTOR



2.4 m ceiling	**Ø0.63 m**
2.7 m ceiling	**Ø0.71 m**
3.0 m ceiling	**Ø0.79 m**

05 PHOTOMETRICS




06 COLOUR TEMP



2700K | 3000K | 4000K | 5000K | 5700K


Selectable colour temperature at the back of the module.

07 INSTALLATION




01
ISOLATE POWER

Turn off the supply at the switchboard before installing or servicing.




02
CUT THE CEILING

Cut a Ø80mm hole. Check the ceiling void is clear of joists, pipes and cables.



03
SET COLOUR TEMP


Slide the switch on the back of the module to the required colour temperature.



04
CONNECT & INSERT

Plug the driver flex into the ceiling socket. Hold the spring clips upright, push the fitting in and release.

08 TYPICAL INSTALLATION SECTION VIEW



IC-4 rated. Spring clips bear on the top of the ceiling lining; the external driver connects by flex and plug to a ceiling socket outlet.

09 INSTALLATION NOTES

01 Installation must be carried out by a licensed electrician in accordance with AS/NZS 3000.

02 External LED driver with flex & plug for connection to a ceiling socket outlet. Class 2 – no earth required.

03 Allow a minimum 115mm clear ceiling void (fitting height 112mm).

04 IC-4 rated: building insulation rated for continuous exposure to 90°C may abut and cover the fitting.

05 IP65 applies to the front of the fitting only – the rear must sit in a dry ceiling space.

06 TRIAC models: use a compatible trailing-edge dimmer. DALI models require a DALI-2 control system.

07 Optional reflectors are sold separately – fit the chosen reflector before installing the downlight.

08 Clean with a soft dry cloth only. Do not use solvents or abrasive cleaners.

*Beam diameters are calculated from the nominal beam angle (50% peak intensity) and are indicative only. See Warranty Terms & Conditions for more information.