HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel: 02 9381 8383
E-mail:sales@havitcommercial.com.au

Report No.: 001 Test Time: 2019-04-01 10:23


Luminaire Property

Luminaire Manufacturer:
Luminaire Category: Outdoor lighting
Luminaire Description: HCP-8931201-5500K
Lamp Catalog: COB
Luminous Length (mm): -80
Luminous Width (mm): -80
Luminous Height (mm): 0
Voltage: 230.5 V
Current: 0.115 A
Power: 13.12 W
Power Factor: 0.495


Photometric Results

CIE Class: Direct
Total Rated Lamp Lumens: 1274.7 lm
Measurement Flux: 1274.7 lm
Efficiency: 100%
Downward Ratio: 100%
Upward Ratio: 0%
Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 80.2, 80.2, 80.2, 80.3
Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 57.0, 57.1, 56.9, 57.5
Luminaire Efficacy Rating (LER): 97.20
Central Intensity: 1519.11 cd
Max. Intensity: 1519.11 cd
Pos of Max. Intensity: H0 V0
S/MH(C0/C180): 0.90
S/MH(C90/C270): 0.90

Picture Of Luminaire




Luminous Intensity Distribution Curve




C Plane (°):0.0-360.0: 30.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Device: GPM-1600L
Test Type: TYPE C
Distance: 6.583 m
Temperature: 25°C
Humidity:
Operator: DING LI
Inspector:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel: 02 9381 8383
E-mail:sales@havitcommercial.com.au

Luminous Intensity Distribution Curve






C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel: 02 9381 8383
E-mail:sales@havitcommercial.com.au

IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 60.8 lx


(1%): 0.6 lx	(2%): 1.2 lx
(5%): 3.0 lx	(10%): 6.1 lx
(20%): 12.2 lx	(50%): 30.4 lx
(100%): 60.8 lx	

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

HAVIT COMMERCIAL
http://www.havitcommercial.com.au
Tel: 02 9381 8383
E-mail:sales@havitcommercial.com.au

Illuminance at a Distance



Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	1519.11	1.09/1.09	0.9	568.89
2.0	379.78	2.17/2.18	3.7	142.22
3.0	168.79	3.26/3.27	8.4	63.21
4.0	94.94	4.34/4.36	14.9	35.56
5.0	60.76	5.43/5.45	23.3	22.76

Beam Angle(B): H57.0 V57.1 Field Angle(F): H80.2 V80.2

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

UGR Table

Reflectance: Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	18.5	19.4	18.8	19.6	19.8	19.0	19.8	19.2	20.0	20.2
3H	18.4	19.2	18.7	19.4	19.6	18.8	19.6	19.1	19.8	20.1
4H	18.3	19.0	18.6	19.3	19.6	18.8	19.5	19.1	19.7	20.0
6H	18.2	18.9	18.6	19.2	19.5	18.7	19.3	19.0	19.6	19.9
8H	18.2	18.8	18.6	19.1	19.4	18.6	19.3	19.0	19.6	19.9
12H	18.2	18.8	18.5	19.1	19.4	18.6	19.2	19.0	19.5	19.8
X=4H Y=2H	18.3	19.0	18.6	19.3	19.6	18.8	19.5	19.1	19.7	20.0
3H	18.2	18.8	18.5	19.1	19.4	18.6	19.2	19.0	19.5	19.8
4H	18.1	18.6	18.5	19.0	19.3	18.5	19.1	18.9	19.4	19.8
6H	18.0	18.5	18.4	18.9	19.2	18.5	18.9	18.9	19.3	19.7
8H	18.0	18.4	18.4	18.8	19.2	18.4	18.8	18.8	19.2	19.6
12H	17.9	18.3	18.4	18.7	19.2	18.4	18.8	18.8	19.2	19.6
X=8H Y=4H	18.0	18.4	18.4	18.8	19.2	18.4	18.8	18.8	19.2	19.6
6H	17.9	18.2	18.3	18.7	19.1	18.3	18.7	18.8	19.1	19.6
8H	17.8	18.1	18.3	18.6	19.1	18.3	18.6	18.8	19.0	19.5
12H	17.8	18.1	18.3	18.5	19.0	18.2	18.5	18.7	19.0	19.5
X=12H Y=4H	17.9	18.3	18.4	18.7	19.2	18.4	18.8	18.8	19.2	19.6
6H	17.8	18.1	18.3	18.6	19.1	18.3	18.6	18.8	19.0	19.5
8H	17.8	18.1	18.3	18.5	19.0	18.2	18.5	18.7	19.0	19.5
Variations with the observer position at spacings:										
S=1.0H	+5.4/-12.9					+5.3/-12.7				
S=1.5H	+8.2/-14.8					+8.1/-14.3				
S=2.0H	+10.2/-16.7					+10.1/-16.2				

Calculate in accordance with CIE Pub.117. The table is revised with 1275lm (8log(F/F0) = 0.8).

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G0.0	1519.1	1517.1	1515.0	1513.1	1512.6	1509.9	1519.1	1517.1	1515.0	1513.1
G1.0	1514.9	1512.5	1510.7	1506.8	1503.8	1500.3	1517.4	1517.2	1515.7	1514.6
G2.0	1505.2	1504.4	1502.2	1498.1	1495.0	1490.8	1510.7	1512.2	1510.0	1509.9
G3.0	1495.7	1494.3	1492.3	1486.9	1484.5	1483.0	1502.5	1504.4	1498.3	1496.5
G4.0	1484.1	1484.5	1483.8	1477.5	1474.7	1475.4	1496.8	1495.6	1487.3	1481.9
G5.0	1472.3	1472.3	1472.8	1467.0	1465.5	1466.3	1488.6	1484.4	1474.4	1467.5
G6.0	1458.1	1459.4	1460.9	1454.3	1451.7	1454.3	1479.4	1471.7	1459.9	1451.8
G7.0	1445.5	1449.0	1452.3	1447.5	1440.6	1443.9	1466.4	1461.3	1449.2	1443.5
G8.0	1439.3	1443.4	1447.4	1443.0	1433.1	1436.7	1455.3	1451.2	1441.4	1438.1
G9.0	1433.5	1438.3	1445.2	1440.4	1431.1	1432.5	1448.1	1443.0	1436.8	1433.9
G10.0	1425.1	1433.3	1438.7	1433.2	1430.4	1433.1	1444.5	1438.2	1434.3	1433.0
G11.0	1412.4	1420.8	1425.7	1420.8	1423.3	1427.3	1438.6	1429.2	1429.2	1430.4
G12.0	1396.1	1405.3	1409.7	1406.2	1411.7	1415.3	1428.5	1419.8	1421.3	1426.3
G13.0	1375.8	1384.8	1389.0	1387.7	1396.5	1398.7	1416.6	1409.8	1411.9	1414.9
G14.0	1348.7	1356.8	1364.8	1364.8	1375.3	1377.0	1398.6	1395.8	1396.3	1395.8
G15.0	1323.0	1332.8	1335.6	1341.2	1352.7	1352.3	1377.6	1374.1	1374.0	1372.3
G16.0	1302.6	1305.6	1308.1	1313.4	1329.4	1325.3	1348.8	1349.0	1348.2	1348.8
G17.0	1274.5	1281.5	1280.2	1288.3	1302.2	1300.0	1325.4	1320.7	1322.2	1325.1
G18.0	1243.7	1253.3	1256.7	1265.7	1279.9	1278.6	1303.3	1296.0	1294.1	1297.7
G19.0	1204.2	1214.9	1223.2	1237.2	1255.6	1254.3	1282.4	1268.7	1259.9	1262.1
G20.0	1162.1	1176.4	1190.8	1206.3	1227.3	1226.5	1260.3	1237.9	1224.7	1223.4
G21.0	1115.3	1126.4	1152.5	1167.1	1194.5	1192.5	1228.8	1204.2	1184.6	1183.0
G22.0	1056.7	1079.6	1102.8	1124.7	1151.1	1153.7	1190.6	1158.2	1136.3	1130.2
G23.0	998.4	1023.6	1055.1	1076.5	1105.3	1104.9	1149.5	1114.9	1086.0	1076.5
G24.0	936.0	959.8	995.3	1021.7	1049.4	1047.1	1091.4	1064.0	1022.0	1014.5
G25.0	882.4	900.0	938.9	967.6	994.5	987.5	1034.2	997.7	966.7	949.4
G26.0	827.6	842.9	882.5	908.7	935.9	927.3	969.7	937.5	909.6	890.9
G27.0	772.6	786.3	820.7	847.7	875.2	868.5	903.0	873.0	850.4	829.0
G28.0	726.5	738.1	770.0	795.3	824.3	820.6	846.4	823.0	799.5	777.2
G29.0	684.2	687.7	720.1	744.6	776.3	772.7	793.3	773.8	744.8	727.3
G30.0	627.0	646.9	670.0	697.6	728.6	728.8	746.0	722.0	697.1	676.1
G31.0	570.1	587.9	625.5	651.4	683.6	685.2	701.8	677.4	653.8	628.1
G32.0	525.8	541.4	571.8	597.6	631.4	633.6	652.9	629.7	586.8	561.0
G33.0	492.0	504.4	527.8	551.5	582.7	585.0	606.5	583.6	542.1	522.3
G34.0	461.6	470.6	492.0	511.6	537.4	538.3	565.1	541.3	502.9	488.2
G35.0	428.0	439.0	459.3	477.2	495.9	496.4	521.7	501.7	469.0	457.8
G36.0	371.0	395.1	431.9	450.5	463.9	463.9	488.0	471.4	442.1	431.1

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G37.0	301.3	322.2	378.1	407.1	434.1	427.2	457.8	442.0	396.5	379.6
G38.0	214.4	244.5	302.8	340.0	368.0	364.0	412.9	382.3	332.5	301.5
G39.0	141.9	166.8	223.8	261.0	292.5	290.3	342.2	307.6	255.7	224.6
G40.0	75.2	95.3	144.8	176.2	209.1	202.2	256.6	220.5	169.8	140.5
G41.0	39.2	48.0	81.1	107.4	133.8	131.2	178.5	147.4	103.8	80.1
G42.0	31.3	32.9	40.9	57.0	74.9	71.1	107.4	84.6	53.9	40.1
G43.0	27.6	28.7	31.2	34.1	37.3	36.1	54.0	41.0	33.0	30.1
G44.0	24.5	25.7	27.7	30.3	31.8	31.3	34.1	33.1	29.4	27.0
G45.0	21.7	22.4	24.6	26.5	28.3	27.9	30.4	29.5	26.2	24.2
G46.0	18.5	19.5	21.7	23.6	25.0	25.1	27.4	26.4	23.4	21.5
G47.0	16.8	17.4	18.9	20.8	22.3	22.5	24.8	23.5	20.9	18.8
G48.0	15.5	15.9	16.7	17.9	19.0	19.6	21.7	20.5	18.3	16.9
G49.0	14.2	14.7	15.5	16.3	17.0	17.5	19.1	18.5	17.0	15.7
G50.0	13.0	13.4	14.2	14.9	15.6	16.1	17.3	16.8	15.6	14.5
G51.0	11.9	12.3	12.9	13.6	14.1	14.6	15.8	15.3	14.2	13.2
G52.0	10.9	11.3	11.9	12.4	12.9	13.2	14.6	14.0	13.0	12.3
G53.0	10.1	10.3	10.8	11.2	11.9	12.2	13.3	12.8	12.0	11.2
G54.0	9.2	9.6	9.9	10.2	10.8	11.0	12.2	11.7	11.0	10.3
G55.0	8.6	8.8	9.1	9.5	9.9	10.1	11.2	10.8	10.3	9.6
G56.0	7.8	8.0	8.3	8.6	9.0	9.2	10.2	9.9	9.4	8.7
G57.0	7.2	7.4	7.7	8.0	8.3	8.4	9.4	9.1	8.7	8.0
G58.0	6.5	6.8	7.0	7.3	7.6	7.8	8.7	8.4	8.0	7.4
G59.0	5.9	6.1	6.4	6.6	7.0	7.1	7.9	7.6	7.3	6.7
G60.0	5.4	5.6	5.8	6.1	6.4	6.5	7.3	7.0	6.7	6.2
G61.0	4.9	5.1	5.3	5.5	5.9	5.9	6.5	6.4	6.0	5.6
G62.0	4.4	4.6	4.8	5.1	5.3	5.4	6.0	5.8	5.5	5.1
G63.0	4.0	4.1	4.4	4.5	4.9	4.9	5.6	5.4	5.0	4.6
G64.0	3.5	3.8	3.9	4.1	4.4	4.5	5.1	4.8	4.5	4.2
G65.0	3.1	3.3	3.5	3.8	4.0	4.1	4.5	4.5	4.1	3.8
G66.0	2.8	2.9	3.1	3.3	3.7	3.7	4.2	4.1	3.7	3.4
G67.0	2.4	2.6	2.8	2.9	3.3	3.3	3.8	3.5	3.2	3.0
G68.0	2.2	2.3	2.4	2.6	2.9	2.9	3.3	3.1	2.9	2.7
G69.0	1.9	2.1	2.2	2.3	2.5	2.6	2.9	2.8	2.5	2.4
G70.0	1.6	1.8	1.9	2.1	2.2	2.3	2.6	2.5	2.3	2.1
G71.0	1.4	1.4	1.6	1.8	2.0	2.0	2.3	2.3	2.0	1.9
G72.0	1.1	1.2	1.3	1.5	1.8	1.7	2.0	1.9	1.8	1.6
G73.0	1.0	1.0	1.1	1.2	1.5	1.5	1.8	1.6	1.5	1.3

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G74.0	0.7	0.8	0.9	1.1	1.3	1.2	1.5	1.5	1.3	1.1
G75.0	0.5	0.5	0.7	0.9	1.0	1.0	1.3	1.2	1.1	0.9
G76.0	0.3	0.4	0.5	0.6	0.8	0.6	1.1	1.0	0.8	0.6
G77.0	0.2	0.2	0.2	0.4	0.5	0.5	0.8	0.8	0.6	0.4
G78.0	0.0	0.1	0.1	0.2	0.3	0.3	0.6	0.5	0.3	0.2
G79.0	0.0	0.0	0.0	0.0	0.2	0.0	0.4	0.4	0.1	0.0
G80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2	0.2	0.1	0.0
G81.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.0	0.0
G82.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G83.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G84.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G89.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C300.0	C330.0	C360.0							
G0.0	1512.6	1509.9	1519.1							
G1.0	1513.3	1512.4	1514.9							
G2.0	1507.3	1507.6	1505.2							
G3.0	1494.4	1495.7	1495.7							
G4.0	1480.4	1485.1	1484.1							
G5.0	1466.9	1473.4	1472.3							
G6.0	1454.8	1460.7	1458.1							
G7.0	1444.9	1449.4	1445.5							
G8.0	1437.2	1439.7	1439.3							
G9.0	1435.7	1434.2	1433.5							
G10.0	1434.6	1430.6	1425.1							
G11.0	1431.5	1425.5	1412.4							
G12.0	1422.8	1415.3	1396.1							
G13.0	1407.6	1398.3	1375.8							
G14.0	1383.7	1373.0	1348.7							
G15.0	1360.2	1348.6	1323.0							
G16.0	1334.0	1325.1	1302.6							
G17.0	1308.0	1298.3	1274.5							
G18.0	1275.3	1270.2	1243.7							
G19.0	1237.3	1234.6	1204.2							
G20.0	1200.3	1196.6	1162.1							
G21.0	1156.8	1156.1	1115.3							
G22.0	1103.2	1100.3	1056.7							
G23.0	1047.5	1042.6	998.4							
G24.0	983.9	988.5	936.0							
G25.0	923.8	922.9	882.4							
G26.0	866.1	870.6	827.6							
G27.0	806.8	810.7	772.6							
G28.0	757.1	762.9	726.5							
G29.0	707.9	716.5	684.2							
G30.0	662.2	668.3	627.0							
G31.0	597.3	604.7	570.1							
G32.0	545.7	551.9	525.8							
G33.0	509.9	514.7	492.0							
G34.0	478.7	482.1	461.6							
G35.0	450.6	452.0	428.0							
G36.0	416.1	418.7	371.0							

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C300.0	C330.0	C360.0							
G37.0	348.8	359.4	301.3							
G38.0	271.0	276.1	214.4							
G39.0	194.7	198.9	141.9							
G40.0	113.5	117.3	75.2							
G41.0	58.2	60.9	39.2							
G42.0	33.0	32.6	31.3							
G43.0	28.7	28.5	27.6							
G44.0	25.8	25.6	24.5							
G45.0	22.6	22.8	21.7							
G46.0	19.9	19.8	18.5							
G47.0	17.4	17.3	16.8							
G48.0	16.1	15.9	15.5							
G49.0	15.0	14.7	14.2							
G50.0	14.0	13.6	13.0							
G51.0	12.7	12.5	11.9							
G52.0	11.6	11.4	10.9							
G53.0	10.6	10.6	10.1							
G54.0	9.9	9.7	9.2							
G55.0	9.1	8.9	8.6							
G56.0	8.4	8.2	7.8							
G57.0	7.7	7.5	7.2							
G58.0	7.0	6.9	6.5							
G59.0	6.4	6.2	5.9							
G60.0	5.9	5.7	5.4							
G61.0	5.3	5.3	4.9							
G62.0	4.8	4.7	4.4							
G63.0	4.3	4.3	4.0							
G64.0	3.9	3.9	3.5							
G65.0	3.5	3.5	3.1							
G66.0	3.1	2.9	2.8							
G67.0	2.8	2.6	2.4							
G68.0	2.5	2.3	2.2							
G69.0	2.2	2.1	1.9							
G70.0	1.9	1.9	1.6							
G71.0	1.6	1.5	1.4							
G72.0	1.4	1.3	1.1							
G73.0	1.1	1.0	1.0							

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector:

Candlepower Table (Continue 5)

Unit: cd

G\C	C300.0	C330.0	C360.0							
G74.0	0.8	0.9	0.7							
G75.0	0.7	0.5	0.5							
G76.0	0.5	0.3	0.3							
G77.0	0.3	0.1	0.2							
G78.0	0.1	0.0	0.0							
G79.0	0.0	0.0	0.0							
G80.0	0.0	0.0	0.0							
G81.0	0.0	0.0	0.0							
G82.0	0.0	0.0	0.0							
G83.0	0.0	0.0	0.0							
G84.0	0.0	0.0	0.0							
G85.0	0.0	0.0	0.0							
G86.0	0.0	0.0	0.0							
G87.0	0.0	0.0	0.0							
G88.0	0.0	0.0	0.0							
G89.0	0.0	0.0	0.0							
G90.0	0.0	0.0	0.0							

C Plane (°):0.0-360.0: 30.0
Test Lab: NINGBO LED LIGHTING CO.,LTD.
Test Type: TYPE C
Temperature: 25°C
Operator: DING LI

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 6.583 m
Humidity:
Inspector: